View NSN Online: https://aerobasegroup.gr/nsn/5915-00-944-6257 FILTRON CO INC -- FA9201 -- 5915-00-944-6257 Product ID:FA9201 MSDS Date:01/01/1985 FSC:5915 NIIN:00-944-6257 MSDS Number: BFYNZ === Responsible Party === Company Name: FILTRON CO INC Address:148 SWEET HOLLOW RD City:OLD BETHPAGE State:NY ZIP:11804-1315 Country:US **Emergency Phone Num:NONE** CAGE:81831 === Contractor Identification === Company Name: FILTRON CO INC Add ress:148 SWEET HOLLOW RD Box:City:OLD BETHPAGE State:NY ZIP:11804-1315 Country:US Phone:914-699-2000 CAGE:81831 ======= Composition/Information on Ingredients ======== Ingred Name: POLYCHLORINATED BIPHENYLS (PCBS) (SARA III) CAS:1336-36-3 RTECS #:TQ1350000 EPA Rpt Qty:1 LB DOT Rpt Qty:1 LB ========== Hazards Identification =============== Effects of Overexposure: INHAL: RESP TK IRRIT; SKIN/EYE;IRRIT,INFLAM,CHLORACNE; MAY CAUSE LIVER DAMAGE

First Aid:INHAL:RMV TO FRESH AIR. IF NOT BRTHNG GIVE CPR. IF BRTHNG DIFF,GIVE OXYGEN. EYE:IMMED FLUSH W/PLENTY OF WATER. SKIN:WASH W/SOAP&WATER. RMV CONTAM CLTHNG&SHOES. INGEST:INDUCE VOMIT. RPT UNTIL VOMIT IS CLEAR. NOTHG BY MOUTH IF UNCONSC. GET MEDICAL ATTN
=========== Fire Fighting Measures =============
Flash Point:NONE Extinguishing Media:EXTINQUISH W. AGENT SUITABLE FOR SURROUNDING FIRE. Fire Fighting Procedures:WEAR CHEMICAL PROTECTIVE SUIT WITH SELF CONTD BRTHG APP. Unusual Fire/Explosion Hazard:MATL IS NON-FLAMMABLE BUT MAY GENERATE TOXIC GASES IN HEAT OF FIRE.
========== Accidental Release Measures ==========
Spill Release Procedures:EVAC N0N-ESSENTL PESONNEL. VENT SPIL AREA. WEAR PROTECT EQUIPT. STOP LEAK. SOAK UP LIQUID W/NON-REACTIVE MATL (SAND, DIRT, ETC) OR RMV BY DIKE & PUMPING OR OTHER SUITABLE MEANS. CLEAN AREA W/SUITABLE SAFETY SOLVENT. LA UNDER CONTAMINATED CLOTHING.
=========== Handling and Storage ============
Handling and Storage Precautions:STORE IN COOL,DRY,WELL VENTILATED AREA. PROTECT FROM PHYSICAL DAMAGE.AVOID ANY PHYSICAL CONTACT. KEEP CONTAINERS TIGHTLY CLOSED Other Precautions:CHLORODIPHENYLS MAY ATTACK SOME TYPES OF RUBBER AND PLASTIC. DO NOT USE CONTAMINATED WORK CLOTHING. WASH/SHOWER AFTER EXPOSURE TO PCB'S.
===== Exposure Controls/Personal Protection ====================================
Respiratory Protection:NIOSH/MESA APPR SCBA/AIR SUPP RESPIR. Ventilation:LOCAL EXHAUST TO MAINTN BELOW TLV. Protective Gloves:IMPERVIOUS Eye Protection:GOGGLES/FACE SHIELD Other Protective Equipment:WEAR FULL PROTECTIVE CLOTHING. Supplemental Safety and Health OVEREXPOS:CAN CAUSE FORMATION OF CYSTS,CAUSES STILLBIRTHS.IRRITATES EYES,NOSE THROAT.
========= Physical/Chemical Properties ==========
HCC:Z3 Solubility in Water:NEGLIGIBLE Appearance and Odor:PALE YELLOW VIS

===== First Aid Measures ==========

COUS LIQUID W/HYDROCARBON ODOR

=======================================	Stability and	Reactivity Data	
===========	Stability and	Reactivity Data	===========

Stability Indicator/Materials to Avoid:YES STRONG OXIDIZING AGENTS. Stability Condition to Avoid:SEE OTHER PRECAUTIONS Hazardous Decomposition Products:HYDROGEN CHLORIDE, CO, & OTHER TOXIC/IRRITATING GASES/FUMES.

======= Disposal Considerations ===========

Waste Disposal Methods:CONTROLLED DISOPSAL REQD. GEN. V.HIGH TEMP INCINERATION. IAW ALL LOCAL, STATE, & FEDE RAL REGULATIONS.

PERMITTED DISPOSAL OPERATOR REQUIRED.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.