

CONVOY OIL CORPORATION -- MIL-L-46150,LUBRICATING OIL -- 9150-00-949-0323

=====
Product Identification
=====

Product ID:MIL-L-46150,LUBRICATING OIL

MSDS Date:01/01/1985

FSC:9150

NIIN:00-949-0323

MSDS Number: BFY TZ

=== Responsible Party ===

Company Name:CONVOY OIL CORPORATION

Emergency Phone Num:(215) 739-5281

CAGE:CONVY

=== Contractor Identification ===

Company Name:CONVOY OIL CORP

Address:1410 N

FRONT STREET

Box:29366

City:PHILADELPHIA

State:PA

ZIP:19125

Country:US

Phone:215-739-5281

CAGE:6A438

Company Name:CONVOY OIL CORPORATION

CAGE:CONVY

=====
Composition/Information on Ingredients
=====

Ingred Name:LITHIUM STEARATE DIESTER (LUBRICATING OIL)

Fraction by Wt: 75%

Ingred Name:POLYTETRAFLUOROETHYLENE (TEFLON)

CAS:116-14-3

RTECS #:KX4025000

Fraction by Wt: 25%

ACGIH TLV:SEE ACGIH-B1

=====
Hazards Identification
=====

Effects of Ove

reexposure:SLIGHT TO MODERATE IRRITATION OF SKIN/WYES,MINIMIZE SKIN CONTCT.USE GOOD HYGIENE.

=====
First Aid Measures
=====

First Aid:INHAL-DOES NOT GEVE OFF HARMFUL CONC VAPOR EXCEPT AT HI TEMP.INGEST-DO NOT INDUCE VOMIT-GIVE 1/2 PT MILK OR WATER & OBTAIN MEDICAL ATTN.ASPIRATION-GET MEDICAL ATTN.EYES-WASH WITH COPIOUS QUANTITIES WAT ER

=====
Fire Fighting Measures
=====

Flash Point:NONE

Extinguishing Media

:CO*2, FOAM, DRY CHEM.

Fire Fighting Procedures:DO NOT USE WATER JETS USE AIR SUPP BREATHING GEAR IN ENCLOS

Unusual Fire/Explosion Hazard:NONE

=====
Accidental Release Measures
=====

Spill Release Procedures:ABSORB WITH CLAY,DIATOMACEOUS EARTH,OR OTHER INERT ABSORBENT.SHOULD NOT CONTAMINATE DRAINAGE SYSTEMS,RIVERS,OR WATERWAYS.

=====
Handling and Storage
=====

Handling and Storage Precautions:FOLLOW NORMAL GOOD HOUSEK EEPING

PROCEDURES & QUALITY CONTROL REQUIREMENTS

Other Precautions:WASH HANDS THOROUGHLY WITH SOAP & WARM WATER BEFORE HANDLING FOOD OR SMOKING.

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection:AIR SUPPLIED BREATHING EQUIPMENT IF OIL MIST IS GENERATED

Ventilation:MECHANICAL(GENERAL) RECOMMENDED,LOCAL EXHAUST IF NEEDED

Protective Gloves:AS REQUIRED

Eye Protection:GOGGLES-IF OIL IS SPRAYED

Other Protective Equipment:AS REQUIRED TO PREVENT PRO

LONGED CONTACT.
Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:V6
Boiling Pt:B.P. Text:NO DATA-MIX
Spec Gravity:9000
Appearance and Odor:NO INFO AVAILABLE

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
STRONG OXIDIZING AGENTS SUCH AS LIQUID OXYGEN
Stability Condition to Avoid:EXTREME HEAT
Hazardous Decomposition Products:SMOKE,FUMES,CARBON MONOXIDE DURING
COMB OR PAST
FLASHPOINT

===== Disposal Considerations =====

Waste Disposal Methods:CONTROLLED BURNING,OR DISPOSAL CONFORMING TO
LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person
utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.