View NSN Online: https://aerobasegroup.gr/nsn/5970-00-997-6347

VARFLEX CORPORATION -- SYNTHOLVAR 120/210 -- 5970-00-997-6347

Product ID:SYNTHOLVAR 120/210 MSDS Date:10/01/1985 FSC:5970 NIIN:00-997-6347 **MSDS Number: BGCLM** === Responsible Party === Company Name: VARFLEX CORPORATION Address:512 WEST COURT STREET City:ROME State:NY ZIP:13440 Country:US Info Phone Num:315-336-4400 Emergency Phone Num:315-336-4400 CAGE:79074 === Co ntractor Identification === Company Name: VARFLEX CORPORATION Address:512 WEST COURT STREET Box:City:ROME State:NY ZIP:13440 Country:US Phone:315-336-4400 CAGE:79074 Ingred Name: PLASTICIZED POLYVINYL CHLORIDE RESIN

Ingred Name:ADDITIVES (INCLUDES 5% PIGMENTS) CAS:24937-78-8 Fraction by Wt: 5.5%

Routes of Entry: Inhalation:NO Skin:NO Ingestion:NO Reports o

 f Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:ACUTE: NONE SPECIFIED BY MANUFACTURER. CHRONIC: NONE SPECIFIED BY MANUFACTURER. Explanation of Carcinogenicity:MATERIAL IS NOT CONSIDERED AS A CARCINOGEN BY NTP, IARC OR OSHA Effects of Overexposure:NONE SPECIFIED BY MANUFACTURER. Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.
======================================
First Aid:IF VAPORS FROM HIGH TEMPERATURES AR E INHALED, REMOVE TO FRESH AIR.
======================================
Autoignition Temp:Autoignition Temp Text:NONE Extinguishing Media:WATER Fire Fighting Procedures:NO SPECIAL REQUIREMENTS. Unusual Fire/Explosion Hazard:HYDROGEN CHLORIDE GAS LIBERATED DURING COMBUSTION AND AT 500F AND ABOVE.
======================================
Handling and Storage Precautions:DO NOT EXPOSE TO SUNLIGHT. STORE BELOW 70 DEG. F. Other P recautions:NONE
======================================
Respiratory Protection:NONE REQUIRED. Ventilation:MECHANICAL(GENERAL) RECOMMENDED. Protective Gloves:NONE Eye Protection:NONE Other Protective Equipment:NONE Work Hygienic Practices:WASH AND SHOWER NORMALLY AT THE END OF A WORKDAY. Supplemental Safety and Health NONE
======================================

HCC:N1 Decomp Temp:Decomp Text:>500F,>260C Spec Gravity:1.19-1.41 Solub ility in Water:INS. Appearance and Odor:CLEAR PLASTIC INSULATION SLEEVING, 100 FOOT SPOOL. NO ODOR. Percent Volatiles by Volume:0

Stability Indicator/Materials to Avoid:YES

DIRECT CONTACT WITH SILVER AND COPPER UNDER CERTAIN CONDITIONS CAN CAUSE CORROSION.

Stability Condition to Avoid: TEMPERATURES OVER 400F.

Hazardous Decomposition Products: HYDROGEN CHLORIDE GAS IS LIBERATED DURING COMBUSTION AND AT 500F OR HIGHER.

Waste Disposal Methods: DISPOSE OF IAW LOCAL, STATE, FED. REGS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek com petent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.