View NSN Online: https://aerobasegroup.gr/nsn/9330-01-006-5310

Product ID:STEPANFOAM G-506-T MSDS Date:07/21/1987 FSC:9330 NIIN:01-006-5310 Kit Part:Y **MSDS Number: BGCTZ** === Responsible Party === Company Name: STEPAN COMPANY Address:22 W. FRONTAGE RD City:NORTHFIELD State:IL ZIP:60093-3407 Country:US Info Phone Num:312-446-7500 Emergency Phone Num:1-800-228-5635/312-446 -7500 CAGE:87570 === Contractor Identification === Company Name: STEPAN COMPANY Address: EDENS EXPY WINNETKA RD Box:City:WINNETKA State:IL ZIP:60093 Country:US Phone:800-228-5635, CHEMTREC 800-424-9300 CAGE:87570 Ingred Name: TOLUENE-2, 4-DIISOCYANATE (TDI) (SARA III) CAS:584-84-9 RTECS #:CZ6300000 Fraction by Wt: 75.0% OSHA PEL:C,0.02 PPM/0.02 STEL ACGIH TLV:0.005PPM/0.02STEL;93 EPA Rpt Qty:100 LBS DOT Rpt Qty:100 LBS

=======

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:YES Health Hazards Acute and Chronic: ACUTE: SEE SIGNS AND SYMPTOMS OF OVEREXPOSURE. CHRONIC:NOT ESTABLISHED. Explanation of Carcinogenicity: TOLUENE DIISOCYANATE IS A SUSPECTED HUMAN CARCINOGEN. Effects of Overexposure:EYE:PAIN,IRRITATION;SKIN:IRRITATION;INHALATION:MIST MAY IRRITATE NASAL PASSAGE; INGESTION: NAUSE A.ABDOMINAL PAIN. First Aid: EYES: FLUSH WITH PLENTY OF WATER; SKIN: REMOVE CONTAMINATED CLOTHING.WASH OF WITH WATER; INHALATION: REMOVE TO FRESH AIR. GIVE CPR/OXYGEN IF NEEDED; INGESTION: SEE DOCTOR IMMEDIATELY. Flash Point Method:SCC Flash Point:>200F/93C Lower Limits:1.0 Extinguishing Media:WATER SPRAY, FOAM, CARBON DIOXIDE, DRY CHEMICAL **EXTINGUISHER** Fire Fighting Procedures: WEAR SCBA AND PROTECTIVE CLOTHING Unusual Fire/Explosion Hazard: ONE IGNITED, THESE FOAMS MAY BURN RAPIDLY & PRODUCE INTENSE HEAT, DENSE MOKE & IRRIT TOXIC GASES. Spill Release Procedures: SOAK UP WITH ABSORBANT. SHOWER INTO APPROPIATE WASTE CONTAINER.FLUSH AREA WITH WATER. (1% AMMONIA MAY BE USED TO NEUTRALIZE SPILLS). (SPILLED MATERIAL IS SLIPPERY) Neutralizing Agent:1% AMMONIA. \_\_\_\_\_ Handling and Storage Precautions: STORE IN COOL, DRY WELL VENTILATED AREA, AWAY FROM HEAT, IGNITION SOURCES AND STRONG OXIDIZING AGENTS. Other Precautions: DO NOT POUR INTO DRAINS, AS SOLIDS THAT FORM WILL PLUG SEWERS. 

Respiratory Protection: IF AVOID ARE PRESENT, USE NIOSH/MSHA APPROVED RESPIRATOR FOR ORGANIC VAPORS, AIR-LINE RESPIRATOR OR SCBA. Ventilation: MECHANI CAL (GENERAL) AND/OR LOCAL EXHAUST TO KEEP BELOW TLV. Protective Gloves: IMPERVIOUS Eye Protection: FULL FACE SHIELD OR GOGGLES. Other Protective Equipment: WEAR PROTECTIVE CLOTHING TO PREVENT REPEATED OR PROLONGED CONTACT. EYE WASH STATION AND SAFETY SHOWER. Work Hygienic Practices: WASH THOROUGHLY AFTER HANDLING. REMOVE AND LAUNDER CONTAMINATED CLOTHING. Supplemental Safety and Health KIT CONSISTS OF 2 PARTS. FOR OTHER PART, SEE PNI A, SAME NSN. KEY1:T3. ======= Physi HCC:T3 Boiling Pt:B.P. Text:>200F/93C Vapor Density:>AIR Spec Gravity:1.22 Appearance and Odor:YELLOW LIQUID W/SWEET, FRUITY, PUNGENT ODOR. Percent Volatiles by Volume:0 Stability Indicator/Materials to Avoid:YES STRONG OXIDIZING AGENTS, WATER, ALCOHOLS, AMINES, ALKALIES, METAL CMPDS. Stability Condition to Avoid: EXPOSURE TO INTENSE HEAT SOURCES Hazardous Decomposition Products:CYANIDES & AMMONIA MAY BE FORMED. Waste Disposal Methods: DISPOSE IN A PERMITTED LANDFILL IN ACCORDANCE WITH ALL APPLICABLE FEDERAL, STATE AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and

disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.