

AIRCO WELDING PRODUCTS -- GMAW WIRE,TYPE A5356 -- 3439-01-012-6661

=====  
Product Identification  
=====

Product ID:GMAW WIRE,TYPE A5356

MSDS Date:01/01/1987

FSC:3439

NIIN:01-012-6661

MSDS Number: BGDHH

=== Responsible Party ===

Company Name:AIRCO WELDING PRODUCTS

Emergency Phone Num:(201)464-8100

CAGE:83923

=== Contractor Identification ===

Company Name:AIRCO WELDING PRODUCTS DIV OF THE BOC GROUP I  
NC.

Address:4437 E 49TH STRRET

City:CLEVELAND

State:OH

ZIP:44125-1005

Country:US

Phone:216-641-8790

CAGE:83923

Company Name:DIV OF THE BOC GROUP INC AIRCO INC

Address:575 MOUNTAIN AVENUE

Box:City:MURRAY HILL

State:NJ

ZIP:07974

Country:US

Phone:908-665-2400

CAGE:6S493

=====  
Composition/Information on Ingredients  
=====

Ingred Name:ALUMINUM (SARA III)

CAS:7429-90-5

RTECS #:BD0330000

Fraction by Wt: 94%

OSHA PEL:15MG/M3 DUST/5 FUME

ACGIH TLV:10MG/M3 DUST; 9192

Ingred Name:MAGNE

SIUM  
CAS:7439-95-4  
RTECS #:OM2100000  
Fraction by Wt: 5%

Ingred Name:CHROMIUM (SARA III)  
CAS:7440-47-3  
RTECS #:GB4200000  
Fraction by Wt: 0.1%  
OSHA PEL:1 MG/M3  
ACGIH TLV:0.5 MG/M3; 9192  
EPA Rpt Qty:1 LB  
DOT Rpt Qty:1 LB

Ingred Name:MANGANESE (SARA III)  
CAS:7439-96-5  
RTECS #:OO9275000  
Fraction by Wt: 0.1%  
OSHA PEL:(C) 5 MG/M3 DUST  
ACGIH TLV:5 MG/M3 DUST 9293

=====  
Hazards Identification =====

Effects of Overexposure:DIZZINESS,NAUSEA,OR DRYNESS OR IRRITATION O  
F  
NOSE,THROAT,OR EYES.

=====  
First Aid Measures =====

First Aid:INHALE:REMOVE TO FRESH AIR, GIVE CPR/O\*2 IF NEED;EYES:FLUSH W  
LG AMTS H\*2O FOR 15 MIN;SKIN:FLUSH W LG AMTS H\*2O;INGEST:RINSE  
MOUTH.

=====  
Fire Fighting Measures =====

Extinguishing Media:EXTINGUISH WITH AGENT SUITABLE FOR SURROUNDING FIRE  
Unusual Fire/Explosion Hazard:WELDING ARC AND SPARKS CAN IGNITE  
COMBUSTIBLE PRODUCTS

=====

Accidental Release Measures =====

Spill Release Procedures:CLEAN UP ANY GRINDING DUST OR WASTE RESIDUE AND PLACE IN SUITABLE DOT APPVD DISPOSAL CONTAINER.

===== Handling and Storage =====

Other Precautions:WELD IN WELL VENTILATED AREA.AVOID INHALATION OF WELDING FUMES.AVOID ELECTRICAL SHOCK BY MAINTAINING DRY WORK AREA.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:FUME RESP.OR AIR SUPPLIE D RESP.IN CONFINED SPACES.

Ventilation:MECHANICAL (GENERAL) ACCEPTABLE LOCAL EXHAUST IF NEEDED.

Protective Gloves:WELDER'S GLOVES

Eye Protection:FACE SHLD W.FILTER LENS.

Other Protective Equipment:APRON.LEGGINGS,BOOTS,CAPES,SHOULDR COVERS-SEE SUPPL.DATA-

Supplemental Safety and Health

MSDS DATED 11-15-79/HAZ.DECOMP:IN ARC WELDING SLIGHT NO\*2,AND

OZONE/OTHER PROTECTIVE EQUIPMENT:HARD HAT,SCREENS,LOW REFLECTIVITY WALLS OR BOOTHS/

===== Physical/Chemical Properties =

=====

HCC:N1

Appearance and Odor:ELECTRODE,WELDING

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

NONE

Hazardous Decomposition Products:FUME OF METALS&METAL OXIDES INCLUD.BASE MTL&COATNG-SEE SUPPL

===== Disposal Considerations =====

Waste Disposal Methods:KISPOSE IAW LOCAL,STATE & FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This i

nformation is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.