

EASTMAN KODAK COMPANY -- 101 3176;LIQUID DEVELOPER SYSTEM CLEANER;CONC;KAN 427808
-- 6750-01-026-9410

===== Product Identification =====

Product ID:101 3176;LIQUID DEVELOPER SYSTEM CLEANER;CONC;KAN 427808

MSDS Date:02/16/1994

FSC:6750

NIIN:01-026-9410

MSDS Number: BGFQT

=== Responsible Party ===

Company Name:EASTMAN KODAK COMPANY

Address:343 STATE STREET

City:ROCHESTER

State:NY

ZIP:14650

Country:U

S

Info Phone Num:716-477-3194 MSDS :800- 242-2424

Emergency Phone Num:716-722-5151

CAGE:19139

=== Contractor Identification ===

Company Name:EASTMAN KODAK CO GOVERNMENT MARKETS CONTRACTS

Address:343 STATE ST

Box:City:ROCHESTER

State:NY

ZIP:14650-1115

Country:US

Phone:716-722-5151/(800) 242-2424

CAGE:19139

Company Name:EASTMAN KODAK CO US CUSTOMER SERVICE/GOVERNMENT SALES

Address:800 LEE RD

Box:City:ROCHESTER

State:NY

ZIP:14650-3129

Country:US

Phone:800-828-6203

CAGE:5K871

===== Composi

tion/Information on Ingredients =====

Ingred Name:WATER
CAS:7732-18-5
RTECS #:ZC0110000
Fraction by Wt: 65-70%
Other REC Limits:NONE RECOMMENDED

Ingred Name:SODIUM BICHROMATE (SARA III)
CAS:10588-01-9
RTECS #:HX7700000
Fraction by Wt: 15-20%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:C 0.1 MG (CRO3)/M3
ACGIH TLV:0.05 MG(CR)/M3; 9394
EPA Rpt Qty:10 LBS
DOT Rpt Qty:10 LBS

Ingred Name:SULFURIC ACID (SARA III)
CAS:7664-93-9
RTECS #:WS5600000
Fraction by Wt: 17%
Other REC Limits:NONE RE
COMMENDED
OSHA PEL:1 MG/M3
ACGIH TLV:1 MG/M3; 9394
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

===== Hazards Identification =====

LD50 LC50 Mixture:TLV SODIUM DICHROMATE IS 0.05MG/KG TWA
Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:YES OSHA:NO
Health Hazards Acute and Chronic:EYES:MAY CAUSE IRRITATION AND SEVERE
BURNS.SKIN:MAY CAUSE IRRITATION AND SEVERE BURNS.INGEST:MAY CAUSE
GI TRACT IRRITATION AND
CAUSE KIDNEY DAMAGE.INHAL:MAY CAUSE
RESPIRATORY IRRITATION.CHRONIC:HEXAVALENT CHROMIUM COMPOUNDS ARE
SUSPECT CARCINOGENS.
Explanation of Carcinogenicity:HEXAVALENT CHROMIUM COMPOUNDS ARE
SUSPECT CARCINOGENS.
Effects of Overexposure:SKIN:ALLERGIC SKIN REACTIONS.
Medical Cond Aggravated by Exposure:PERSONS WITH PRE-EXISTING KIDNEY
AILMENTS MAY BE AT INCREASED RISK FROM EXPOSURE.

===== First Aid Measures =====

First Aid:SKIN:REMOVE CONTAMINAT

ED CLOTHING;WASH WITH WATER.EYES:FLUSH WITH WATER FOR 15 MINUTES.INHAL:REMOVE TO FRESH AIR.GIVE OXYGEN OR ARTIFICIAL RESPIRATION IF NEEDED.INGEST:DO NOT INDUCE VOMITING.GET PROMPT QUALIFIED MEDICAL ATTENTION.IF CONSCIOUS,GIVE A GLASS OF WATER.

===== Fire Fighting Measures =====

Flash Point:NONE

Extinguishing Media:USE MEDIA APPROPRIATE FOR SURROUNDING FIRE.

Fire Fighting Procedures:USE A SELF-CONTAINED BREATHING APPARATUS AND FULL PROTECTIVE EQUIPMENT.

Unusual Fire/Explosion Hazard:FIRE CONDITIONS MAY EVOLVE TOXIC FUMES.DRIED PRODUCT CAN ACT AS A STRONG OXIDIZER.

===== Accidental Release Measures =====

Spill Release Procedures:SOAK UP WITH NON-COMBUSTIBLE INERT ADSORBANT(EG.CLAY);PLACE COLLECTED MATERIEL IN AN APPROPRIATE CONTAINER FOR DISPOSAL;CLEAN SPILL AREA TO REMOVE SLIPPERINESS.CLEAN SPILL AREA THOROUGHLY.

Neutralizing Agent:NOT REPORTED.

===== Handling and Storage =====

Handling and Storage Precautions:USE WITH ADEQUATE VENTILATION.KEEP CONTAINERS CLOSED.KEEP AWAY FROM BASES AND COMBUSTIBLE MATERIALS.

Other Precautions:FOLLOW LABEL DIRECTIONS.AVOID BREATHING VAPORS.AVOID SKIN AND EYE CONTACT.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:WHERE ENVIRONMENTAL CONTROLS ARE LACKING OR IN ENCLOSED SPACES USE EITHER A SELF-CONTAINED BREATHING APPARATUS OR A NIOSH/MSHA APPROVED RESPIRATOR FOR ACID GAS,DEPENDING ON THE AIRBORN CONCENTRATION.

Ventilation:LOCAL VENTILATION AT THE WORKSITE;MECHANICAL(GENERAL) VENTILATION TO MAINTAIN TLV/PEL.

Protective Gloves:IMPERVIOUS

Eye Protection:CHEMICAL GOGGLES.

Other Protective Equipment:PROTECTIVE CLOTHING,AS NEEDED.PROVIDE A LOCAL EYE WASH STATION AND SAFETY SHOWER.

Work Hygienic Practices:WASH HANDS.SEPERATE WORK CLOTHES FROM STREET CLOTHES.LAUNDER WORK CLOTHES BEFORE REUSE.KEEP FOOD OUT OF THE WORK AREA.

S

Supplemental Safety and Health
KEY1;C1.

===== Physical/Chemical Properties =====

HCC:C1
Boiling Pt:B.P. Text:>212F,>100C
Vapor Pres:18
Vapor Density:0.6
Spec Gravity:1.262
pH:1.0
Solubility in Water:COMPLETE
Appearance and Odor:LIQUID;ORANGE;SLIGHT ACRID
Percent Volatiles by Volume:65

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
REDUCING AGENTS,BASES,COMBUSTIBLE MATERIALS.
Stability Condition to Avoid:
d:NONE SPECIFIED BY MANUFACTURER.
Hazardous Decomposition Products:SULFUR DIOXIDE.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH FEDERAL,STATE AND
LOCAL REGULATIONS.HMIS SUGGESTS TO EVALUATE TCLP AND CONSIDER RCRA
CODE D007(CHROMIUM).

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.