View NSN Online: https://aerobasegroup.gr/nsn/6810-01-027-4771

Product ID:METHANOL ABSOLUTE MSDS Date:01/01/1987 FSC:6810 NIIN:01-027-4771 **MSDS Number: BGFRK** === Responsible Party === Company Name: ALLIED CHEMICAL CORP Address:COLUMBIA RD & PARK AVE Box:1087R City:MORRISTOWN State:NJ ZIP:07960 Country:US **Emergency Phone Num:NONE** CAGE:1L168 === Contractor Identifica tion === Company Name: ALLIED CHEMICAL COMPANY Box:1087R CAGE:1L168 Company Name: ALLIED-SIGNAL INC Address:Box:2332R City:MORRISTOWN State:NJ ZIP:07962-2332 Country:US Phone:201-455-4414 CAGE:1L164

Ingred Name:METHYL ALCOHOL (METHANOL) (SARA III) CAS:67-56-1 RTECS #:PC1400000 Fraction by Wt: 99.9% OSHA PEL:S,200PPM/250STEL ACGIH TLV:S,200PPM/250STEL; 93 EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS

====== Hazards

Effects of Overexposure:SKIN:DEFATNG.EYES:IRRITNT.INHALE:HEAD,DIZYNES,WEAK,GI/ VISUAL DISTURB.INGEST:INEBRATN, DROWS, BLINDNESS First Aid:SKIN:WASH W WATER.EYES:FLUSH W WATER.INHALED:GIV CPR/OXYGEN IF NECESSARY.INGEST: IMMEDIATELY INDUCE VOMITING BY HAVING VICTIM DRINK SOAPY WATER.FOR ALL ROUTES KEEP PATIENT WARM/COVER EYES.SEEK MEDICAL ATTENTION. _____ Flash Point:54F,12C CC Autoignition Temp: Autoignition Temp Text: 725F Lower Limits:6.0 Upper Limits:36.5 Extinguishing Media: ALCOHOL FOAM, CO*2, DRY CHEMICAL. Fire Fighting Procedures: USE H*20 TO COOL CONT. WEAR NIOSH APPRVD SELF-CNTND BRTHG APP Unusual Fire/Explosion Hazard:STATIC EXPLOSIONS REPORTED FOR AS LITTLE AS 30%. VAPOR IS EXPLOSV HAZARD. Spill Release Procedures:EL IMINATE IGNITION SOURCES.REMOVE UNPROTECTED PERSONS.STOP LEAK IF POSSIBLE W/O RISK.SM SPILL:FLUSH AREA W LG AMT H*20.LG SPILL: DIKE FOR LATER DISPOSAL AND DILUTE W LG AMTS H*20.KEEP OUT OF SEWERS.RUN OFF MAY POLLUTE.

Handling and Storage Precautions:AVOID HEAT,IGNITION SOURCES.GROUND CONT FOR POURING/TRANSFER.STORE IN COOL WELL-VENTILATED AREAS.USE NON-SPARKING TOOLS. Other Precautions:REGULARLY INSPECT ALL

ELECTRICAL, MECHANICAL, INCLUDING AUTOMOTIVE, EQUIPMENT NEAR METHANOL.

======= Exposure Controls/Personal Protection ==========

Respiratory Protection:FOR HIGH CONCENTRATIONS,AIR SUPPLIED RESPIRATOR. Ventilation:DOWN-DRAFT TYPE LOCAL EXHAUST.50 PPM HOOD FACE VELOCITY. Protective Gloves:RUBBER/NEOPRENE Eye Protection:CHEMICAL GOGGLES Other Protective Equipment:STATIC FREE PROTECTV CLOTHING,BOOTS. Supplemental Safety and Health VAPOR HEAVIER THAN AIR,MAY TRAVEL ALONG GROUND. DO NOT U SE COMPRESSED GAS FOR FILLING,DISCHARGING. DEFATS SKIN. SUPPLIED B: HOCKING INT'L CHEM CORP (FSCM 60930)

HCC:F2 Boiling Pt:B.P. Text:148F,64C Vapor Pres:92 Vapor Density:1.1 Spec Gravity:0.79 Evaporation Rate & amp; Reference:6.3(ETHER=1) Solubility in Water:COMPLETE Appearance and Odor:COLORLESS LIQUID,MILD ALCOHOL ODOR. Percent Volatiles by Volume:100

==

Stability Indicator/Materials to Avoid:YES STRONG OXIDANTS,ACTIVE METALS,ISOCYANATES. Stability Condition to Avoid:HEAT,IGNITION SOURCES. Hazardous Decomposition Products:COMBUSTION REPORTED TO YIELD CO*2 & CO.

Waste Disposal Methods: ELIMINATE IGNITION SOURCES.NOTIFY AUTHORITIES.PACKAGE AND DISPOSE IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compil

ing agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.