

SULFLO, INC., SUBSIDIARY OF BATTENFELD GREASE & OIL -- MIL-L-2105C, LUBRICATING OIL, GEAR, GRD 80W-90 -- 9150-01-035-5393

=====  
Product Identification  
=====

Product ID: MIL-L-2105C, LUBRICATING OIL, GEAR, GRD 80W-90

MSDS Date: 01/01/1987

FSC: 9150

NIIN: 01-035-5393

MSDS Number: BGGKZ

==== Responsible Party ====

Company Name: SULFLO, INC., SUBSIDIARY OF BATTENFELD GREASE & OIL

Emergency Phone Num: (716) 695-2100

CAGE: MO657

==== Contractor Identification ====

Company Name: SULFLO INC

Address: 1158 ERIE AVE

Box: 285

City: NORTH TONAWANDA

State: NY

ZIP: 14120-3507

Country: US

Phone: 716-695-3585

CAGE: 1V074

Company Name: SULFLO, INC., SUBSIDIARY OF BATTENFELD GREASE & OIL

CAGE: MO657

=====  
Composition/Information on Ingredients  
=====

Ingred Name: MINERAL OIL; CAS #64742-41-2

Fraction by Wt: 94.0%

ACGIH TLV: 5MG/CUM(MIST)

Ingred Name: HITEC E-312 (AN ADDITIVE MFRD BY EDWIN

COOPER, INC. ST. LOUIS, MO); TH

IS INFO PER SULFLO MSDS.

Fraction by Wt: 06.0%

=====  
Hazards Identification  
=====

Effects of Overexposure: NONE NOTED BY MFR. LOW TOXICITY & LOW HAZARD TO HEALTH.

=====  
First Aid Measures  
=====

First Aid: SKIN: WASH WITH SOAP AND WATER. EYES: FLUSH WITH WATER.

INHALED: REMOVE TO FRESH AIR. REMOVE CONTAMINATED CLOTHING.; MFR

NOTES, TREAT AS PETROLEUM DISTILLATE

=====  
Fire Fighting Measures  
=====

Flash Point:400F(204C)-COC  
Extinguishing Media:FOAM, DRY CHEMICAL, CO\*2  
Fire Fighting Procedures:WEAR SELF-CNTD BRTHG,APP H\*20 SPRAY TO COOL  
CONTR.  
Unusual Fire/Explosion Hazard:NONE NOTED BY MANUFACTURER.

===== Accidental Release Measures =====

Spill Release Procedures:ELIMINATE IGN SOURCE.USE PROTECTIVE EQUIPMENT  
SUCH AS GLOVES & CLOTHES;ABSORB IN SAND OR OIL SORB & PLACE IN  
CLOSED CONTAINERS;DIKE LG SPILL OF OIL & PUMP TO SALVAGE TANK

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN COOL,DRY,VENTILATED AREA.KEEP  
FROM FREEZING.PROTECT CONTAINERS FROM PHYSICAL DAMAGE.KEEP TIGHTLY  
CLOSED.

Other Precautions:NONE KNOWN.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:DUST/MIST RESPIR  
Ventilation:NORMAL ROOM VENTILATION.  
Protective Gloves:BUNA-N  
Eye Protection:AS REQUIRED  
Other Protective Equipment:NONE  
Supplemental  
Safety and Health  
MSDS FM MFR DATED:4/84;OIL IS GRADE 80W-90 OF MIL-L-2105C.

===== Physical/Chemical Properties =====

HCC:V6  
Boiling Pt:B.P. Text:>700F  
Vapor Pres:.01  
Vapor Density:0.01  
Spec Gravity:0.90  
Solubility in Water:NEGLIGIBLE  
Appearance and Odor:FLUID OIL-TERPENE

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES  
NONE NOTED BY MFR,BUT AVOID STORING NEAR OXIDIZERS.  
Stability Condition to Avoid:EX

CESSIVE HEAT/IGN SOURCES

Hazardous Decomposition Products:CO\*2,CARBON MONOXIDE IF INCOMPLETE  
COMBUSTION

===== Disposal Considerations =====

Waste Disposal Methods:INCINERATE IN APPROVED INCINERATOR OR DISPOSE OF  
IN APPROVED CHEMICAL DUMP IN ACCORDANCE WITH LOCAL,STATE & FEDERAL  
REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense. The U  
nited States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.