

BRAY OIL CO., INC -- BRAYCO 689A LUBE OIL,GEAR,GR 80 W/90 -- 9150-01-035-5394

=====
Product Identification
=====

Product ID:BRAYCO 689A LUBE OIL,GEAR,GR 80 W/90

MSDS Date:01/01/1987

FSC:9150

NIIN:01-035-5394

MSDS Number: BGGMF

=== Responsible Party ===

Company Name:BRAY OIL CO., INC

Emergency Phone Num:714-850-1151

CAGE:LO548

=== Contractor Identification ===

Company Name:BRAY OIL CO., INC.

CAGE:

LO548

Company Name:CASTROL INDUSTRIAL NORTH AMERICA INC SPECIALTY PRODUCTS
DIV

Address:1001 WEST 31ST STREET

Box:City:DOWNERS GROVE

State:IL

ZIP:60515-1280

Country:US

Phone:800-621-2661/ FAX: 630-241-4140

CAGE:2R128

=====
Composition/Information on Ingredients
=====

Ingred Name:PETROLEUM HYDROCARBON

Fraction by Wt: 91.6%

Ingred Name:ANLAMOL 99(TRADENAME CHEMICAL;SEE HMIS INDES FOR DATA)

Fraction by Wt: 6.5%

Ingred Name:ACRYLOID 150 (TRADENAME ADDITIVE;SEE HMIS INDEX FOR
DATA)

Fraction by Wt: 2.0%

=====
Hazards Identification
=====

Effects of Overexposure:NOT EXPECTED TO CAUSE ILL EFFECT EXCEPT POSS IN
VERY SENSITIVE INDIVID; MAY CAUSE EYE IRRITATION.

=====
First Aid Measures
=====

First Aid:EYE:FLUSH THOROUGHLY W/WATER;CALL MD. SKIN:WASH W/SOAP &
WATER.INGESTION: DO NOT INDUCE VOMITING CALL MD.

=====
Fire Fighting Measures
=====

Flash Point:4

30F ASTM D92-COC

Extinguishing Media: DRY CHEMICAL, CARBON DIOXIDE, FOAM, WATER FOG

Fire Fighting Procedures: DO NOT USE WATER EXCEPT TO COOL CONTAINER OR TANK

Unusual Fire/Explosion Hazard: SELF-CONTAINED RESPIRATORY EQUIPMENT WHEN FIRE FIGHTING IN CONFINED AREA.

===== Accidental Release Measures =====

Spill Release Procedures: STOP FLOW & SHUT OFF SOURCES OF IGNITION. WIPE OR MOP UP OR ABSORB WITH CLAY, DIATOMACEOUS EARTH, OR OTHER INERT MATERIAL. STORE IN CLOSED METAL CONTAINERS.

===== Handling and Storage =====

Handling and Storage Precautions: DO NOT STORE NEAR HEAT, OPEN FLAME OR OTHER SOURCES OF IGNITION

Other Precautions: AVOID EYE CONTACT.

===== Exposure Controls/Personal Protection =====

Respiratory Protection: NOT NORMALLY REQUIRED EXCEPT IF OIL MIST EXCEEDS TLV

Ventilation: ONLY IF OIL MIST EXCEEDS TLV

Protective Gloves: PLASTIC, RUBBER

Eye Protection: SAFETY GLASSES RECOMMENDED

Supplemental

Safety and Health

CONFORMS TO MILITARY SPEC MIL-L-2105C

===== Physical/Chemical Properties =====

HCC: V6

Boiling Pt: B.P. Text: 500F

Spec Gravity: 0.907

Solubility in Water: INSOLUBLE

Appearance and Odor: DARK BROWN OILY LIQUID, PETROLEUM ODOR.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES

AVOID STRONG OXIDIZING MATERIALS

Hazardous Decomposition Products: COMBUSTION MAY PRODUCE CO & ASPHYXIANTS

===== Disposal Considerations =====

Waste Disposal Methods:CONTROLLED INCINERATION OR METHOD IN COMPLIANCE
W/LOCAL STATE OR FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use.

Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.