

DOW CORNING CORPORATION -- DOW CORNING(R) QR-2805 CHANNEL SEALANT --
8030-01-043-2295

=====
Product Identification
=====

Product ID:DOW CORNING(R) QR-2805 CHANNEL SEALANT

MSDS Date:11/09/1987

FSC:8030

NIIN:01-043-2295

MSDS Number: BGHGV

=== Responsible Party ===

Company Name:DOW CORNING CORPORATION

Address:3901 SOUTH SAGINAW ROAD

City:MIDLAND

State:MI

ZIP:48686

Info Phone Num:(517) 496-5900

Emerg

ency Phone Num:(517) 496-5900

Preparer's Name:JACK L. SHENEBERGER

CAGE:5D028

=== Contractor Identification ===

Company Name:DOW CORNING CORP

Address:3901 S SAGINAW RD

Box:997

City:MIDLAND

State:MI

ZIP:48686-0997

Country:US

Phone:517-496-6000/517-496-6315

CAGE:5D028

Company Name:DOW CORNING CORP

Address:2200 W SALZBURG RD

Box:City:AUBURN

State:MI

ZIP:48611

Country:US

Phone:517-496-4388

CAGE:71984

=====
Composition/Information on Ingredients
=====

Ingred Name:NON-HAZARDOUS FOR

INGREDIENTS

Fraction by Wt: 100%

===== Hazards Identification =====

Routes of Entry: Inhalation:NO Skin:NO Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:EYE: MAY CAUSE TEMPORARY DISCOMFORT WITH MILD REDNESS & DRYNESS SIMILAR TO WINDBURN. NO IRRITATION TO EYES & RESPIRATORY PASSAGES. INGESTION: SMALL AMTS TRANSFERRED TO THE MOUTH BY FINGERS DURING USE. SHOULDN'T INJURE. SWALLOWING LARGE AMT S MAY CAUSE DIGESTIVE DISCOMFORT.
Explanation of Carcinogenicity:NONE
Effects of Overexposure:NO KNOWN ADVERSE CHRONIC HEALTH EFFECTS, BUT UNNECESSARY EXPOSURE TO ANY CHEMICAL SHOULD BE AVOIDED.

===== First Aid Measures =====

First Aid:EYES: FLUSH WITH WATER. SKIN: WIPE OFF AND FLUSH WITH WATER. INHALATION/INGESTION: NO FIRST AID SHOULD BE NEEDED.

===== Fire Fighting Measures =====

Flash Point Method:CC
Flash Point:200F
Extinguishing Media:WATER FOG, CO, DRY CHEMICAL, FOAM
Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS (SCBA) AND FULL PROTECTIVE CLOTHING.
Unusual Fire/Explosion Hazard:TOXIC FLUORINE COMPOUNDS. EVACUATE AREA IN CASE OF OVERHEATING OR FIRE.

===== Accidental Release Measures =====

Spill Release Procedures:REMOVE PRODUCT AND USE ABSORBENT MATERIAL TO TAKE CARE OF ANY OIL-LIKE RESIDUES.

===== Handling and Storage =====

Handling and Storage Precautions:USE REASONABLE CARE & CAUTION. ROOM TEMPERATURE HANDLING; USE AT ELEVATED TEMPS, OR AEROSOL/SPRAY, MAY REQUIRE.
Other Precautions:HIGHLY TOXIC VAPORS, TRIFLUOROPROPIONALDEHYDE (TFPA), MAY EVOLVE IF MATERIAL IS HEATED IN AIR >300F OR BURNED. IF USED >300F PROVIDE ADEQUATE VENTILATION. IN CASE OF OVERHEATING OR FIRE. EVACUATE THE AREA.

===== Exposure Controls/Personal Protection =====

Respiratory Prot

ction:NONE SHOULD BE NEEDED

Ventilation:MECHANICAL: RECOMMENDED

Eye Protection:SAFETY GLASSES

Work Hygienic Practices:ANY AMT OF CHEMICAL SHOULD BE REMOVED FROM SKIN
AS SOON AS PRACTICAL, ESPECIALLY BEFORE EATING OR SMOKING.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:N1

Spec Gravity:1.36

Solubility in Water: