

EASTMAN KODAK COMPANY -- 121 6944,RP X-OMAT DEVL REPL,PT B(SEE SUPP) --  
6525-01-061-1694

=====  
===== Product Identification =====

Product ID:121 6944,RP X-OMAT DEVL REPL,PT B(SEE SUPP)

MSDS Date:07/30/1980

FSC:6525

NIIN:01-061-1694

MSDS Number: BGJSZ

=== Responsible Party ===

Company Name:EASTMAN KODAK COMPANY

Address:343 STATE STREET

City:ROCHESTER

State:NY

ZIP:14650

Country:US

Emergency Phone Num:(716

) 722-5151

CAGE:19139

=== Contractor Identification ===

Company Name:EASTMAN KODAK CO GOVERNMENT MARKETS CONTRACTS

Address:343 STATE ST

Box:City:ROCHESTER

State:NY

ZIP:14650-1115

Country:US

Phone:716-722-5151/(800) 242-2424

CAGE:19139

=====  
===== Composition/Information on Ingredients =====

Ingred Name:DIETHYLENE GLYCOL (50-55%)

CAS:111-46-6

RTECS #:ID5950000

Fraction by Wt: 52.5%

Ingred Name:ACETIC ACID (SARA III)

CAS:64-19-7

RTECS #:AF1225000

Fraction by Wt: 37.5%

OSHA PEL:10 P

PM  
ACGIH TLV:10 PPM/15 STEL; 9192  
EPA Rpt Qty:5000 LBS  
DOT Rpt Qty:5000 LBS

Ingrid Name:1-PHENYL-3-PYRAZOLIDINONE (5-10%)  
CAS:92-43-3  
RTECS #:UQ8750000  
Fraction by Wt: 07.5%

=====  
Hazards Identification  
=====

Effects of Overexposure:INH:VAP MAY CAUSE IRRITN;EYES:LIQ CONTCT MAY  
CAUSE BURNS;SKIN:LIQ CAUSES IRRIT/ALLERGIC REACTION.

=====  
First Aid Measures  
=====

First Aid:GET MED ATTN IF IRRITATION OF EYES/SKIN PERSIST  
S.

=====  
Fire Fighting Measures  
=====

Flash Point:NONE  
Extinguishing Media:CO\*2, FOAM, DRY CHEM.  
Fire Fighting Procedures:NONE  
Unusual Fire/Explosion Hazard:NONE

=====  
Accidental Release Measures  
=====

Spill Release Procedures:ELIM IGN SOURCES.STOP LEAK W/O RISK.WEAR  
PROTECTV EQUIPMNT;NEUTRALIZE SM SPILL W/SPDIUM BICARBONATE.FLUSH TO  
SEWER IAW FED,STATE & LOCAL REGS;LG SPILL:DIKE FAR AHEAD  
W/COMMERCIAL ABSORBENT FOR LA  
TER D ISPOSAL OR PUMP LIQ TO COVERED  
DRUMS.

=====  
Handling and Storage  
=====

Handling and Storage Precautions:STORE IN COOL,DRY,WELL VENTILATED  
AREA. PROTECT FROM PHYSICAL DAMAGE.AVOID ANY PHYSICAL CONTACT. KEEP  
CONTAINERS TIGHTLY CLOSED  
Other Precautions:NONE KNOWN

=====  
Exposure Controls/Personal Protection  
=====

Respiratory Protection:AN APPROVED ORGANIC ACID RESPIRATOR IF  
VENTILATION IS INADEQUATE  
Ventilation:MECH(GEN)O

R LOCAL EXHAUST THAT PROVIDES ADEQUATE VENTILATION

Protective Gloves:IMPERVIOUS

Eye Protection:SAFETY/CHEM GOGGLES

Other Protective Equipment:AS NECESSARY TO PREVENT SKIN CONTACT

Supplemental Safety and Health

THIS IS PART B OF 3 PARTS PRODUCT;PART B CAT #122 6240 WAS CHANGED TO 141 8151 & TO 162 0509 RESPECTIVELY.WITH THE CHANGE OF CAT #,MFR ALSO CHANGED THE FORMULATION BUT KEPT THE SAME NSN.NEW FORMULATION & NEW CAT # UNDER PNI-B OF THIS NSN;FOR PART A SEE NSN 6525-01-061-

1693 AND FOR PART C SEE NSN 6525-01-061-4366.

===== Physical/Chemical Properties =====

HCC:C2

Boiling Pt:B.P. Text:>212F/100C

Vapor Pres:15

Vapor Density:2.07

Spec Gravity:1.11

pH:2.0

Solubility in Water:COMPLETE

Appearance and Odor:ORANGISH OR LIGHT BROWN,VINEGAR ODOR

Percent Volatiles by Volume:70

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

ALKALINE SOLUTIONS,STRONG OXIDIZERS/FLAMMABLE LIQUIDS.

S

Stability Condition to Avoid:NONE KNOWN

===== Disposal Considerations =====

Waste Disposal Methods:OR FOLLOW STEP OF NEUTRALIZATION IAW EFFLUENT LAWS OF FED,STATE & LOCAL.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims a

It liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.