View NSN Online: https://aerobasegroup.gr/nsn/6850-01-263-8219

Product ID:ZL-1D ZYGLO PENETRANT MSDS Date:05/28/1986 FSC:6850 NIIN:01-263-8219 MSDS Number: BGRNS === Responsible Party === **Company Name: MAGNAFLUX CORPORATION** Address:7300 W.LAWRENCE AVENUE City:CHICAGO State:IL ZIP:60656 Country:US Info Phone Num:312-867-8000 Emergency Phone Num:312-867-8000 Pre parer's Name: BRUCE C.GRAHAM CAGE:37676 === Contractor Identification === Company Name: ILLINOIS TOOL WORKS INC MAGNAFLUX DIV Address:3624 WEST LAKE AVENUE Box:City:GLENVIEW State:IL ZIP:60025 Country:US Phone:847-657-5300/ CAGE:37676

Ingred Name:KEROSENE CAS:8008-20-6 RTECS #:OA5500000 Fraction by Wt: 10.0% ACGIH TLV:100MG/CUM

Ingred Name:UNIDENTIFIED COMPONENTS Fraction by Wt: 90.0%

======================= Hazards Identifica

Routes of Entry: Inhalation:NO Skin:YES Ingestion:NO Health Hazards Acute and Chronic:IRRITATES EYES. Effects of Overexposure:INHALATION:CAUSES DIZZINESS,DROWSINESS,NAUSEA; SKIN:LIQUID IRRITATES BY DISSOLVING SKIN OIL; EYES:VAPORS/LIQUID CAUSES IRRITATION; INGESTION:CAUSES GASTRIC UPSET. Medical Cond Aggravated by Exposure:NOT KNOWN

First Aid:INHALATION:REMOVE TO FRESH AIR.IF BREATHING IS DIFFICULT,GIVE OXYGEN; SKIN:REMOVE CONTAMINATED CLOTHES.WASH OFF WITH FLOWING WATER.USE SOOTHING LOTION.IF IRRITATION PERSISTS,GET MEDICAL ATTN; EYES:IMM EDIATELY RINSE/FLUSH WITH COPIOUS AMOUNT OF RUNNING WATER,AND GET MEDICAL ATTENTION; INGESTION:GET MEDICAL ASSISTANCE.

Flash Point Method:PMCC Flash Point:200F/93C Lower Limits:6.0% Upper Limits:1.0% Extinguishing Media:CARBON DIOXIDE,FOAM Fire Fighting Proc edures:KEEP CONTAINERS COOL WITH WATER SPRAY.DO NOT SPRAY WATER ON BURNING PRODUCT. Unusual Fire/Explosion Hazard:WHEN INVOLVE IN COMBUSTION,MAY EMIT TOXIC GASES AT OR ABOVE DECOMPOSITION TEMPERATURE.

Spill Release Procedures:REMOVE IGNITION SOURCES.SM QTY:WIPE UP OR MOP UP BUT DO NOT BREATHE VAPORS.PLACE RAGS IN CLOSED DRUMS; LG QTY:WEAR PERSONAL SAFETY EQUIPMENTS.DIKE AREA FAR AHEAD.ABSORB LIQUID WITH COM MERCIAL ABSORBEN T.TRANSFER WASTE MATL IN SALVAGE TANKS.

Handling and Storage Precautions:STORE AWAY FROM HEAT SOURCES IN WELL
VENTILATED AREA.AVOID AGAINST PHYSICAL DAMAGE TO CONTAINERS.KEEP
CONTAINERS TIGHTLY CLOSED.
Other Precautions:DO NOT BREATHE VAPORS.DO NOT SMOKE WHILE USING.DO NOT

HEAT ABOVE 130F(54C).AVOID FREQUENT OR PROLONGED SKIN CONTACT.

====== Exposure Controls/Personal Protection =====

=======

Respiratory Protection:WEAR RESPIRATOR WITH FILTER CARTRIDGE IF SPRAYING IN UNVENTILATED AREA. Ventilation:GENERAL VENTILATION OF 1-3 CHANGES PER HOUR,WHEN SPRAYED. Protective Gloves:NITRILE RUBBER GLOVES Eye Protection:FULL GOGGLES Other Protective Equipment:NOT KNOWN Work Hygienic Practices:WASH THOROUGHLY AFTER HANDLING OR USE.LAUNDER CONTAMINATED CLOTHES BEFORE REUSE. Supplemental Safety and Health KEY1:N1.

==

==========

HCC:N1 Boiling Pt:B.P. Text:410F/210C Vapor Pres:1.0 Spec Gravity:0.92 Solubility in Water:NEGLIGIBLE Appearance and Odor:GREEN OILY LIQUID,PETROLEUM DISTILLATES ODOR Percent Volatiles by Volume:10.0

Stability Indicator/Materials to Avoid:YES NOT KNOWN TO MFR.HOWEVER,AVOID STRONG OXIDIZERS. Stability Condition to Avoid:HEAT,HIGH TEMPERATURES. Hazardous Decomposition Products:EMITS OXIDES OF CARBON AND NITROGEN.

Waste Disposal Methods:INCINERATE OR DISPOSE OF AS EPA HAZARDOUS WASTE D001 (IGNITABLE WASTE),IN ACCORDANCE WITH ALL APPLICABLE FEDERAL,STATE,LOCAL REGULATIONS;IF LOCAL AUTHORITIES PROHIBIT DUMPING RINSINGS DOWN THE SEWER,P URIFY RINSINGS WITH MAGNAFLUX TREATMENTSYSTEM.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense . The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.