View NSN Online: https://aerobasegroup.gr/nsn/6850-01-266-4553

Product ID:VP-31A PENETRANT MSDS Date:10/15/1986 FSC:6850 NIIN:01-266-4553 **MSDS Number: BGRZC** === Responsible Party === Company Name: MET-L-CHEK COMPANY Address:1639 EUCLID STREET **City:SANTA MONICA** State:CA ZIP:90404-3770 Country:US Info Phone Num:213-450-1111 Emergency Phone Num:213-450-1111 CAGE:98733 == = Contractor Identification === Company Name:MET-L-CHEK COMPANY Address:1639 EUCLID ST Box:00000 **City:SANTA MONICA** State:CA ZIP:90404 Country:US Phone:310-450-1111/FAX 310452-4046 CAGE:98733

Ingred Name:DISTILLATE (PETROLEUM),HYDROTREATED MIDDLE; ON MSDS MFR SIMPLY NOTED AS "PETROLEUM HYDROCARBON" FOR ABOVE CAS NO. CAS:64742-46-7 RTECS #:JN9379645 OSHA PEL:5MG/CUM ACGIH TLV:5MG/CUM

=================== Hazards Identifi

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:UNKNOWN IARC:UNKNOWN OSHA:YES Health Hazards Acute and Chronic:PER MANUFACTURER,MAY CAUSE SLIGHT IRRITATION TO SKIN ON CONTACT AND RESPIRATORY TRACT SYSTEM.

Explanation of Carcinogenicity:CARCINOGENICITY OF THE PRODUCT FOR OSHA REQUIREMENTS IS SPECIFIED "YES" BY THE MFR BUT DID NOT SPECIFY THE COMPONENT.

Effects of Overexposure:EYES:PRESUMED NON-IRRITATING;SKIN:S LIGHT

IRRITATION ON LIQUID CONTACT; INHALATION: VAPORS OR OIL MIST MAY CAUSE MILD IRRITATION OF UPPER RESPIRATORY TRACT; INGESTION: MAY RESULT IN VOMITING.

Medical Cond Aggravated by Exposure:PRE-EXISTING SKIN AND RESPIRATORY DISORDERS MAY BE AGGRAVATED BY EXPOSURE TO THIS PRODUCT.

First Aid:EYES:FLUSH WITH WATER.GET MEDICAL HELP IF IRRITATION OCCURS OR PERSISTS; SKIN:FLUSH WITH WATER.WASH WITH WATER & SOAP.GE T MED

ATTN FOR PERSISTING IRRITATION; INHALATION:REMOVE TO FRESH AIR.PROVIDE OXY GEN IF BREATHING IS DIFFICULT,GET MED ATTN IF NEEDED; INGESTION:DO NOT INDUCE VOMITING.GET MEDICAL ATTENTION.

Flash Point Method: PMCC

Flash Point:188F(86.7C)

Extinguishing Media:WATER FOG, DRY CHEMICAL, CARBON DIOXIDE OR FOAM; DO NOT USE DIRECT STREAM OF WATER.

Fire Fighting Procedures: IN CONFINED AREA, DO NOT ENTER WITHOUT A FULL

BUNKER GEAR INCLUDING A POSITIVE PRESSURE NIOSH APPROVED SELF CONTAINED BREATHING APPARATUS. Unusual Fire/Explosion Hazard:NOT KNOWN

Spill Release Procedures: ELIM IGNITION SOURCES. WEAR APPROPRIATE PROTECTIVE CLOTHING & RESPIRATOR. DIKE & TRANSFER LIQ TO A SALVAGE TANK.SOAK UP RESIDUE WITH ABSORBENT CLAY, SAND OR OTHER MATL.PLACE RAGS & ABSORBED WASTE MATERIA L IN COVERED NON-LEAKING CONTAINERS.

Handling and Storage Precautions: KEEP AWAY FROM HEAT/IGNITION SOURCES. STORE IN DRY,COOL & VENTILATED LOCATION. DO NOT STORE NEAR OXIDIZING MATERIAL. AVOID PHYSICAL DAMAGE TO CANS. Other Precautions: MINIMIZE SKIN CONTACT.

Respiratory Protection: IF EXPOSURE EXCEEDS TLV, USE NIOSH APPROVED RESPIRATOR TO PREVENT OVEREXPOSURE. Ventilation: PER MANUFACTURER, PROVIDE LOC AL EXHAUST, OR MECHANICAL(GENERAL) VENTILATION TO MAINTAIN TLV. Protective Gloves: CHEMICAL RESISTANT Eye Protection:GOGGLES Other Protective Equipment: EYE WASH FOUNTAINS AND SAFETY SHOWERS Work Hygienic Practices: WASH WITH SOAP AND WATER BEFORE EATING, DRINKING, SMOKING OR USING TOILET FACILITIES. Supplemental Safety and Health NSN FOR 2 PARTS KIT OF TYPE II, METHOD B UNDER MIL-I-25135, REVISION D; I/A/W QPL-25135-15, THE KIT CONTAINS 1-1 GAL CONTNR OF VP-31A PENETRANT & 1-1 GAL CONTA INER OF E-50 EMULSIFIER; KEY1:F8; THIS ENTRY DESCRIBES P/N:VP-31A PENETRANT.

HCC:V4 Boiling Pt:B.P. Text:>400F/>204C Spec Gravity:0.86 Solubility in Water:NEGLIGIBLE Appearance and Odor:DEEP REDDISH-PURPLE LIQUID,HYDROCARBON ODOR.

Stability Indicator/Materials to Avoid:YES OXIDIZING MATERIAL Stability Condition to Avoid:HEAT & IGNITION SOURCES. Hazardo

us Decomposition Products:CARBON MONOXIDE & OTHER UNIDENTIFIED ORGANIC COMPOUNDS.

Waste Disposal Methods:DISPOSE OF AS EPA HAZARDOUS WASTE #D001,IGNITABLE WASTE.PLACE WASTE MATERIAL IN AN APPROPRIATE DISPOSAL FACILITY,OR DISPOSE OF IN COMPLIANCE WITH FEDERAL,STATE & LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and

disclaims all liability for its use. Any person utilizing this

document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.