View NSN Online: https://aerobasegroup.gr/nsn/6850-01-268-6706

MAGNAFLUX CORPORATION -- ZL-22D ZYGLO PENETRANT -- 6850-01-268-6706

Product ID:ZL-22D ZYGLO PENETRANT MSDS Date:11/17/1986 FSC:6850 NIIN:01-268-6706 **MSDS Number: BGSDC** === Responsible Party === **Company Name: MAGNAFLUX CORPORATION** Address:7300 W.LAWRENCE AVENUE City:CHICAGO State:IL ZIP:60656 Country:US Info Phone Num:312-867-8000 Emergency Phone Num:312-867-8000 Ρ reparer's Name: BRUCE C.GRAHAM CAGE:37676 === Contractor Identification === Company Name: ILLINOIS TOOL WORKS INC MAGNAFLUX DIV Address:3624 WEST LAKE AVENUE Box:City:GLENVIEW State:IL ZIP:60025 Country:US Phone:847-657-5300/ CAGE:37676 Ingred Name: DISTILLATES (PETROLEUM), HYDROTREATED MIDDLE CAS:64742-46-7 RTECS #: JN9379645 Fraction by Wt: 25.0% Ingred Name:KEROSENE CAS:8008-20-6 RTECS #:OA5500000 Fraction by Wt: 10.0% ACGIH TL

V:100MG/CUM

Ingred Name:DISTILLATES(PETROLEUM),CATALYTIC REFORMER FRACTIONATER RESIDUE,LOW BOILING CAS:68477-31-6 Fraction by Wt: 20.0%

Ingred Name:UNIDENTIFIED COMPONENTS Fraction by Wt: 45.0%

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:ACUTE:IRRITATES EYES,MILDLY. Effects of Overexposure:INHALATION:SPRAY MIST MAY IRRITATE TO BREATHING PASSAGES; EYES:LIQUID CONTACT MAY CAUS

E IRRITATION; SKIN:SOLVENT IN

THE PRODUCT MAY IRRITATE SKIN; INGESTION:NOT NOTED BY MANUFACTURER. Medical Cond Aggravated by Exposure:NOT STATED BY MANUFACTURER.

First Aid:INHALATION:REMOVE TO FRESH AIR.IF BREATHING IS DIFFICULT,GIVE OXYGEN; SKIN:REMOVE CONTAMINATED CLOTHES.WASH OFF WITH FLOWING WATER.USE SOOTHING LOTION.IF IRRITATION PERSISTS,GET MEDICAL ATTN; EYES:IMM EDIATELY RINSE/FLUSH WITH COPIOUS AMOUNT OF RUNNING

WATER, AND GET MEDICAL ATTENTION.

Flash Point Method:PMCC Flash Point:>200F/>93C Extinguishing Media:CARBON DIOXIDE,FOAM Fire Fighting Procedures:KEEP CONTAINERS COOL WITH WATER SPRAY.DO NOT SPRAY ON BURNING PRODUCT. Unusual Fire/Explosion Hazard:WHEN INVOLVE IN COMBUSTION,MAY EMIT TOXIC GASES AT OR ABOVE DECOMPOSITION TEMPERATURE.

Sp

III Release Procedures:REMOVE IGNITION SOURCES.SM QTY:WIPE UP OR MOP UP BUT DO NOT BREATHE VAPORS.PLACE RAGS IN CLOSED DRUMS; LG QTY:WEAR PERSONAL SAFETY EQUIPMENTS.DIKE AREA FAR AHEAD.ABSORB LIQUID WITH COMMERCIAL ABSORBEN T.TRANSFER WASTE MATL IN SALVAGE TANKS.

Handling and Storage Precautions:STORE AWAY FROM HEAT SOURCES IN WELL VENTILATED AREA.AVOID AGAINST PHYSICAL DAMAGE TO CONTAINERS.KEEP CONTAIN

ERS TIGHTLY CLOSED.

Other Precautions:DO NOT BREATHE VAPORS.DO NOT SMOKE WHILE USING.DO NOT HEAT ABOVE 130F(54C).AVOID FREQUENT OR PROLONGED SKIN CONTACT.

======= Exposure Controls/Personal Protection ==========

Respiratory Protection:WEAR A RESPIRATOR WITH CHEMICAL CARTRIDGE. IN CONFINED AREAS,WEAR A FULL MASK WITH SEPARATE AIR SUPPLY.

Ventilation: GENERAL VENTILATION TO KEEP BELOW 350PPM LIMIT.

Protective Gloves:NITRILE RUBBER GLOVES

Eye Protection: FULL GOGGLES WHEN SPRAYIN

G OR POURING

Other Protective Equipment: EITHER USE IN A SPRAY BOOTH OR NEXT TO AN EXHAUST VENT.

Work Hygienic Practices: WASH THOROUGHLY AFTER HANDLING OR USE. LAUNDER CONTAMINATED CLOTHES BEFORE REUSE.

Supplemental Safety and Health

NSN FOR TYPE I,METHOD D,LEVEL 3 MATERIAL OF MIL-I-25135D ZL-22D PENETRANT IS A QUALIFIED PRODUCT OF QPL-25135-15 FOR TYPE I,METHOD D,LVL 3;THE QPL SPECIFIED THE PENETRANT CAN ALSO BE A PART OF KIT WIT H ZR-10A EMULSIFIER;SEE PNI B FOR OTHERQUALIFIE D PENETRANT FOR

SAME TYPE, METHOD & LEVEL.

HCC:N1 Boiling Pt:B.P. Text:410F/210C Vapor Pres:0.5 @ 100F Vapor Density:>1.0 Spec Gravity:0.95 Solubility in Water:NEGLIGIBLE Appearance and Odor:GREEN LIQUID WITH PETROLEUM DISTILLATE ODOR Percent Volatiles by Volume:5.0%

Stability Indicator/Materials to Avoid:YES MFR STATED "NONE" Stability Condition to Avoi

d:HEAT,HIGH TEMPERATURES Hazardous Decomposition Products:EMITS OXIDES OF CARBON AND NITROGEN ON COMBUSTION

Waste Disposal Methods:INCINERATE OR DISPOSE OF AS EPA HAZARDOUS WASTE D001 (IGNITABLE WASTE),IN ACCORDANCE WITH ALL APPLICABLE FEDERAL,STATE,LOCAL REGULATIONS;IF LOCAL AUTHORIES PROHIBIT DUMPING RINSINGS DOWN THE SEWER,PUR IFY RINSINGS W/MAGNAFLUX WASTEWATER TREATMNT SYSTM

Disclaimer (provided with

this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.