Product ID:AWS 316 WELDING ELECTRODE

MSDS Date:11/01/1985

FSC:3439

NIIN:01-039-4382

MSDS Number: BGSLH === Responsible Party ===

Company Name: TECHALLOY MARYLAND INC. REID-AVERY DIV.

Address:2310 CHESAPEAKE AVE

City:BALTIMORE

State:MD

ZIP:21222-4012

Emergency Phone Num:301-633-9300

CAGE:59711

=== Contractor Identification ===

Company Name:

TECHALLOY COMPANY, INC.

Address:2310 CHESAPEAKE AVENUE

Box:City:BALTIMORE

State:MD ZIP:21222 Country:US

Phone:410-633-9300; 800-638-1458

CAGE:59711

======= Composition/Information on Ingredients =======

Ingred Name:IRON CAS:7439-89-6

RTECS #:NO4565500

Ingred Name: CHROMIUM (SARA III)

CAS:7440-47-3

RTECS #:GB4200000 Fraction by Wt: 17-20% OSHA PEL:1 MG/M3

ACGIH TLV:0.5 MG/M3; 9192

EPA Rpt Qty:1 LB DOT Rpt Qty:1 LB

Ingred Name: NICKEL (SARA III)

CAS:7440-02-0

RTECS #:QR5950000

Fr

action by Wt: 11-14% OSHA PEL:1 MG/M3 ACGIH TLV:1 MG/M3; 9192

Ingred Name: MANGANESE (SARA III)

CAS:7439-96-5

RTECS #: OO9275000

OSHA PEL:(C) 5 MG/M3 DUST ACGIH TLV:5 MG/M3 DUST 9293

Ingred Name: SILICON

CAS:7440-21-3

RTECS #: VW0400000

OSHA PEL:15 MG/M3 TDUST

ACGIH TLV:10 MG/M3 TDUST; 9293

Ingred Name: MOLYBDENUM

CAS:7439-98-7

RTECS #:QA4680000 Fraction by Wt: 2-2.5%

OSHA PEL:15 MG/M3 TDUST ACGIH TLV:10 MG/M3; 9293

========== Hazards Identification =================

## Routes of

Entry: Inhalation:YES Skin:NO Ingestion:NO

Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:NO

Health Hazards Acute and Chronic:ACUTE:MAY RESULT IN DISCOMFORT SUCH AS DIZZINESS,NAUSEA,DRYNESS OR IRRITATION OF NOSE,THROAT OR EYES.TIGHTNESS IN CHEST,FEVER & ALLERGIC REACTIONS. CHRONIC:MAY LEAD TO SIDEROSIS & IS BELIEVED BY SOME INVESTIGATORS TO AFFECT PULMONARY FUNCTION.

Explanation of Carcinogenicity:NICKEL & CHROMIUM ARE LISTED AS CARCINOGENIC.

Medical Cond Aggravated by Exposure:NONE STATED

First Aid:REMOVE TO FRESH AIR.IF BREATHING IS DIFFICULT, ADMINISTER OXYGEN, IF BREATHING GAS STOPPED, APPLY ARTIFICIAL RESPIRATOR, GET MEDICAL HELP.

========== Fire Fighting Measures ================

Extinguishing Media:USE PROPER MEDIA FOR SURROUNDING FIRE. Fire Fighting Procedures:NEED TO WEAR PROTECTIVE EQUIPMENT. Unusual Fire/Explosion Hazard:WELDING ARC & SPARKS CAN IGNIT

COMBUSTIBLES.
========= Accidental Release Measures ==========
Spill Release Procedures:SWEEP UP OR SCOOP UP.
=========== Handling and Storage ============
Handling and Storage Precautions: USE EXHAUST SYSTEM TO CLEAR WELDING FUMES.
====== Exposure Controls/Personal Protection ========
Respiratory Protection:USE RESPIRABLE FUME RESPIRATORY OR AIR SUPPLIED RESPIRATOR WHEN WELDING IN A CONFINED SPACE OR WHERE LOCAL EXHAUST
OR VENTILATION DOES NOT KEEP EXPOSURE BELOW TLV.  Ventilation: USE ADEQUATE GENERAL VENTILATION & LOCAL EXHAUST AT THE ARC.
Protective Gloves:WELDER'S GLOVES. Eye Protection:HELMET/FACE SHIELD WITH FILTER LENS. Other Protective Equipment:WEAR PROTECTIVE CLOTHING. Supplemental Safety and Health
======================================
HCC:N1 Solubility in Water:INSOLUBLE Appearance and Odor:SOLID WIRE OR ROD. Percent Volatiles by Volume:0
======== Sta bility and Reactivity Data ==========
Stability Indicator/Materials to Avoid:YES NONE Stability Condition to Avoid:NONE STATED. Hazardous Decomposition Products:IT IS COMPLEX & CAN NOT BE CLASSIFIED GASILY,DEPENDING ON THE ELECTRODE USED,COATING & CONTAMINANTS IN THE ATMOSPHERE.
======= Disposal Considerations ==========
Waste Disposal Methods:DISCARD ANY PRODUCT RESIDUE,DISPOSABLE CONTAINER OR LINER IN AN ENVIROMENTALLY ACCEPTABLE MANNER.

Discla

Ε

imer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.