

MET-L-CHEK COMPANY -- VP-30 PENETRANT -- 6850-01-265-7233

=====
Product Identification
=====

Product ID:VP-30 PENETRANT

MSDS Date:10/24/1986

FSC:6850

NIIN:01-265-7233

MSDS Number: BGSRQ

=== Responsible Party ===

Company Name:MET-L-CHEK COMPANY

Address:1639 EUCLID STREET

City:SANTA MONICA

State:CA

ZIP:90404-3770

Country:US

Info Phone Num:213-450-1111

Emergency Phone Num:213-450-1111

CAGE:98733

===

Contractor Identification ===

Company Name:MET-L-CHEK COMPANY

Address:1639 EUCLID ST

Box:00000

City:SANTA MONICA

State:CA

ZIP:90404

Country:US

Phone:310-450-1111/FAX 310452-4046

CAGE:98733

=====
Composition/Information on Ingredients
=====

Ingred Name:SOLVENT NAPHTHA (PETROLEUM) MEDIUM ALIPHATIC

CAS:64742-88-7

OSHA PEL:500PPM

ACGIH TLV:100PPM

Ingred Name:SOLVENT NAPHTHA (PETROLEUM) LIGHT AROMATIC

CAS:64742-95-6

OSHA PEL:500PPM

ACGIH TLV:100PPM

Ingred Name:ISOBUTANE/PROPANE

MIXTURE (AS PROPELLANT)
OSHA PEL:1000PPM (PROPANE)
ACGIH TLV:ASPHYXIANTS

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:UNKNOWN IARC:NO OSHA:NO
Health Hazards Acute and Chronic:MAY CAUSE MILD IRRITATION TO SKIN &
RESP TRACT SYSTEM.
Explanation of Carcinogenicity:NO
Effects of Overexposure:INHALATION:MAY CAUSE IRRITATION TO NOSE AND
RESPIRATORY SYSTEM.EARLY TO MODERATE CNS
DEPRESSION MAY BE
EVIDENCED BY DIZZ,GIDDINESS,HEADACHE,NAUSEA;EYES:VAPOR MAY CAUSE
IRRITATION;SKIN:LIQUID CONTACT M AY IRRITATE MILDLY;INGESTION:NOT
LISTED.
Medical Cond Aggravated by Exposure:PRE-EXISTING SKIN,EYE,AND
RESPIRATORY DISORDERS MAY BE AGGRAVATED.

===== First Aid Measures =====

First Aid:INHALATION:REMOVE TO FRESH AIR.GIVE CPR IF
NEEDED;EYES/SKIN:FLUSH WITH RUNNING WATER FOR AT LEAST 15
MINUTES.GET MEDICAL HELP IF IRRITA
TION OCCURS OR PERSISTS;
INGESTION:IF VICTIM IS CONSCIOUS,GIVE WA TER.DO NOT INDUCE
VOMITING.NOTHING BY MOUTH IF UNCONSCIOUS.GET MEDICAL ATTN.

===== Fire Fighting Measures =====

Flash Point:N/R (AEROSOLS)
Lower Limits:2.0 (LIQ)
Upper Limits:12.0 (LIQ)
Extinguishing Media:WATER FOG,"ALCOHOL" FOAM,DRY CHEMICAL OR CO*2.
Fire Fighting Procedures:CONTAINERS EXPOSED TO INTENSE HEAT FROM FIRES
SHOULD BE COOLED WITH WATER SPRAY TO PREVENT VAPOR PRESSURE
BUILD-UP.DON'T STORE ABOVE 120F.
Unusual Fire/Explosion Hazard:AEROSOL CANS MAY RUPTURE/EXPLODE DUE TO
VAPOR PRESSURE BUILDUP IF EXPOSED TO INTENSE HEAT.

===== Accidental Release Measures =====

Spill Release Procedures:ELIMINATE IGNITION SOURCES WEAR PROTECTIVE
CLOTHING & APPROPRIATE RESPIRATOR.SOAK UP RESIDUE WITH ABSORBENT
CLAY,SAND,EARTH, OR OTHER MATERIAL.PLACE RAGS & ABSORBED WASTE AND
DAMAGED BUT EMPTY CANS IN DOT COVERED NON-LEAKING CONTAIN

ERS.

=====
===== Handling and Storage =====

Handling and Storage Precautions:STORE AWAY FROM HOT PLACES & IGNITION SOURCES.DO NOT STORE OR HANDLE IN ALUMINUM EQUIPMENT AT TEMP ABOVE 120F.

Other Precautions:DURING TRANSFER OF LIQUID IN BULK,GROUND THE HANDLING EQUIPMENT.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE NIOSH APPROVED RESPIRATOR IF EXPOSURE EXCEEDS TLV LIMIT.

Ventilation:PER MFR,LOCAL EXHAUST OR MECH(GEN) TO MAINTAIN TLV.

Protective Gloves:CHEMICAL RESISTANT.

Eye Protection:GOGGLES.

Other Protective Equipment:EYE WASH FOUNTAINS AND SAFETY SHOWERS.

Work Hygienic Practices:WASH WITH SOAP & WATER BEFORE EATING,DRINKING,SMOKING OR USING TOILET FACILITIES.

Supplemental Safety and Health

NSN FOR AEROSOL CAN OF MIL-I-25135,REV D TYPE II,METHOD C;I/A/W QPL-25135-15,MFR MAY SUPPLY EITHER VP-30 OR VP-31A PENETRANT FOR THIS NSN; THIS ENTRY IS OF VP-30.

=====
===== Physical/Chemical Properties =====

HCC:V3

Spec Gravity:0.8 (BULK)

Evaporation Rate & Reference:1.4 OF LIQ(ETHYL AC=1.0)

Solubility in Water:APPRECIATE

Appearance and Odor:LIQUID BEFORE FILLING IN AEROSOL CANS IS DEEP RED COLORED LIQ;HYDROCARBON ODOR.

=====
===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
STRONG OXIDIZING MATERIALS.

Stability Condition to Avoid:HEAT,SPARKS,IGNITION SOURCES.

Hazardous Decomposition Produ

cts:CARBON MONOXIDE & UNIDENTIFIED ORGANIC
COMPOUNDS.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF AS EPA HAZARDOUS WASTE
#D001,IGNITABLE WASTE.EMPTY AEROSOL CAN BEFORE DISPOSING OF
THEM.PRESSURIZED AEROSOL CANS ARE NOT ACCEPTABLE WASTE,COMPLY ALL
FEDERAL,STATE & LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department

of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.