

MET-L-CHEK COMPANY -- E-58A EMULSIFIER (SEE SUPPL DATA) -- 6850-01-263-8230

=====
Product Identification
=====

Product ID:E-58A EMULSIFIER (SEE SUPPL DATA)

MSDS Date:10/31/1986

FSC:6850

NIIN:01-263-8230

Kit Part:Y

MSDS Number: BGTCB

=== Responsible Party ===

Company Name:MET-L-CHEK COMPANY

Address:1639 EUCLID STREET

City:SANTA MONICA

State:CA

ZIP:90404-3770

Country:US

Info Phone Num:213-450-1111

E

mergency Phone Num:213-450-1111

CAGE:98733

=== Contractor Identification ===

Company Name:MET-L-CHEK COMPANY

Address:1639 EUCLID ST

Box:00000

City:SANTA MONICA

State:CA

ZIP:90404

Country:US

Phone:310-450-1111/FAX 310452-4046

CAGE:98733

=====
Composition/Information on Ingredients
=====

Ingred Name:ETHYLENE GLYCOL (SARA III)

CAS:107-21-1

RTECS #:KW2975000

Fraction by Wt: 50.0%

OSHA PEL:C 50 PPM

ACGIH TLV:C 50 PPM,VAPOR; 9192

EPA Rpt Qty:1 LB

DOT Rpt Qty:1 LB

=====

==== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:MAY CAUSE SLIGHT SKIN IRRITATION;
VAPORS OR OIL MIST MAY CAUSE MILD IRRITATION OF UPPER RESPIRATORY
TRACT.

Effects of Overexposure:EYES:MAY CAUSE IRRITATION; SKIN:SLIGHT
IRRITATION ON CONTACT WITH LIQUID; INHALATION:VAPORS OR MIST OF
PRODUCT MAY CAUSE MILD IRRITATION OF UPPER RESPIRATOR
Y TRACT. CAN
CAUSE CENTRAL NERVOUS SYSTEM DE PRESSION. INGESTION:MAY RESULT IN
VOMITING.

Medical Cond Aggravated by Exposure:PRE-EXISTING SKIN AND RESPIRATORY
DISORDERS MAY BE AGGRAVATED BY EXPOSURE TO THIS PRODUCT.

==== First Aid Measures =====

First Aid:EYES:FLUSH WITH WATER FOR AT LEAST 15 MINUTES.GET MEDICAL
HELP IR IRRITATION OCCURS OR PERSISTS; SKIN:FLUSH WITH WATER.WASH
WITH LUKE WARM WATER & SOAP.GET MEDICAL HELP FOR PERSISTING

IRRITATION; INHA LATION:REMOVE TO FRESH AIR.PROVIDE OXYGEN IF
BREATHING IS DIFFICULT.GET MEDICAL ASSISTANCE IF NEEDED;
INGESTION:IF SWALLOWED, INDUCE VOMITING.GET MEDICAL ASSISTANCE.

==== Fire Fighting Measures =====

Flash Point Method:PMCC

Flash Point:232F/111.1C

Upper Limits:3.2

Extinguishing Media:WATER FOG,DRY CHEMICAL,CARBON DIOXIDE OR FOAM; DO
NOT USE DIRECT STREAM OF WATER ON THE FIRE.

Fire Fighting Procedures:IN CONFINED AREA,DO NOT E
NTER WITHOUT A FULL

BUNKER GEAR INCLUDING A POSITIVE PRESSURE NIOSH APPROVED
SELF-CONTAINED BREATHING APPARATUS.

Unusual Fire/Explosion Hazard:CONTAINERS MAY BURST AND/OR RUPTURE IN
INTENSE HEAT OF FIRE. PER MANUFACTURER,PRODUCT MAY IGNITE IN AIR
WHEN EXPOSED TO FLAME AT 775F.

==== Accidental Release Measures =====

Spill Release Procedures:ELIMINATE IGNITION SOURCES.WEAR APPROPRIATE
PROTECTIVE CLOTHING AND RESPIRATORS.SOAK UP WITH ABSORBENT.PLAC

E

WASTE IN SEALED CONTAINERS.FLUSH WITH WATER.LG LIQ:DIKE LIQUID & PUMP INTO SALVAGE TANK.ABS ORB RESIDUE WITH COMM ABSORBENT & PUT IN CLOSED DR

=====
===== Handling and Storage =====

Handling and Storage Precautions:KEEP AWAY FROM SOURCES OF HEAT/IGNITION.STORE IN COOL,DRY & VENTILATED AREA.DO NOT STORE NEAR OXIDIZING MATERIAL;AVOID PHYSICAL DAMAGE TO CONTAINERS.
Other Precautions:MINIMIZE SKIN CONTACT.AVOID BREATHING VAPORS.

=====
===== Ex
posure Controls/Personal Protection =====

Respiratory Protection:NOT NEEDED IN NORMAL CONDITIONS OR USES WHEN VAPORS/MIST CONCENTRATIONS ARE BELOW TLV/PEL LIMITS. WEAR NIOSH APPROVED ORGANIC TYPE RESPIRATOR IN ABSENCE OF PROPER ENVIRONMENTAL CONTROL.

Ventilation:LOCAL EXHAUST OR MECHANICAL(GENERAL) TO MAINTAIN TLV OR BELOW TLV LIMITS.

Protective Gloves:CHEMICAL RESISTANT

Eye Protection:SAFETY GLASSES OR SPLASH-PROOF GOGGLES

Other Protective Equipment:CHEMICAL RESISTANT APRON TO PREVENT CLOTHING/SKIN CONTACT.

Work Hygienic Practices:WASH HANDS WITH SOAP & WATER BEFORE EATING, SMOKING OR USING TOILET FACILITIES;DO NOT EAT/DRINK IN VAPOR CONTMNTD AREA.

Supplemental Safety and Health

NSN FOR A KIT OF 2 PARTS UNDER TYPE I,METHOD 1,LEVEL 2 OF MIL-I-25135,REV D;PER QPL-25135-15,THE SET MAY CONSIST OF FP-93A(M) PENETRANT AND E-58A OR E-58D EMULSIFIER (I.E. THE MFR MAY SUPPLY EITHER E- 58A OR E-58D EMULSIFIER WITH FP-93A(M) PENETRANT UNDER T

HIS NSN);KEY1:N1;THIS DATA ENTRY DESCRIBES: E-58A EMULSIFIER.

=====
===== Physical/Chemical Properties =====

HCC:N1

Boiling Pt:B.P. Text:380F(193.3C

Spec Gravity:ABOUT 1.2

Solubility in Water:COMPLETE

Appearance and Odor:LIGHT REDDISH PINK LIQUID. PRACTICALLY ODORLESS

=====
===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
OXIDIZING MATERIAL

Stability Condition to Avoid:SOURCE OF HEAT/IGNITION. AVOID EXPOSURE TO

OXIDANTS.

Hazardous Decomposition Products:OXIDES OF CARBON (CARBON MONOXIDE,CARBON DIOXIDE)

===== Disposal Considerations =====

Waste Disposal Methods:PER MANUFACTURER, THE WASTE CAN BE INCINERATED OR DISPOSED OF AS EPA HAZARDOUS WASTE # D001,IGNITABLE WASTE, IN FULL COMPLIANCE WITH ALL FEDERAL STATE & LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of t

he Department

of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.