

VOLVOLUME OIL COMPANY -- TECTYL 511 M,PETRO BASED RUST PREVENTIVE -- 8030-00-137-1671

=====
Product Identification
=====

Product ID:TECTYL 511 M,PETRO BASED RUST PREVENTIVE

MSDS Date:12/19/1987

FSC:8030

NIIN:00-137-1671

MSDS Number: BGTJT

=== Responsible Party ===

Company Name:VOLVOLUME OIL COMPANY

Address:200 E. MAIN STREET

Box:1400

City:LEXINGTON

State:KY

ZIP:40512

Info Phone Num:606-268-7777

E

mergency Phone Num:606-324-1133

CAGE:KO187

=== Contractor Identification ===

Company Name:VALVOLUME OIL CO

Address:3499 BLAZER PKY

Box:14000

City:LEXINGTON

State:KY

ZIP:40512

Country:US

Phone:606-357-7206 / 800-274-5263

CAGE:72527

Company Name:VOLVOLUME OIL COMPANY

Address:200 E. MAIN STREET

Box:1400

City:LEXINGTON

State:KY

ZIP:40512

Phone:606-268-7777

CAGE:KO187

=====
Composition/Information on Ingredients
=====

Ingred Name:STODDARD SOLVENT

CAS:8052-41-3

RTECS #:WJ8925000

Fr

action by Wt: 40-55%
OSHA PEL:500 PPM
ACGIH TLV:100 PPM; 9293

Ingred Name:ALIPHATIC PETROLEUM DISTILLATES (MINERIL OIL)
CAS:64742-53-6
Fraction by Wt: 10-30%
OSHA PEL:5 MG/CUM
ACGIH TLV:5 MG/CUM

Ingred Name:2-BUTOXYETHANOL
CAS:111-76-2
RTECS #:KJ8575000
Fraction by Wt: 1%
OSHA PEL:S, 50 PPM
ACGIH TLV:S, 25 PPM; 9293

=====
===== Hazards Identification =====
=====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:EYE CONTACT CAN CAUSE SEVERE
IRRITATION,REDNESS,TEARING,BURRED VISION; EXCESSIVE INHALATION OF
VAPORS CAN CAUSE NASAL & RESPIRATORY IRRITATION,CENTRAL NERVOUS
SYSTEM EFFECTS; SWALLOW CAN CAUSE GASTROINTESTINAL
IRRITATION.ASPIRATION OF MATERIAL INTO LUNGS CAN CAUSE CHEMICAL
PNEUMONITIS;PROLONGED SKIN CONTACT;DEFATTING.

Effects of
Overexposure:INH:DIZZINESS,WEAKNESS,FATIGUE,NAUSEA,HEADACHE,POSSIBLE
UNCONSCIOUSNESS,DEATH;ING:NAUSEA,VOMITING & DIARRHEA;
EYE:REDNESS,TEARING,BLURRED VISION.

=====
===== First Aid Measures =====
=====

First Aid:SKIN:WASH EXPOSED AREAS WITH SOAP & WATER.REMOVE CONTAMINATED
CLOTHING.LAUNDER BEFORE REUSE; EYES:FLUSH WITH LARGE AMOUNTS OF
WATER,LIFTING EYELIDS OCCASIONALLY;ING:DO NOT INDUCE VOMITING,KEEP
PERSON WARM,QUIET & GET MEDICAL ATTENTION;INH:REMOVE TO FRESH
AIR.IF BREATHING IS DIFFICULT,ADMINISTER OXYGEN,IF BREATHING HAS
STOPPED,GIVE ARTIFICIAL

AL RESPIRATION.

===== Fire Fighting Measures =====

Flash Point Method:PMCC

Flash Point:>100F/38C

Lower Limits:1.0

Extinguishing Media:FOAM,CO*2 OR DRY CHEMICAL.

Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS WITH A FULL FACEPIECE OPERATED IN THE POSITIVE PRESSURE DEMAND MODE.

Unusual Fire/Explosion Hazard:WATER OR FOAM MAY CAUSE FROTHING.NEVER USE WELDING OR CUTTING TORCH ON OR NEAR DRUM BECAUSE PRODUCT CAN IGNITE EXPLOSIVELY.

==

===== Accidental Release Measures =====

Spill Release Procedures:ELIMINATE ALL IGNITION SOURCES,WEAR PROTECTIVE EQUIPMENT.DIKE AREA TO PREVENT SPREADING.PUMP LIQUID TO SALVAGE TANK,REMAINING SMALL AMOUNT OF LIQUID MAY BE TAKEN UP ON SAND,CLAY,EARTH,ABSORBENT & SHOVELLED INTO CONTAINERS.

===== Handling and Storage =====

Handling and Storage Precautions:DO NOT TRANSFER TO UNLABELED CONTAINER.USE OR STORE ONLY WITH ADEQUATE VENTILATION.DO NOT USE CUTTING OR WELDING TORCH ON THIS CONTAINER.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF TLV IS EXCEEDED,A NIOSH/MSHA APPROVED AIR SUPPLIED RESPIRATOR IS ADVISED IN ABSENCE OF PROPER ENVIRONMENTAL CONTROL.

Ventilation:PROVIDE SUFFICIENT MECHANICAL VENTILATION.

Protective Gloves:NEOPRENE OR NITRILE GLOVES.

Eye Protection:CHEMICAL SPLASH GOGGLES OR SAFETY GLASSE

Supplemental Safety and Health

=====

=== Physical/Chemical Properties =====

HCC:F4

Boiling Pt:B.P. Text:>334F/167C

Vapor Pres:1

Spec Gravity:0.83-0.85

Evaporation Rate & Reference:SLOWER THAN ETHER

Appearance and Odor:LIQUID,HOMOGENEOUS SOLUTION.

Percent Volatiles by Volume:40-55

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS.

Stability Condition to Avoid:NONE STATED.

Hazardous Decomposition Products:NONE STATED.

=====

===== Disposal Considerations =====

Waste Disposal Methods:CONTAMINATED ABSORBENT MAY BE DEPOSITED IN A
LANDFILL IN ACCORDANCE WITH LOCAL,STATE & FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability f

or its use. Any person utilizing this

document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.