

MET-L-CHEK COMPANY -- E-58A EMULSIFIER (SEE SUPP DATA) -- 6850-01-263-8231

=====
Product Identification
=====

Product ID:E-58A EMULSIFIER (SEE SUPP DATA)

MSDS Date:10/31/1986

FSC:6850

NIIN:01-263-8231

Kit Part:Y

MSDS Number: BGTMZ

=== Responsible Party ===

Company Name:MET-L-CHEK COMPANY

Address:1639 EUCLID STREET

City:SANTA MONICA

State:CA

ZIP:90404-3770

Country:US

Info Phone Num:213-450-1111

Eme

rgency Phone Num:213-450-1111

CAGE:98733

=== Contractor Identification ===

Company Name:MET-L-CHEK COMPANY

Address:1639 EUCLID ST

Box:00000

City:SANTA MONICA

State:CA

ZIP:90404

Country:US

Phone:310-450-1111/FAX 310452-4046

CAGE:98733

=====
Composition/Information on Ingredients
=====

Ingred Name:ETHYLENE GLYCOL (SARA III)

CAS:107-21-1

RTECS #:KW2975000

Fraction by Wt: 50.0%

OSHA PEL:C 50 PPM

ACGIH TLV:C 50 PPM,VAPOR; 9192

EPA Rpt Qty:1 LB

DOT Rpt Qty:1 LB

=====

==== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:MAY CAUSE SLIGHT SKIN
IRRITATION;VAPORS OR OIL MIST MAY CAUSE MILD IRRITATION OF UPPER
RESPIRATORY TRACT.
Effects of Overexposure:EYES:PRESUMED NON-IRRITATING;SKIN:SLIGHT
IRRITATION ON LIQUID CONTACT;INHALATION:VAPORS OR OIL MIST MAY
CAUSE MILD IRRITATION OF UPPER RESPIRATORY TRACT;INGEST
ION:MAY
RESULT IN VOMITING.
Medical Cond Aggravated by Exposure:PRE-EXISTING SKIN AND RESPIRATORY
DISORDERS MAY BE AGGRAVATED BY EXPOSURE TO THIS PRODUCT.

=====
===== First Aid Measures =====

First Aid:EYES:FLUSH WITH WATER.GET MEDICAL HELP IF IRRITATION OCCURS
OR PERSISTS; SKIN:FLUSH WITH WATER.WASH WITH WATER & SOAP.GET MED
ATTN FOR PERSISTING IRRITATION; INHALATION:REMOVE TO FRESH
AIR.PROVIDE OXY GEN IF BREATHING IS DIFFICULT.GET MED ATTN
IF
NEEDED;INGESTION:INDUCE VOMITING.GET MEDICAL ATTENTION.

=====
===== Fire Fighting Measures =====

Flash Point Method:PMCC
Flash Point:232F/111.1C
Lower Limits:3.2
Extinguishing Media:WATER FOG,DRY CHEMICAL,CARBON DIOXIDE OR FOAM;DO
NOT USE DIRECT STREAM OF WATER.
Fire Fighting Procedures:IN CONFINED AREA,DO NOT ENTER WITHOUT A FULL
BUNKER GEAR INCLUDING A POSITIVE PRESSURE NIOSH APPROVED
SELF-CONTAINED BREATHING APPARATUS.
Unusual Fire/Explosion Ha
zard:CONTAINERS MAY BURST/RUPTURE IN INTENSE
OF HEAT.PER MFR,WILL IGNITE IN AIR AT ABOUT 775F.

=====
===== Accidental Release Measures =====

Spill Release Procedures:ELIM IGNITION SOURCES.WEAR APPROPRIATE
PROTECTIVE CLOTHING & RESPIRATOR.DIKE & TRANSFER LIQ TO A SALVAGE
TANK.SOAK UP RESIDUE WITH ABSORBENT CLAY,SAND OR OTHR MATL.PLACE
RAGS & ABSORBED WASTE MATERL I N COVERED NON-LEAKING CONTAINERS.

=====
===== Handling and Storage =====

=====

Handling and Storage Precautions:KEEP AWAY FROM HEAT/IGNITION SOURCES.STORE IN DRY,COOL,& VENTILATED LOCATION.DO NOT STORE NEAR OXIDIZING MATERIAL. AVOID PHYSICAL DAMAGE TO CANS.
Other Precautions:MINIMIZE SKIN CONTACT.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NOT NEEDED IN NORMAL CONDITIONS OR USES.USE AN ORGANIC VAPOR CHEMICAL CARTRIDGE OR CANISTER WHEN TLV IS EXCEEDED.
Ventilation:LOCAL EXHAUST OR MECHENICAL(GENERAL) A S REQUIRED TO MAINTAIN TLV OR BELOW TLV.
Protective Gloves:CHEMICAL RESISTANT.
Eye Protection:SPLASHPROOF GOGGLES/SAFETY GLASSES.
Other Protective Equipment:APRONS TO PREVENT CLOTHING/SKIN CONTACT.
Work Hygienic Practices:WASH HANDS WITH SOAP AND WATER BEFORE EATING,SMOKING OR USING TOILET FACILITIES;DONT EAT/DRINK IN VAPOR CONTAMNTD AREA.
Supplemental Safety and Health
NSN FOR A 2 PART KIT OF TYPE I,METHOD D,LVL 3 OF MIL-I-25135D;PER QPL-25135-15, THE SET MAY CONSIST OF FP-95A(M) PENETRANT AND E-58A OR E-58D EMULSIFIER.THE MFR MAY SUPPLY EITHER E-58A OR E-58D EMULSIFIER WITH FP-95A(M) PENETRANT UNDER THIS NSN;KEY1:N1; THIS DATA ENTRY DESCRIBES: E-58A EMULSIFIER;SEE PNI-A FOR PENETRAN

===== Physical/Chemical Properties =====

HCC:N1
Boiling Pt:B.P. Text:380F(193.3C
Spec Gravity:ABOUT 1.2
Solubility in Water:COMPLETE
Appearance and Odor:LIGHT REDDISH PINK LIQUID.PRACTICALLY ODORLESS.
Corrosion Rate:N//K

===== Stabil
ity and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
OXIDIZING MATERIAL.
Stability Condition to Avoid:SOURCE OF HEAT/IGNITION.
Hazardous Decomposition Products:CARBON MONOXIDE,CARBON DIOXIDE.

===== Disposal Considerations =====

Waste Disposal Methods:DISOSE OF AS EPA HAZARDOUS WASTE #D001,IGNITABLE WASTE.PLACE WASTE MATERIAL IN AN APPROPRIATE DISPOSAL FACILITY, OR DISPOSE OF IN COMPLIANCE WITH FEDERAL,STATE & LOCAL REGUL

ATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particula
r situation.