

DOW CORNING CORP -- 93-118 CURING AGENT,PART A -- 8030-01-033-1530

===== Product Identification =====

Product ID:93-118 CURING AGENT,PART A

MSDS Date:08/17/1990

FSC:8030

NIIN:01-033-1530

Kit Part:Y

MSDS Number: BGWSL

=== Responsible Party ===

Company Name:DOW CORNING CORP

Address:3901 SOUTH SAGINAW ROAD

Box:997

City:MIDLAND

State:MI

ZIP:48640

Country:US

Info Phone Num:517-496-5900

Emergency Phone

Num:517-496-5900

Preparer's Name:JACK L. SHENEBERGER

CAGE:5D028

=== Contractor Identification ===

Company Name:DOW CORNING CORP

Address:3901 S SAGINAW RD

Box:997

City:MIDLAND

State:MI

ZIP:48686-0997

Country:US

Phone:517-496-6000/517-496-6315

CAGE:5D028

Company Name:DOW CORNING CORP

Address:2200 W SALZBURG RD

Box:City:AUBURN

State:MI

ZIP:48611

Country:US

Phone:517-496-4388

CAGE:71984

===== Composition/Information on Ingredients =====

Ingred Name:DIMETHYL, METHYL HYDROGEN SILOX

ANE COPOLYMER  
CAS:68037-59-2  
Fraction by Wt: 11%  
Other REC Limits:NONE SPECIFIED

=====  
===== Hazards Identification =====

Routes of Entry: Inhalation:NO Skin:NO Ingestion:NO  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:ACUTE EFFECTS:DIRECT CONTACT WITH EYES  
MAY CAUSE TEMPORARY DISCOMFORT. CHRONIC EFFECTS:NONE KNOWN.  
Explanation of Carcinogenicity:NONE OF THE INGREDIENTS IN THIS PRODUCT  
IS LISTED BY NTP, IARC OR OSHA  
AS A CARCINOGEN.  
Effects of Overexposure:EYES: MAY CAUSE TEMPORARY DISCOMFORT. SKIN:  
SEVERAL, PROLONGED EXPOSURE (HOURS) MAY CAUSE SLIGHT IRRITATION.  
INHALATION: NO IRRITATION TO NOSE OR THROAT EXPECT-ED. NO INJURY IS  
LIKELY FROM RELATIVELY SHORT EXPOSURE. ORAL: AMOUNTS TRANS-FERRED  
TO MOUTH BY FINGERS DURING NORMAL USE SHOULD NOT CAUSE INJURY.  
Medical Cond Aggravated by Exposure:MAY ENHANCE ALLERGIC CONDITIONS ON  
CERTAIN PEOPLE.

=====  
===== First Aid Measures =====

First Aid:EYES: FLUSH WITH WATER. SKIN: WIPE OFF AND FLUSH WITH  
WATER. INHALATION: NO PROBLEM. ORAL: NO PROBLEM:

=====  
===== Fire Fighting Measures =====

Flash Point Method:CC  
Flash Point:>212F,>100C  
Autoignition Temp:Autoignition Temp Text:UNKNON  
Extinguishing Media:USE WATER FOG, CARBON DIOXIDE, FOAM, OR DRY  
CHEMICAL.  
Fire Fighting Procedures:FIRE FIGHTERS SHOULD USE NIOSH APPROVED SCBA &  
FULL PROTECTIVE EQUIPMENT WHEN  
FIGHTING CHEMICAL FIRE. USE WATER  
SPRAY TO COOL NEARBY CONTAINERS EXPOSED TO FIRE.  
Unusual Fire/Explosion Hazard:FIRE OR EXCESSIVE HEAT MAY CAUSE  
PRODUCTION OF HAZARDOUS DECOMPOSITION PRODUCTS.

=====  
===== Accidental Release Measures =====

Spill Release Procedures:USE ABSORBENT MATERIAL TO COLLECT AND CONTAIN  
FOR SALVAGE OR DISPOSAL.

=====  
===== Handling and Storage =====

Handling and Storage Precautions:STORE IN COOL, DRY, WELL

VENTILATED

AREA. PROTECT FROM PHYSICAL DAMAGE, HEAT, IGNITION SOURCES AND INCOMPATIBLE MATERIALS. KEEP CONTAINERS CLOSED.

Other Precautions:PRODUCT EVOLVES MINUTE AMOUNTS OF HYDROGEN GAS. DO NOT REPACKAGE OR STORE IN UNVENTED CONTAINERS. AVOID EYE AND SKIN CONTACT. DO NOT BREATHE VAPORS.

=====  
===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE NORMALLY REQUIRED. NIOSH/MSHA-APPROVED RESPIRATOR OR SCBA AS APPROPRIATE FOR EXPOSURE OF CONCENTRATIONS IF EXPOSURE LEVELS ARE EXCEEDED.

Ventilation:MECHANICAL (GENERAL) VENTILATION RECOMMENDED.

Protective Gloves:NONE SPECIFIED BY MANUFACTURER.

Eye Protection:SAFETY GLASSES, AS A MINIMUM

Other Protective Equipment:NONE SPECIFIED BY MANUFACTURER.

Work Hygienic Practices:WASH THOROUGHLY AFTER HANDLING AND BEFORE EATING. LAUNDER CONTAMINATED CLOTHING BEFORE REUSE.

Supplemental Safety and Health

KEY1:N1. THIS IS PART A OF A 2-PART KIT FOR PART B, SEE PNI B, SAME NSN. CONTACT WITH WATER, SOME METALS, ACIDS OR BASES MAY LIBERATE FLAMMABLE, EXPLOSIVE HYDROGEN GAS.

=====  
===== Physical/Chemical Properties =====

HCC:N1

Vapor Pres: