

CON-LUX COATINGS, INC. -- ENAMEL LUSTERLESS QK DRY 34087 OLIVE DRAB -- 8010-00-902-0182  
===== Product Identification =====

Product ID:ENAMEL LUSTERLESS QK DRY 34087 OLIVE DRAB

MSDS Date:04/25/1984

FSC:8010

NIIN:00-902-0182

MSDS Number: BHDYC

=== Responsible Party ===

Company Name:CON-LUX COATINGS, INC.

Address:TALMADGE ROAD

Box:847

City:EDISON

State:NJ

ZIP:08818

Country:US

Info Phone Num:(201) 287

-4000

Emergency Phone Num:(201) 287-4000

CAGE:60189

=== Contractor Identification ===

Company Name:CON-LUX COATINGS INC

Address:226 TALMADGE RD

Box:847

City:EDISON

State:NJ

ZIP:08818-0847

Country:US

Phone:732-287-4000

CAGE:60189

===== Composition/Information on Ingredients =====

Ingred Name:ALIPHATIC NAPHTHA (LEL 1.0)

(VAPOR PRESSURE 30 @ 100F)

Fraction by Wt: 29.7%

ACGIH TLV:500 PPM

Ingred Name:N-BUTYL ALCOHOL (SARA III)

CAS:71-36-3

RTECS #:EO1400000

Fractio

n by Wt: 7.4%  
OSHA PEL:100 PPM  
ACGIH TLV:S, C 50 PPM; 9293  
EPA Rpt Qty:5000 LBS  
DOT Rpt Qty:5000 LBS

Ingred Name:TOLUENE (SARA III)  
CAS:108-88-3  
RTECS #:XS5250000  
Fraction by Wt: 5.1%  
OSHA PEL:200 PPM/150 STEL  
ACGIH TLV:50 PPM; 9293  
EPA Rpt Qty:1000 LBS  
DOT Rpt Qty:1000 LBS

Ingred Name:LEAD CHROMATE PIGMENT  
(.1-CRO3-.2PB MGM3)  
Fraction by Wt: 1.8%  
OSHA PEL:0.05 MG/M3 (PB)  
ACGIH TLV:0.05MG/M3(CR)A2;8990

=====  
Hazards Identification  
=====

Route  
s of Entry: Inhalation:YES Skin:YES Ingestion:NO  
Effects of Overexposure:EYES: MAY CAUSE IRRITATION  
SKIN: MAY CAUSE IRRITATION  
INHALATION: MAY  
IRRITATE RESPIRATORY TRACT, CAUSING HEADACHE OR DIZZINESS.

=====  
First Aid Measures  
=====

First Aid:EYES: FLUSH WITH PLENTY OF WATER  
SKIN: FLUSH WITH PLENTY OF WATER  
INHALATION: REMOVE TO FRESH AIR. IF  
IRRITATION PERSISTS, CONSULT A PHYSICIAN

=====  
Fire Fighting Measures  
=====

Flash Point Method:TCC  
Flash Point:50F/10C  
Extinguishing Media:FOAM, CO2, DRY CHEMICAL, WATER MIST  
Fire Fighting Procedures:SMOTHER FLAMES WITH ONE OF THE ABOVE  
EXTINGUISHING MEDIA. WATER MAY BE USED TO COOL DOWN UNOPENED  
CONTAINERS IN VICINITY.  
Unusual Fire/Explosion Hazard:CONTAINS FLAMMABLE SOLVENT. DO NOT USE IN  
AREAS WHERE SPARKS OR OPEN FLAMES ARE PRESENT.

=====  
Accidental Release Measures  
=====

=====  
Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION. AVOID  
PROLONGED BREATHING OF VAPORS. VENTILATE AREA.CLEAN UP WITH  
ABSORBENT MATERIAL.

=====  
Handling and Storage =====

Handling and Storage Precautions:STORE IN BUILDINGS DESIGNED AND  
PROTECTED FOR STORAGE OF NFPA CLASS II FLAMMABLE LIQUIDS.  
Other Precautions:STORE IN BUILDINGS DESIGNED AND PROTECTED FOR  
STORAGE OF NFPA CLASS II FLAMMABLE LIQUIDS.

=====  
Exposure Controls/Personal Protection =====

Respiratory Protection:IN OUTDOOR OR OPEN,USE NIOSH APPRVD FILTER  
RESPRTR TO REMOVE SOLID AIRBORNE PAR-TICLES OF OVERSPRAY DURING  
SPRAY APPLICATION.IN RESTRICTED VENTILATION AREAS,USE NIOSH APPRVD  
CHEM FILTERS DESIGNED TO RE MOVE A COMBINATION OF PARTICULATE/VAPOR

Ventilation:GENERAL DILUTION OR LOCAL EXHAUST VENTILATION.

Protective Gloves:REQUIRED FOR LONG OR REPEATED EXPOSURE

Eye Protection:USE SAFETY EYEWEAR

Supplementa

I Safety and Health

PREVENT PROLONGED SKIN CONTACT WITH CONTAMINATED CLOTHING.

=====  
Physical/Chemical Properties =====

Boiling Pt:B.P. Text:230-245F

Vapor Density:>AIR

Evaporation Rate & Reference:SLOWER THAN ETHER

Percent Volatiles by Volume:64.7

=====  
Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

NK

Hazardous Decomposition Products:CO,CO2

=====  
Disposal Considerations =====

=====

Waste Disposal Methods:DISPOSE IN ACCORDANCE W/LOCAL, STATE, AND  
FEDERAL REGULATIONS. DONOT INCINERATE UNOPENED CONTAINERS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should se

ek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.