View NSN Online: https://aerobasegroup.com/nsn/8030-00-822-3505

HERON MANUFACTURING INC. -- NUTS N BOLTS. 223 -- 8030-00-822-3505

Product ID:NUTS N BOLTS. 223 MSDS Date:09/01/1989 FSC:8030 NIIN:00-822-3505 **MSDS Number: BHFSL** === Responsible Party === Company Name: HERON MANUFACTURING INC. Address:865 ESSEX STREET City:BROOKLYN State:NY ZIP:11208-5220 Country:US Info Phone Num:718-649-3000 Emergency Phone Num:718-649-3000 Pr eparer's Name: JOSEF ARNON CAGE: JO919 === Contractor Identification === Company Name: HERNON MANUFACTURING Address:121 TECH DRIVE Box:City:SANFORD State:FL ZIP:32771 Country:US Phone:407-322-4000/800-255-3924 CAGE:61603 Company Name: HERON MANUFACTURING INC. Address:865 ESSEX STREET Box:City:BROOKLYN State:NY ZIP:11208-5220 Country:US Phone:718-649-3000 CAGE: JO919

Ingred Name:POLYGLYCOL DIMETHACRYLATES Fraction by Wt: 60-65% OSH ACGIH TLV:NA Ingred Name: BIS-PHENOL A FUMARATE RESIN Fraction by Wt: 30-35% **OSHA PEL:NA** ACGIH TLV:NA Ingred Name:1-METHYL-1-PHENYLETHYL HYDROPEROXIDE (CUMENE HYDROPEROXIDE) (SARA III) CAS:80-15-9 RTECS #:MX2450000 Fraction by Wt: 3% EPA Rpt Qty:10 LBS DOT Rpt Qty:10 LBS Ingred Name:N,N-DIALKYLTOLUIDINES Fraction by Wt: 2000MG/KG Routes of Entry: Inhalation:NO Skin:YES Ingestion:YES Effects of Overexposure: MAY CAUSE DERMATITIS ON PROLONGED CONTACT IN SENSITIVE INDIVIDUALS = First Aid:INGESTION: DO NOT INDUCE VOMITING. KEEP INDIVIDUAL CALM OBTAIN MEDICAL ATTENTIONINHALATION: DOES NOT APPLY SKIN CONTACT: FLUSH WITH WATEREYE CONTAC T: FLUSH WITH WATER Flash Point Method:TCC Flash Point:>200F Extinguishing Media:CO2, FOAM, AND DRY CHEMICAL Fire Fighting Procedures:NONE LISTED **Unusual Fire/Explosion Hazard:NONE** Spill Release Procedures: SOAK UP IN AN INERT ABSORBENT. STORE IN PARTLY-FILLED, CLOSED CONTAINER UNTIL DISPOSAL. Handling and Storage Precautions: STORAGE: STORE BELOW 110F TO PRESERVE SHELF-LIFE HANDLING: AVOID PROLONGED SKIN CONTACT Other Precautions: KEEP OUT OF THE REACH OF CHILDREN ======= Exposure Controls/Personal Protection =========

A PEL:NA

Ventilation:NOT NORMALLY NECESSARY Protective Gloves:RUBBER OR PLASTIC GLOVES RECOMMENDED Eye Protection:SAFETY GLASSES OR GOGGLES RECOMMENDED Supplemental Safety and Health NK

Boiling Pt:B.P. Text:>300F Vapor Pres: