View NSN Online: https://aerobasegroup.gr/nsn/8010-01-131-6259

Product ID:COATING, POLYURETHANE SAND 33303 ID754208 MSDS Date:10/15/1987 FSC:8010 NIIN:01-131-6259 Kit Part:Y **MSDS Number: BHGFN** === Responsible Party === Company Name: PRATT & LAMBERT, INC. Address:16116 E 13TH ST Box:2153 City:WICHITA State:KS ZIP:67201 Country:US Preparer's Name:CLARA 67201 CAGE:FO127 === Contractor Identification === Company Name: PRATT & LAMBERT, INC/BUFFALO, NY 14240 Box:22 CAGE:FO127 Company Name: PRATT AND LAMBERT INC Address:Box:6027 City:CLEVELAND State:OH ZIP:44101-1027 Country:US Phone:216-566-2902 CAGE:61196

Ingred Name:PROPYLENE GLYCOL METHYL ETHER ACETATE (VP MM HG @ 20 DEG C 2) CAS:108-65-6 RTECS #:AI8925000 OSHA PEL:NONE ESTABLISHED ACGIH TLV:NONE ESTABLLISHED

I

ngred Name:TOLUENE (SARA III) CAS:108-88-3 RTECS #:XS5250000 OSHA PEL:200 PPM/150 STEL ACGIH TLV:50 PPM; 9293 EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS

Ingred Name:METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA III) CAS:78-93-3 RTECS #:EL6475000 OSHA PEL:200 PPM/300 STEL ACGIH TLV:200 PPM/300STEL 9192 EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS

Ingred Name:SILICA, CRYSTALLINE - CRISTOBALITE CAS:14464-46-1 RTECS #:VV7325000 OSHA PEL:SEE TABLE Z3 ACGIH TLV:0.05 MG/M3 RDUST9293

Ingred Name:SILICA, CRYSTALLINE - CRISTOBALITE CAS:14464-46-1 RTECS #:VV7325000 OSHA PEL:SEE TABLE Z3 ACGIH TLV:0.05 MG/M3 RDUST9293

Ingred Name:SILICA, CRYSTALLINE - QUARTZ CAS:14808-60-7 RTECS #:VV7330000 OSHA PEL:SEE TABLE Z3 ACGIH TLV:0.1 MG/M3 RDUST;9293

Ingred Name:TITANIUM DIOXIDE CAS:13463-67-7 RTECS #:XR2275000 OSHA PEL:15 MG/M3 TDUST ACGIH TLV:10 MG/M3 TDUST; 9293

Ingred Name:VOL ORGANIC CMPD 4.5 LB/GL LESS WATER & NPRS* 540 G/L LESS WATER VOC 12.4 LB/GAL SOLIDS 1488 G/L SOLIDS CALCULATED RTECS #: Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Health Hazards Acute and Chronic:SWALLOWING-GASTROINTESTINAL IRRITATION, ASPIRATION OF MATERIAL INTO LUNG MAY CAUSE CHEMICAL PNEUMONITIS. EYE AND SKIN-IRRITATION. HIGH CONCENTRATIONS MAY CAUSE ACUTE CENTRAL NERVOUS SYSTEM DEPRESSION CHARACTERIZED BY HEADACHED,DIZZINESS,NAUSEA AND CONFUSION. Explanation of Carcinogenicity:AT THE TLV THE TIO2 MA

NUFACTURER

CONCLUDES THAT THERE IS NO SIGNIFICANT HAZARD FOR MAN. Effects of Overexposure:INTENTIONAL MISUSE BY DELIBERATELY INHALING THE CONTENTS MAY BE HARMFUL OR FATAL.OVEREXPOSURE TO TOLUENE MAY CAUSE LIVER DAMAGE.OVEREXPOSURE TO SOLVENTS WITH PERMANENT BRAIN/NERVOUS SYSTEM DAMAGE.

Medical Cond Aggravated by Exposure:PREEXISTING RESPIRATORY CONDITIONS MAY BE AGGRAVATED BY EXPOSURE TO CRYSTALLINE SILICA.

First Aid:SWALLOWING-CALL POISON CENTER AND GET MED ATTN. INHALATION-REMOVE TO FRESH AIR AND GET MED ATTN. EYE-FLUSH WITH WATER FOR 15 MIN. GET MED ATTN. SKIN-REMOVE CONTAMINATED CLOTHING, WASH AFFECTED AREA IF IRRITATION PERSISTS.GET MED ATTN. NOTETO PHYSICIAN-ANY TREATMENT THAT MIGHT BE REQUIRED FOR OVEREXPOSURE SHOULD BE DIRECTED AT THE CONTROL OF SYMPTOMS AND THE CLINICAL CONDITIONS

Flash Point:

24F/-4.44C

Extinguishing Media:USE CLASS B FIRE EXTINGUISHERS. POLYMER FOAM IS PREFERRED FOR LARGE FIRES.

Fire Fighting Procedures:WEAR SELF CONTAINED BREATHING APPARATUS. USE WATER TO COOL EXPOSED CONTAINERS TO PREVENT POSSIBLE AUTO IGNITION/EXPLOSION. USE FOG NOZZLES IF WATER IS USED.

Unusual Fire/Explosion Hazard:OVEREXPOSURE TO DECOMPOSITION MAY CAUSE HEALTH HAZARD. SYMPTOMS MAY NOT BE IMMEDIATELY APPARENT. OBTAIN MEDICAL ATTENTION.

========== Accidental Release

Measures ===============

Spill Release Procedures: ELIMINATE ALL IGNITION SOURCES. DIKE AND CONTAIN SPILL WITH INERT MATERIAL. RECOVERY OR DISPOSAL IN A COVERED METAL CONTAINER. USE NON-SPARKING TOOLS. PREVENT CONTAMINATION OF SEWERS, STREAMS, GROUNDWATE R. Neutralizing Agent: NONE LISTED.

Handling and Storage Precautions:DO NOT STORE ABOVE 95F. STORE LARGE QUANTITIES IN COMPLIANCE WITH OSHA 29CFR1910.106.

Oth

er Precautions:DO NOT TAKE INTERNALLY. CLOSE CONTAINER AFTER EACH USE. DO NOT BREATH SANDING DUST. DO NOT RE-USE CONTAINER. DO NOT WELD/BRAZE OR CUT ON EMPTY CONTAINER. NEVER USE PRESSURE TO EMPTY. CONT GROUNDED AND BONDED TO THE RECEIVING CONTAINER.

Respiratory Protection: WHEN SPRAYING OUTDOORS, OR IN OPEN OR WELL-VENTILATED AREAS, USE NIOSH APPROVED MECHANICAL FILTER **RESPIRATOR TO REMOVE OVERSPRAY. REFER** TO OSHA 29CFR1910.134 **RESPIRATORY PROTECTION.** Ventilation: GENERAL DILUTION AND LOCAL EXHAUST VENT IN SUFFICIENT **VOLUME & PATTERN TO MAINTAIN CONCENTRATIONS OF HAZARDOUS SUBSTANCE** Protective Gloves: SOLVENT IMPERMEABLE GLOVES ARE REQUIRED. Eye Protection: WEAR SAFETY SPECTACLES. Other Protective Equipment:NOT LIKELY TO BE NEEDED. Work Hygienic Practices:NONE LISTED. Supplemental Safety and Health THIS URETHANE BASE IS ONE PART OF A TWO COMPONENT MIXTURE. IT IS INTENDED TO BE MIXED WITH AN ACTIVATOR. THE CONTENTS OF THIS PACKAGE MUST BE BLENDED WITH OTHER COMPONENTS BEFORE THE PRODUCT CAN BE US ED. BEFORE OPENING PACKAGES, BE SURE YOU UNDERSTAND THE WARNING MESSAGES AND LABELS OF ALL COMPONENTS.

HCC:F2

Boiling Pt:B.P. Text:175F/281F Vapor Density:>AIR Evaporation Rate & amp; Reference:SLOWER THAN ETHER Percent Volatiles by Volume:63

====

Stability Indicator/Materials to Avoid:YES

STRONG ACIDS OR ALKALINE MATERIALS.

Stability Condition to Avoid:AVOID EXCESSIVE HEAT AND SOURCES OF IGNITION.

Hazardous Decomposition Products:BURNING/WELDING/CUTTING WILL PRODUCE SMOKE,CARBON MONOXIDE AND CARBON DIOXIDE.

Conditions to Avoid Polymerization: KEEP AWAY FROM HEAT, SPARKS AND FLAME.

Waste Disposal Methods: DISPOSE IAW FED/ST/LOCAL LAWS. INCINERATE ONLY IN

EPA FACILITY.DISPOSE IN A HAZARDOUS WASTE LANDFILL. RCRA CLASSIFICATION WOULD BE D001. ENVIRONMENTAL HAZARD NONE KNOWN.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek compete nt professional advice to verify and assume responsibility for the suitability of this information to their particular situation.