

CO-POLYMER CHEMICALS, INC. -- EPOXYN ENAMEL SERIES R PART A -- 8010-00-118-2456

=====  
Product Identification  
=====

Product ID:EPOXYN ENAMEL SERIES R PART A

MSDS Date:01/01/1987

FSC:8010

NIIN:00-118-2456

Kit Part:Y

MSDS Number: BHMDY

=== Responsible Party ===

Company Name:CO-POLYMER CHEMICALS, INC.

Address:12350 MERRIMAN RD

City:LIVONIA

State:MI

ZIP:48150

Country:US

Info Phone Num:313-421-0800

Emer

gency Phone Num:313-421-0800

CAGE:13178

=== Contractor Identification ===

Company Name:CO-POLYMER CHEMICALS INC

Address:12350 MERRIMAN RD

Box:City:LIVONIA

State:MI

ZIP:48150-1923

Country:US

CAGE:13178

=====  
Composition/Information on Ingredients  
=====

Ingred Name:EPOXY RESIN

Fraction by Wt: 28%

Ingred Name:DI ACETONE ALCOHOL

RTECS #:HI5600000

Fraction by Wt: 3%

OSHA PEL:50 PPM

ACGIH TLV:50 PPM

Ingred Name:XYLENES (O-,M-,P- ISOMERS) (SARA III)

CAS:1330-20-7

RTECS #:ZE2100000

Fraction by Wt: 15%  
OSHA PEL:100 PPM/150 STEL  
ACGIH TLV:100 PPM/150STEL;9192  
EPA Rpt Qty:1000 LBS  
DOT Rpt Qty:1000 LBS

Ingred Name:ISOPROPYL ALCOHOL (SARA III)  
CAS:67-63-0  
RTECS #:NT8050000  
Fraction by Wt: 4%  
OSHA PEL:400 PPM/500 STEL  
ACGIH TLV:400 PPM/500STEL;9192

Ingred Name:METHYL ISOBUTYL CARBINOL  
CAS:108-11-2  
RTECS #:SA7350000  
Fraction by Wt: 4%  
OSHA PEL:S,25 PPM/40 STEL  
ACGIH TLV:S,25 PPM/40STEL;9192

Ingred Name:METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA III)  
CAS:78-93-3  
RTECS #:EL  
6475000  
Fraction by Wt: 1%  
OSHA PEL:200 PPM/300 STEL  
ACGIH TLV:200 PPM/300STEL 9192  
EPA Rpt Qty:5000 LBS  
DOT Rpt Qty:5000 LBS

Ingred Name:INERT PIGMENTS  
Fraction by Wt: 44%  
OSHA PEL:200 PPM  
ACGIH TLV:200 PPM

=====  
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES  
Health Hazards Acute and Chronic:EYES: CAN CAUSE SEVERE IRRITATION.  
SKIN: PROLONGED/REPEATED CONTACT CAN CAUSE IRRITATION. DEFATTING  
& POSSIBLE DERMATITIS

. BREATHING EXCESSIVE AMOUNTS OF VAPORS  
MAY CAUSE NASAL & RESPIRATORY IRR I, NAUSEA OR UNCONSC. SWALLOW:  
VOMIT,IRRI, NAUSEA, ASPIRATION INTO LUNGS CAN CAUSE CHEM  
PNEUMONITIS CAN BE FATAL.

Explanation of Carcinogenicity:NA

Effects of Overexposure:OVER EXPOSURE CAN CAUSE INTOXICATION, EYE  
IRRITATION, EYE IRRITATION, REDNESS & OTHER ALLERGIC RESPONSES SUCH  
AS SKIN IRRITATION OR DERMATITIS.

Medical Cond Aggravated by Exposure:RESPIRATORY DISORDERS AND  
DERMATITIS.

=====

===== First Aid Measures =====

First Aid:EYES: FLUSH WITH WATER FOR 15 MIN., CONSULT PHYSICIAN  
IMMEDIATELY. SKIN: WASH WITH SOAP & WATER, LAUNDRER CLOTHING  
BEFORE RE-USE. IF SWALLOWED: DO NOT INDUCE VOMITING. KEEP PERSON  
WARM, QUIET & GET MEDICAL ATTENTION IMMEDIATELY.

===== Fire Fighting Measures =====

Flash Point Method:TOC

Flash Point:73 F/ 23 C

Lower Limits:1.0

Upper Limits:7.0

Extinguishing Media:CARBON DIOXID  
E OR DRY CHEMICAL.

Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS WITH  
FULL FACE PIECE OPERATED IN POSITIVE PRESSURE MODE.

Unusual Fire/Explosion Hazard:VAPORS ARE HEAVIER THAN AIR AND MAY  
TRAVEL ALONG GROUND TO POSSIBLE IGNITION SOURCES DISTANT FROM  
HANDLING POINT.

===== Accidental Release Measures =====

Spill Release Procedures:SOAK UP WITH INNERT ABSORBANT MATERIAL. STORE  
IN COVERED METAL CONTAINER BEFORE DISPOSAL. KEEP AW  
AYFROM OPEN  
FLAME OR SPARKS.

===== Handling and Storage =====

Handling and Storage Precautions:KEEP AWAY FROM EXTREME HEAT, OPEN  
FLAME, SPARKS OROther IGNITION SOURCES.

Other Precautions:DO NOT WELD OR USE CUTTING TORCH ON ANY EMPTY  
CONTAINER.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:RESPIRATOR-BUREAU OF MINES APPROVED FOR ORGANIC  
VAPOR IF IN CONFINED AREA OR SPRAYED.

Ventilation:LOCAL EXH

AUST IF NECESSARY TO CONTROL VAPOR BELOW TLV  
LIMIT.MECHANICAL SUFFICIENT TO MAINTAIN VAPOR BELOW TLV.  
Protective Gloves:IMPERVIOUS VINYL OR BUTYL RUBBER.  
Eye Protection:CHEMICAL SPLASH GOGGLES.  
Other Protective Equipment:IMPERVIOUS APRON OR COVERALLS TO PROTECT  
CLOTHING.  
Work Hygienic Practices:AVOID INHALATION OF VAPORS. DO NOT ALLOW  
CONTACT WITH SKIN OR EYES.  
Supplemental Safety and Health  
NK

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Te  
xt:175 F  
Melt/Freeze Pt:M.P/F.P Text:NA  
Vapor Pres:70  
Vapor Density:1.03  
Spec Gravity:1.5  
Evaporation Rate & Reference:< 1.0 (ETHER=1)  
Solubility in Water:20%  
Appearance and Odor:HEAVY LIQUID - HYDROCARBON ODOR

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES  
STRONG OXIDIZERS OR STRONG ACIDS.  
Stability Condition to Avoid:EXTREME HEAT, OPEN FLAME OR SPARKS.  
Hazardous Decomposition Products:CARBON DIOXIDE, CARBON MONOXIDE & MAY  
FORM OTHER HYDROCARBONBY PRODUCTS.  
Conditions to Avoid Polymerization:EXTREME HEAT, OPEN FLAME OR SPARKS.

===== Disposal Considerations =====

Waste Disposal Methods:INCINERATE IN ACCORDANCE WITH LOCAL, STATE AND  
FEDERAL REGULATIONS. VERY SMALL AMOUNTS MAY BE BURIED IN  
LANDFILL IN ACCORDANCE WITH ALL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the

Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.