

KOP-COAT, INC. -- BITUMASTIC 50 COMMODITY NUMBER 52101001 -- 8030-00-275-8121

=====  
Product Identification  
=====

Product ID:BITUMASTIC 50 COMMODITY NUMBER 52101001

MSDS Date:01/01/1989

FSC:8030

NIIN:00-275-8121

MSDS Number: BHMJC

=== Responsible Party ===

Company Name:KOP-COAT, INC.

Address:436 SEVENTH AVENUE

City:PITTSBURGH

State:PA

ZIP:15219

Country:US

Info Phone Num:1-800-556-7737

Emergency Ph

one Num:1-800-553-5631

CAGE:HO783

=== Contractor Identification ===

Company Name:KOP-COAT INC

Address:436 7TH AVENUE

City:PITTSBURGH

State:PA

ZIP:15219-1818

Country:US

Phone:800-553-5631, CHEMTREC 800-424-9300

CAGE:00297

Company Name:KOP-COAT, INC.

Address:436 SEVENTH AVENUE

City:PITTSBURGH

State:PA

ZIP:15219

Country:US

Phone:800-547-2468

CAGE:HO783

=====  
Composition/Information on Ingredients  
=====

Ingred Name:COAL TAR PITCH VOLATILES (BENZENE SOLUBLE FRACTION),  
ANTHRACE

NE, BAP, PHENANTRACENE, ACRIDINE, CHRYSENE, PYRENE.

CAS:65996-93-2

RTECS #:GF8655000

Fraction by Wt: < 20%

OSHA PEL:0.2 MG/M3

ACGIH TLV:0.2 MG/M3, A1; 9192

Ingred Name:CREOSOTE (SARA III)

CAS:8001-58-9

RTECS #:GF8615000

Fraction by Wt: < 25%

EPA Rpt Qty:1 LB

DOT Rpt Qty:1 LB

Ingred Name:NAPHTHALENE (SARA III)

CAS:91-20-3

RTECS #:QJ0525000

Fraction by Wt: < 2%

OSHA PEL:10 PPM/15 STEL

ACGIH TLV:10 PPM/15 STEL; 9192

EPA Rpt Qty:100 LBS

DOT Rpt Qty:100 LBS

Ingred Name:INDENE

CAS:95-13-6

RTECS #

:NK8225000

Fraction by Wt: < 15%

OSHA PEL:10 PPM

ACGIH TLV:10 PPM; 9192

Ingred Name:BENZENE (SARA III)

CAS:71-43-2

RTECS #:CY1400000

Fraction by Wt: < 0.5%

OSHA PEL:1PPM/5STEL;1910.1028

ACGIH TLV:10 PPM; A2; 9192

EPA Rpt Qty:10 LBS

DOT Rpt Qty:10 LBS

Ingred Name:XYLENES (O-,M-,P- ISOMERS) (SARA III)

CAS:1330-20-7

RTECS #:ZE2100000

Fraction by Wt: < 2%

OSHA PEL:100 PPM/150 STEL

ACGIH TLV:100 PPM/150STEL;9192

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

===== Hazards Identificati

on =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:YES

Health Hazards Acute and Chronic:EYE: IRRITATION &/OR CORNEAL CHANGES. SKIN: IRRITATION, ACCENT BY SUNLIGHT, PHOTOTOXIC SKIN REACTION. PROLONGED SKIN DISORDERS, CANCER. HEATED THERMAL BURNS. ABSORBED INTERNAL ORGAN DAMAGE, POSSIBLE DEATH. INHALATION: RESPIRATORY TRACT IRRITATION, RESPIRATORY DIFFICULTY, CNS, DIZZINESS, UNCONSCIOUSNESS, COLLAPSE, POSSIBLE DEATH, LEUKEMIA. INGESTION: GASTROINTESTINAL DISTURBANCE, IRRITATION

IRRITATION, SEE BELOW

Explanation of Carcinogenicity:IARC MONOGRAPHS STATE THAT THERE IS SUFFICIENT EVIDENCE THAT COAL TAR PITCHES ARE CARCINOGENIC IN HUMANS.

Effects of Overexposure:INGESTION: GASTROINTESTINAL DISTURBANCE, IRRITATION, NAUSEA, VOMITING, ABDOMINAL PAIN & EXTREME CASES CARDIOVASCULAR INVOLVEMENT. SEE ABOVE ALSO. EYE: DIRECT EYE CONTACT MAY CAUSE IRRITATION. SKIN: CHRONIC OVEREXPOSURE MAY LEAD TO LEUKEMIA.

Medical Conditions Aggravated by Exposure:HISTORY OF DISEASE IN LIVER, KIDNEY, SKIN, EYE, CNS, RESPIRATORY SYSTEM, BLOOD-FORMING ORGANS, OR

W/ BLEEDING ABNORMALITIES, OR EXPOSURE TO MATERIAL HARMFUL TO THESE SYSTEMS ARE AT A GREATER THAN NORMAL HEALTH RISK

===== First Aid Measures =====

First Aid:EYE: IMMEDIATELY FLUSH WITH LARGE AMOUNTS OF WATER 15 MIN. SEEK MEDICAL AID. SKIN: WASH THOROUGHLY WITH SOAP & WATER OR WATERLESS HAND CLEANER. MOLTEN PRODUCT, DO NOT REMOVE CONTAMINATED CLOTHES. FLUSH IMMEDIATELY WITH LARGE AMOUNTS OF COLD WATER. POSSIBLE, SUBMERGE AREA IN COLD WATER. PACK WITH ICE. SEEK MEDICAL

AID. INHALATION: REMOVE FROM EXPOSURE. IF BREATH STOP OR DIFFICULTY, ADMINISTER CPR/OXYGEN AS INDICATED. SEEK MEDICAL AID. INGESTION: DO NOT INDUCE VOMITING. 1-2 GLASS MILK

===== Fire Fighting Measures =====

Flash Point Method:PMCC

Flash Point:100 F/ 38 C

Lower Limits:ND

Upper Limits:ND

Extinguishing Media:USE DRY CHEMICAL, CARBON DIOXIDE, FOAM OR WATER SPRAY. WATER OR FOAM MAY CAUSE FROTHING, IF MOLTEN

Fire Fighting Procedures:WEAR COMPLETE FIRE SERVICE PROTECTIVE EQUIPMENT,

FULL-FACE MSHA/NIOSH APPROVED SELF CONTAINED BREATHING APPARATUS.  
WATER TO COOL. TOXIC VAPORS MAY BE GIVEN OFF  
Unusual Fire/Explosion Hazard:WHEN HEATED, VAPOR/DECOMP MAY BE RELEASED  
FORM FLAMM/EXPLOSIVE MIX IN AIR. CLOSED CONTAIN MAY EXPLODE WHEN  
EXPOSED TO EXTREME HEAT. VAP HEAVIER-AIR MAY TRAVEL

===== Accidental Release Measures =====

Spill Release Procedures:STOP LEAK IF NOT RISK. STAY UPWIND. SML: TAKE  
UP W/SAND OR OTHER NONCOMBUST ABSORBENT. F  
LUSH AREA W/WATER. DIKE  
LARGE SPILLS FOR LATER DISPOSAL. CONTAIN RUNOFF FROM FIRE CONTROL  
AND DILUTION WATER

===== Handling and Storage =====

Handling and Storage Precautions:AVOID PROLONGED BREATH OF VAPORS, MIST  
ETC. OR CONTACT. APPLICATION OF CERTAIN PROTECTICE CREAMS BEFORE  
USE, SEVERAL APPLICATIONS BENEFICIAL.

Other Precautions:STORE IN AREA/BLDG DESIGN TO COMPLY WITH OSHA  
1910.106. KEEP IN A CLOSED, LABELED CONT WITHIN A COOL (WELL

SHADED), DRY VENT AEA. PROTECT FROM PHYSICIAL DAMAGE. NOT FOR  
USE/STORAGE IN/AROUND HOME. DO NO T TAKE INTERNALLY. UNDERSTAND  
PRECAUTION

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF VENT DOES NOT MAINTAIN INHAL EXPOSURES BELOW  
TLV(PEL), USE MSHA/NIOSH APPROVED UNTIS. PER INSTRUC/WARNING.  
COMBINATION FILTER/ORGANIC VAPOR CARTRIDGE OR CANISTERS MAY BE  
USED. FULL FACE PIECE RESPI RATORY PROTECTIVE UNITS REQUIRED

Ventilation:SUF

FICIENT GEN/LOCAL EXHAUST VENT IN PATTERN/VOL TO CONTROL  
INHAL EXPOSURER BELOW CURRENT EXPOSRE LIMIT/AREA BELOW FLAMM

Protective Gloves:RESISTANT FLEXIBLE TYPE GLOVES, INDUSTR

Eye Protection:INDUST SAFETY GLASS/SIDE SHIELDS/GOGGLES

Other Protective Equipment:WEAR INDUSTRIAL TY WORK CLOTHING & SAFETY  
FOOTWEAR. DEPENDING ON WORKING COND, IMPERVIOUS PROTECTIVE  
GARMENTS, APRON, ET

Work Hygienic Practices:OBSERVE GOOD PERSONAL HYGIENE PRACTICES AND  
RECOMMENDED PROCEDURES.

Supplemental

Safety and Health

EMPTY CONTAINERS MAY RETAIN PRODUCT RESIDUE INCLUDING FLAMMABLE OR EXPLOSIVE VAPORS. DO NOT CUT, DRILL, GRIND OR WELD ON OR NEAR FULL, PARTIALLY FULL OR EMPTY PRODUCT CONTAINERS. DO NOT USE UNTIL MANUFACTURER'S PRECAUTIONS HAVE BEEN READ/UNDERSTOOD. WASH EXPOSED AREAS PROMPTLY & THOROUGHLY AFTER SKIN CONTACT.

===== Physical/Chemical Properties =====

HCC:F4

Boiling Pt:B.P. Text:NA

Melt/Freeze Pt:M.P/F.P Text:ND

Vapor Pres:NA

Vapor

Density:NA

Spec Gravity:10.7

pH:ND

Evaporation Rate & Reference:VERY SLOW

Solubility in Water:NIL

Appearance and Odor:BLACK LIQUID WITH COAL TAR ODOR

Percent Volatiles by Volume:32

===== Stability and Reactivity Data =====

AVOID OXIDIZING MATERIALS. AVOID CONTACT WITH PVC PIPE.

Hazardous Decomposition Products:TOXIC FUMES

===== Disposal Considerations =====

Waste Disposal Methods:EPA DEFINED INGITE HAZARD WASTE. DISPOSE OF  
IGN

ITEHAZARD IN ACCORD W/LOCAL, STATE & FED REG. TIGHTLYSEALED  
LABLED CONT. IF RELEASE INTO ENVIR MUST REPORT NRC 1-800-424-880.  
IF 100 LBS OR MORE. DISPOSE OF INDUST WASTE ACCD STATE, FED ETC.  
EXCEPT IN CA

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disc

laims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.