

PRATT & LAMBERT, INC. -- EN ALKYD LUST QD BROWN 30277 ID744034 -- 8010-00-291-0889  
===== Product Identification =====

Product ID:EN ALKYD LUST QD BROWN 30277 ID744034

MSDS Date:06/05/1989

FSC:8010

NIIN:00-291-0889

MSDS Number: BHMKR

=== Responsible Party ===

Company Name:PRATT & LAMBERT, INC.

Box:2153

City:WICHITA

State:KS

ZIP:67201

Country:US

Info Phone Num:316-733-1361

Emergency Phone Num:316-73

3-1361

Preparer's Name:W.A. ELLISON

CAGE:FO127

=== Contractor Identification ===

Company Name:PRATT & LAMBERT, INC/BUFFALO, NY 14240

Box:22

CAGE:FO127

Company Name:PRATT AND LAMBERT INC

Address:Box:6027

City:CLEVELAND

State:OH

ZIP:44101-1027

Country:US

Phone:216-566-2902

CAGE:61196

===== Composition/Information on Ingredients =====

Ingred Name:NAPHTHA (PETROLEUM SPIRITS OR BENZIN)

CAS:8030-30-6

RTECS #:SE7555000

Fraction by Wt: 10%

OSHA PEL:100 PPM

Ingred Name:ISOBUTYL ALCOH

OL (SARA III)  
CAS:78-83-1  
RTECS #:NP9625000  
Fraction by Wt: 10%  
OSHA PEL:100 PPM  
ACGIH TLV:50 PPM; 9293  
EPA Rpt Qty:5000 LBS  
DOT Rpt Qty:5000 LBS

Ingred Name:TOLUENE (SARA III)  
CAS:108-88-3  
RTECS #:XS5250000  
Fraction by Wt: 5%  
OSHA PEL:200 PPM/150 STEL  
ACGIH TLV:50 PPM; 9293  
EPA Rpt Qty:1000 LBS  
DOT Rpt Qty:1000 LBS

Ingred Name:N-HEPTANE  
CAS:142-82-5  
RTECS #:MI7700000  
Fraction by Wt: 15%  
OSHA PEL:500 PPM/500 STEL  
ACGIH TLV:400 PPM/500 STEL; 9293

Ingred Name:TITANIUM DIOXIDE  
CAS:13463-67-7  
RTECS #:XR2275000  
Fraction by Wt: 10%  
OSHA PEL:15 MG/M3 TDUST  
ACGIH TLV:10 MG/M3 TDUST; 9293

Ingred Name:TALC (CONTAINING NO ASBESTOS)  
CAS:14807-96-6  
RTECS #:WW2710000  
Fraction by Wt: 25%  
OSHA PEL:2 MG/M3 RDUST  
ACGIH TLV:2 MG/M3 RDUST; 9192

Ingred Name:LEAD (SARA III)  
CAS:7439-92-1  
RTECS #:OF7525000  
Fraction by Wt: AIR  
Evaporation Rate & Reference:SLOWER THEN ETHER  
Percent Volatiles by Volume:61

===== Stability and Reactivity Data =====

Stability Indicator/Materia

Is to Avoid: YES

STRONG ACIDS OR ALKALINE MATERIALS. OXIDIZING MATERIALS.  
ACCELERATORS.

Stability Condition to Avoid: AVOID EXCESSIVE HEAT AND SOURCES OF  
IGNITION.

Hazardous Decomposition Products: BURNING, INCLUDING WHEN HEATED BY  
WELDING/CUTTING, WILL PRODUCE SMOKE, CARBON MONOXIDE AND CARBON  
DIOXIDE.

Conditions to Avoid Polymerization: KEEP AWAY FROM HEAT SPARKS OR FLAME

===== Disposal Considerations =====

Waste Disposal Methods: DISPOSE IN ACCORDANCE WITH FEDERAL, STATE AND LOCAL

REGULATIONS. INCINERATE ONLY IN EPA PERMITTED FACILITY. DO NOT  
INCINERATE CLOSED CONTAINERS. CONTAMINATED ABSORBENT MAY BE  
DISPOSED IN A HAZARDOUS WASTE LANDFILL.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims

all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.