View NSN Online: https://aerobasegroup.gr/nsn/8010-00-298-2295

Product ID: ENAMEL ALKYD GLOSS GREEN 14064 ID742412 MSDS Date:03/23/1988 FSC:8010 NIIN:00-298-2295 **MSDS Number: BHMNM** === Responsible Party === Company Name: PRATT & LAMBERT, INC. Box:2153 **City:WICHITA** State:KS ZIP:67201 Country:US Info Phone Num:316-733-1361 **Emergency Phone Num:31** 6-733-1361 Preparer's Name:W.A. ELLISON CAGE:FO127 === Contractor Identification === Company Name: PRATT & LAMBERT, INC/BUFFALO, NY 14240 Box:22 CAGE:FO127 Company Name: PRATT AND LAMBERT INC Address:Box:6027 City:CLEVELAND State:OH ZIP:44101-1027 Country:US Phone:216-566-2902 CAGE:61196

======= Composition/Information on Ingredients ==========

Ingred Name:VM&P NAPHTHA (LIGROINE) CAS:8032-32-4 RTECS #:OI6180000 OSHA PEL:300 PPM/400 STEL ACGIH TLV:300 PPM; 9192

Ingred Name: MINERAL SPI

RITS (VAPOR PRESSURE 2 MMHG @ 20C) CAS:64475-85-0 RTECS #:PY8240000 OSHA PEL:500 PPM 2950 MG/CU.M ACGIH TLV:100 PPM 525 MG/CU.M. Ingred Name:CARBON BLACK CAS:1333-86-4 RTECS #:FF5800000 OSHA PEL:3.5 MG/M3 ACGIH TLV:3.5 MG/M3; 9192 Ingred Name:VOC. ORGANIC CMPD 4.0 LB/GAL LESS WATER & NPRS\* 480 G/L LESS WATER VOC. 10.6 LB/GAL SOLIDS 1272 G/L SOLIDS CALCU RTECS #:999999VO

Routes of Entry: Inhalation:Y ES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:PROLONGED/REPEATED OCCUP OVEREXPOSURE TO SOLVENTS WITH PERMANENT BRAIN AND NERVOUS SYSTEM DAMAGE. INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATION & INHALING THE CONTENTS MAY BE HARMFUL OR FATAL Explanation of Carcinogenicity:NONE CURRENTLY KNOWN Effects of Overexposure:SWALLOW: GASTROINTESTINAL IRRI, NAUSEA, VOMIT, ASPIRATION INTO LUNG, CHEM PNEUMONITITS, CAN BE FA TAL. INHAL: NOSE/THROAT IRRI. HIGH CONCENT CAUSE ACUTE CENT NERV SYS DEPRESSION CHAR HEADACHE, DIZZ, NA USEA & CONFUSION. EYE: IRRI. SKIN: DEFATTNG AND IRRITATION OF THE SKIN. INHAL OF CAN CAUSE ASPHYXIATION OR ANESTHETIC.

First Aid:SWALLOW: DO NOT INDUCE VOMIT. CALL POISON CONTROL CENTER/HOSPITAL EMERG ROOM/PHYSICIAN IMMED. INHAL: REMOVE TO FRESH AIR IMMED. BREATH HAS STOPPED, GIVE CPR. KEEP WARM, QUI ET. GET MED

ATTN IMMED. EYE: FLUSH W/LARGE AMTS OF WATER, LIFTING LIDS OCCAS, FOR AT LEAST 15 MIN. GET MED ATTN. SKIN: REMOVE CONTAM CLOTHES. WASH AFFECT AREA W/SOAP & WTR. OBTAIN MED ATTN. IRRI PERSISTS.

Flash Point:> 102 F/39 C

Extinguishing Media:NFPA CL B FIRE EXTING (CARBON DIOXIDE, ALL PUR DRY CHEM OR ALCOHOL FOAM) FOR EXTING FLAMM LIQ FIRE. POLYMER FOAM PERFER

Fire Fighting Procedures:SELF CONTAI

N BREATH APPARATUS. WTR MAY BE

INEFFECT, USED TO COOL TO PREVENT PRESSURE

BUILD-UP/AUTO-IGNITE/EXPLOSION FROM HEAT. IF WTR USED, FOG NOZZLES PREFERR

Unusual Fire/Explosion Hazard:EMERG COND, OVEREXP TO DECOMP MAY CAUSE HEALTH HAZARD. SYMP MAY NOT BE IMMED APPARENT. OBTAIN MED ATTN. WARNING! FLAMMABLE. CLOSE CONT. ISOLATE FROM HEAT.

Spill Release Procedures: KEEP SPECTATORS AWAY. ELIM ALL IGNITE SOURCES.

DIKE & CONTAIN SPILL W/INERT MATERIAL. TRANSFER LIQ TO COVER METAL CONTAIN FOR RECOVERY/DISPOSAL. USE NON-SPARK TOOL. PREVENT CONTAM OF SEWERS, STREAMS & GROUNDWATER WITH SPILLED MATERIAL OR USED ABSORB

Handling and Storage Precautions:DO NOT STORE ABOVE 95 DEG F. STORE LARGE QUANTITIES IN COMPLIANCE WITH OSHA 29CFR1910.106 DO NOT TAKE INTERNALLY. CLOSE CONTAINER AFTER EACH USE. Other Precautions:KEEP AWAY

FROM CHILDREN. DO NOT BREATHE SANDING DUST.

WASH HANDS & FACE THOROUGHLY BEFORE EATING/DRINKING. EMPTY CONT MUST NOT BE WASHED & RE-USED FOR ANY PURPOSE. CONT GROUNDED/BONDED TO RECEIVING CO NT. DO NOT WELD/BRAZE/CUT EMPTY CONT.

======= Exposure Controls/Personal Protection ===============

Respiratory Protection:GEN EXP TO ORGANIC CHEM MAY NOT REQUIRE RESPIR PROTECT IF WELL VENT AREA. RESTRICTED VENT AREA NIOSH APPROVED CHEM CARTRIDGE RESPIR MAY BE REQUIRED. SPRAYNG: MECH PREFILTER MAY ALSO BE REQUIRED. CONFI NED: NIOSH APPR AIR SUPPLIED RESPIRATOR Ventilation:GEN DILUTION & LOCAL EXHAUST VENT SUFFICIENT VOLUME/PATTERN KEEP CONCEN HAZARD INGRED BELOW THE LOWEST EXPOSURE LIMIT Protective Gloves:PROLONGED USE, SOLVENT IMPERMEABLE GLOVE Eye Protection:SAFETY GLASSES/CHEM GOGGLES/FACE SHIELDS Other Protective Equipment:AS REQUIRED TO PREVENT SKIN CONTACT. NOT LIKELY TO BE NEEDEDSEE OSHA STANDARD FOR LEAD.

Supplemental Safety and Health THIS PRODUCT,

IF DISCARDED DIRECTLY, WOULD BE CLASSIFIED A HAZARDOUS WASTE BASEDON ITS IGNITABILITY CHAR. THIS PRODUCT CONTAINS LEAD, WHICH, IF PRESENT IN WASTEAT 5.0 MG/1 OR MORE AFTER BEING EXTRACTE D, IS CONSIDERED EP TOXIC, AND THEREFOREA HAZARDOUS WASTE UNDER RCRA REGULATIONS. HAZARD WASTE NO. DOO8

Boiling Pt:B.P. Text:280-388 F Vapor Density:> AIR Evaporation Rate & amp; Reference:SLOWER THAN ETHER Percent Volatiles b y Volume:61

Stability Indicator/Materials to Avoid:YES
STRONG ACIDS OR ALKALINE MATERIALS
Stability Condition to Avoid:NORMALLY STABLE. AVOID EXCESSIVE HEAT & SOURCES OF IGNITION.
Hazardous Decomposition Products:BURNING, INCLUDE WHEN HEATED BY
WELD/CUTTING, WILL PRODUCE SMOKE, CARBON MONOXIDE/DIOXIDE. OXIDES OF LEAD-GENERATED

Conditions to Avoid Polymerization: KEEP AWAY FROM HEAT SPARKS AND FLAME

Waste Disposal Methods:DISPOSE OF ACCOD FED, STATE & LOCAL LAWS. INCIN ONLY EPA PERMITTED FACILITY. DO NOT INCINERATE CLOSED CONT. OBSERVE PRECAUTIONS FOR FLAMM DISPOSAL. CONTAM ABSORB DISPOSE IN HAZARDOUS WASTE LANDFILL. IN ACCORD W/FED, STATE & LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.