

SEYMOUR OF SYCAMORE, INC. -- AERO MED OIL ALKYD RESIN YEL ID GP4891-3538 --
8010-00-852-9033

===== Product Identification =====

Product ID:AERO MED OIL ALKYD RESIN YEL ID GP4891-3538

MSDS Date:09/29/1989

FSC:8010

NIIN:00-852-9033

MSDS Number: BHMWZ

=== Responsible Party ===

Company Name:SEYMOUR OF SYCAMORE, INC.

Address:917 CROSBY AVE.

City:SYCAMORE

State:IL

ZIP:60178

Country:US

Info Phone Num:815

-895-9101

Emergency Phone Num:815-895-9101

CAGE:59581

=== Contractor Identification ===

Company Name:SEYMOUR OF SYCAMORE

Address:917 CROSBY AVE.

Box:City:SYCAMORE

State:IL

ZIP:60178-1343

Country:US

Phone:815-895-9101/800-255-3924

CAGE:59581

===== Composition/Information on Ingredients =====

Ingred Name:LEAD CHROMATE (OSHA PEL FOR LEAD FROM 29CFR
1910.1025),(CRO3 CEILING 0.1 MG/M3)

CAS:7758-97-6

RTECS #:GB2975000

Fraction by Wt: 6.01%

OSHA PEL:0.05 MG/M3 (PB)

ACGIH TLV:0.0

5MG/M3(CR)A2;8990

Ingred Name:TITANIUM DIOXIDE

CAS:13463-67-7

RTECS #:XR2275000

Fraction by Wt: 1.05%

OSHA PEL:15 MG/M3 TDUST

ACGIH TLV:10 MG/M3 TDUST; 9293

Ingred Name:ETHYL BENZENE

CAS:100-41-2

Fraction by Wt: .29%

OSHA PEL:435.00 MG/M3

ACGIH TLV:100.00 PPM

Ingred Name:PROPYLENE OXIDE (SARA III)

CAS:75-56-9

RTECS #:TZ2975000

Fraction by Wt: .14%

OSHA PEL:100 PPM

ACGIH TLV:20 PPM; 9293

EPA Rpt Qty:100 LBS

DOT Rpt Qty:100 LBS

Ingred Name:METHYLENE CHLORIDE (SARA III)

CAS:75-09-2

RTECS #:PA8

050000

Fraction by Wt: 27.26%

OSHA PEL:500 PPM/C,1000; Z2

ACGIH TLV:50 PPM, A2; 9192

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:TOLUENE (SARA III)

CAS:108-88-3

RTECS #:XS5250000

Fraction by Wt: 3.60%

OSHA PEL:200 PPM/150 STEL

ACGIH TLV:50 PPM; 9293

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:METHYL ALCOHOL (METHANOL) (SARA III)

CAS:67-56-1

RTECS #:PC1400000

Fraction by Wt: .13%

OSHA PEL:S,200PPM/250STEL

ACGIH TLV:S,200PPM/250STEL; 93

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000

LBS

Ingred Name:MINERAL SPIRITS

CAS:64742-47-8

Fraction by Wt: 9.68%

OSHA PEL:525.00 MG/M3

ACGIH TLV:100.00 PPM

Ingred Name:ISOPROPYL ALCOHOL (SARA III)

CAS:67-63-0

RTECS #:NT8050000

Fraction by Wt: .30%

OSHA PEL:400 PPM/500 STEL

ACGIH TLV:400 PPM/500STEL;9192

Ingred Name:VARNISH MAKERS & PAINTER

CAS:8032-32-4

RTECS #:OF6180000

Fraction by Wt: .45%

OSHA PEL:1,350.00 MG/M3

ACGIH TLV:300.00 PPM

Ingred Name:DENATURED ETHYL ALCOHOL

CAS:64-17-5

Fraction by Wt: 2.86%

OSHA PEL:1,900.00 MG/M3

ACGI

H TLV:1,000.00 PPM

Ingred Name:XYLENES (O-,M-,P- ISOMERS) (SARA III)

CAS:1330-20-7

RTECS #:ZE2100000

Fraction by Wt: 1.18%

OSHA PEL:100 PPM/150 STEL

ACGIH TLV:100 PPM/150STEL;9192

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:HEXANE (N-HEXANE)

CAS:110-54-3

RTECS #:MN9275000

Fraction by Wt: 4.70%

OSHA PEL:500 PPM

ACGIH TLV:50 PPM; 9293

EPA Rpt Qty:1 LB

DOT Rpt Qty:1 LB

Ingred Name:2-BUTOXYETHANOL

CAS:111-76-2

RTECS #:KJ8575000

Fraction by Wt: 1.00%

OSHA PEL:S, 50 PPM

ACGIH TLV:S, 25 PP

M; 9293

Ingred Name:PROPANE

CAS:74-98-6

RTECS #:TX2275000

Fraction by Wt: 18.0%

OSHA PEL:1000 PPM

ACGIH TLV:ASPHYXIAN; 9192

Ingred Name:ISOBUTANE

CAS:78-25-8

Fraction by Wt: 12.0%

Ingred Name:LEAD CHROMATE

CAS:1344-37-2

Fraction by Wt: 12.0%

OSHA PEL:0.05 MG/M3 (PB)

ACGIH TLV:0.05MG/M3(CR)A2;8990

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Health Hazards Acute and

Chronic:INHAL;HEADACHE,DIZZINESS,NAUSEA,U

NCONSCIOUSNESS.RESP:SEEK

MED ATTN. EYE IRRITATION. SKIN;DEFATTING OF SKIN; INGESTION;SEE

MEDICAL ATTN. EYES, FLUSH W/WTR 15 MINSEEK MED. ATTN. SKIN; WASH

W/SOAP & WTR. SEEK MED. INGESTED; SEEK MED. IMMEDIATE

Effects of Overexposure:INHAL; HEADACHE, DIZZINESS, NAUSEA. SKIN;

IRRIATION AND DERNATITIS.

=====
===== First Aid Measures =====

First Aid:INHAL; REMOVE TO FRESH AIR, BREATHING STOPS, GIVE CPR. EYE;

FLUSH W/WTR 15 MIN. SKIN; WASH W/ SOAP

& WTR.

=====
===== Fire Fighting Measures =====

Flash Point Method:TOC

Flash Point:10F/-12.22C

Extinguishing Media:USE CARBON DIOXIDE, DRY CHEMICAL OR FOAM

Fire Fighting Procedures:WTR SPRAY MAYBE INEFFECT,WTR MAYBE USED TO

COOL CONTAINERS TO PREVENT BURSTING FOG NOZZLES ARE PREFERABLE,

WEAR GOGGLES AND SELF CONTAINED BREATHING APPARATUS

Unusual Fire/Explosion Hazard:EXPORSURE TO HEAT MAY CAUSE BURSTING OF

AEROSOL CAN

=====
===== Accidental Re

Release Measures =====

Spill Release Procedures: REMOVE ALL SOURCES OF IGNITION, AVOID BREATHING VAPORS, VENTILATE AREA, WIPE UP WITH INERT MATERIALS AND PLACE IN APPROPRIATE CONTAINER

===== Handling and Storage =====

Handling and Storage Precautions: DO NOT STORE ABOVE 120 DEG. F. EXPOSURE TO HEAT OR PROLONG EXPOSURE TO SUN MAY CAUSE BURSTING
Other Precautions: INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATING VAPORS AND INHALING CONTAMINANTS CAN BE HARMFUL OR FATAL

===== Exposure Controls/Personal Protection =====

Respiratory Protection: AVOID CONTINUOUS BREATHING OF VAPORS AND SPRAY MIST. A SELF CONTAINED BREATHING APPARATUS REQUIRED FOR CONCENTRATIONS ABOVE TLV LIMITS
Ventilation: USE W/ADEQUATE VENTILATION, SUFFICIENT TO PREVENT INHALATION OF SOLVENT VAPORS
Protective Gloves: OPTIONAL
Eye Protection: WHERE SPRAY MIST MIGHT GET INTO EYES
Supplemental Safety and Health
NK

===== Physical/Chemical Properties =====

HCC: V3
Boiling Pt: B.P. Text: NA
Vapor Density: > AIR
Evaporation Rate & Reference: FASTER THAN ETHER
Percent Volatiles by Volume: 85

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES
STRONG OXIDIZING MATERIALS
Stability Condition to Avoid: DO NOT STORE ABOVE 120F. KEEP FROM SPARKS, PILOT LIGHTS OR OPEN FLAME.
Hazardous Decomposition Products: MAY PRODUCE FUMES W/HEATED TO DECOMPOSITION. FUMES

MAY CONTAIN CARBONDIOXIDE/MONOXIDE/HYDROGEN CHLORIDE
VAPOR,& TRACES PHOSGENE

===== Disposal Considerations =====

Waste Disposal Methods:DO NOT INCINERATE AERSOL, DISPOSE OF IN
ACCORDANCEW/LOCAL, STATE & FEDERAL REGULATIONS. DON'T PLACE AERSOL
CANS IN HOME COMPACTOR. DO NOT PUNCTURE

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.