

PRATT & LAMBERT, INC. -- ENAMEL ALKYD GLOSS BLUE 15123 ID742518 -- 8010-00-853-1859

=====  
Product Identification  
=====

Product ID:ENAMEL ALKYD GLOSS BLUE 15123 ID742518

MSDS Date:03/22/1988

FSC:8010

NIIN:00-853-1859

MSDS Number: BHMXC

=== Responsible Party ===

Company Name:PRATT & LAMBERT, INC.

Address:16116 E 13TH ST

Box:2153

City:WICHITA

State:KS

ZIP:67201

Country:US

Preparer's Name:W.A. ELLISO

N

CAGE:FO127

=== Contractor Identification ===

Company Name:PRATT & LAMBERT, INC/BUFFALO, NY 14240

Box:22

CAGE:FO127

Company Name:PRATT AND LAMBERT INC

Address:Box:6027

City:CLEVELAND

State:OH

ZIP:44101-1027

Country:US

Phone:216-566-2902

CAGE:61196

=====  
Composition/Information on Ingredients  
=====

Ingred Name:VM&P NAPHTHA (LIGROINE)

CAS:8032-32-4

RTECS #:OI6180000

OSHA PEL:300 PPM/400 STEL

ACGIH TLV:300 PPM; 9192

Ingred Name:MINERAL SPIRITS

(VAPOR PRESSURE 2

MMHG @ 20C)  
CAS:64475-85-0  
RTECS #:PY8240000  
OSHA PEL:500 PPM 2950 MG/CU.M  
ACGIH TLV:100 PPM 525 MG/CU.M.

Ingred Name:TITANIUM DIOXIDE  
CAS:13463-67-7  
RTECS #:XR2275000  
OSHA PEL:15 MG/M3 TDUST  
ACGIH TLV:10 MG/M3 TDUST; 9293

Ingred Name:VOC. ORGANIC CMPD 3.9 LB/GAL LESS WATER & NPRS\* 468 G/L  
LESS WATER VOC. 9.8 LB/GAL SOLIDS 1176 G/L SOLIDS CALCU  
RTECS #:9999999VO

=====  
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:  
YES

Health Hazards Acute and Chronic:ASPIRATION OF MATL INTO LUNG MAY CAUSE  
CHEMICAL PNEUMONITIS WHICH CAN BE FATAL. HIGH CONCENT. MAY CAUSE  
ACUTE CNTRL NERVOUS SYS. DEPRESS. PROLONGED/REPEATED  
OVEREXPOSURE TO SOLVENTS W/PERMANENT BRA IN & NERVOUS SYSTEM  
DAMAGE. INTENTIONALMISUSE CAN BE HARMFUL OR FATAL.

Effects of Overexposure:EYE: MAY CAUSE IRRITATION.

SKIN: MAY CAUSE IRRITATION &  
DEFATTING OF SKIN INHAL:  
NOSE/THROAT IRRITATION, HEADACHES ,  
DIZZINESS, NAUSEA &  
CONFUSIONINGST: GASTROINTESTINAL IRRITATION, NAUSEA, AND VOMITING.

=====  
===== First Aid Measures =====

First Aid:EYE: FLUSH W/LG AMNTS OF WTR,LIFTING EYELIDS,FOR 15 MINS.,GET  
MEDICAL ATTENTION.SKIN: WASH AFFECTED AREA W/SOAP & WTR,REMOVE  
CONTAMINATED CLOTHES,GET MED. ATTN INHAL: REMOVE TO FRESH AIR  
IMMEDIATELY,G IVE ARTIFICIAL RESP. IF NEEDED,GET MED.ATTENTION  
IMMEDIATELY  
INGST: DO NOT INDUCE VOMITING

, CALL A PHYSICIAN OR HOSPITAL  
IMMEDIATELY

===== Fire Fighting Measures =====

Flash Point Method:SCC  
Flash Point:AIR  
Evaporation Rate & Reference:SLOWER THEN ETHER  
Percent Volatiles by Volume:59

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES  
STRONG ACIDS OR ALKALINE MATERIALS  
Stability Condition to Avoid:AVOID EXCESSIVE HEAT AND SOURCES OF  
IGNITION.  
Hazardous Decomposition Products:BU  
RNING,INCLUDING WHEN HEATED BY  
WELDING OR CUTTING, WILL PRODUCE SMOKE, CARBON MONOXIDE/DIOXIDE.  
Conditions to Avoid Polymerization:KEEP AWAY FROM HEAT SPARK OR FLAME

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE IN ACCORDANCE W/FEDERAL, STATE & LOCAL  
REGULATIONS. DO NOT INCINERATE CLOSED CONTAINERS. INCINERATE ONLY  
IN EPA PERMITTED FACILITY. CONTAMINATED ABSORBANT MAY BE DISPOSED  
IN A HAZARDOUS WASTE LANDFILL.

Disc

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.