View NSN Online: https://aerobasegroup.com/nsn/8010-00-963-4058

Product ID: KRYLON CRYSTAL CLEAR SPRAY COATING (#1303) MSDS Date:12/04/1986 FSC:8010 NIIN:00-963-4058 MSDS Number: BHPQX === Responsible Party === Company Name: BORDEN, CONSUMER PRODS. DIV., DIV. OF BORDENS INC. Address:180 EAST BROAD STREET City:CO LUMBUS State:OH ZIP:43215-3705 Country:US Info Phone Num:614-431-6680 Emergency Phone Num:614-431-6600 CAGE:EO239 === Contractor Identification === **Company Name: BORDEN INC** Address:180 E BROAD ST Box:208 City:COLUMBUS State:OH ZIP:43215-3705 Country:US Phone:614-225-6124 CAGE:07982 Company Name: BORDEN, CONSUMER PRODS. DIV., DIV. OF BORDENS INC. Address:180 EAST BROAD STREET Box:City:COLUMBUS State:OH ZIP:43215-3705 Country:US Phone:614-431-6680 CAGE:EO239

======= Composition/Information o

n Ingredients =========

Ingred Name:ACETONE (SARA III) CAS:67-64-1 RTECS #:AL3150000 Fraction by Wt: 5-15% OSHA PEL:1000PPM ACGIH TLV:750PPM/1000STEL;9293 EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS

Ingred Name:PROPANE CAS:74-98-6 RTECS #:TX2275000 Fraction by Wt: 5-15% OSHA PEL:1000 PPM ACGIH TLV:ASPHYXIANT; 9192

Ingred Name:ISOBUTANE CAS:75-28-5 RTECS #:TZ4300000 Fraction by Wt: 15-30%

Ingred Name:TOLUENE (SARA III) CAS:108-88-3 RTECS #:XS5250000 Fraction by Wt: 5-15% OSHA PEL:200 PPM /150 STEL ACGIH TLV:50 PPM; 9293 EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS

Ingred Name:N-HEPTANE CAS:142-82-5 RTECS #:MI7700000 Fraction by Wt: 15-30% OSHA PEL:500 PPM/500 STEL ACGIH TLV:400 PPM/500STEL;9293

Ingred Name:HEAVY AROMATIC NAPHTHA CAS:64742-94-5 Fraction by Wt: 1-5%

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:ACUTE:

MAY BE HARMFUL IF INHALED. LIQUID OR VAPOR CAN CAUSE IRRITATION OF NOSE, THROAT AND LUNGS; CENTRAL NERVOUS SYSTEM DEPRESSION. SKIN: CAUSES IRRITATION. EYES: CAUSES IRRITATION. CHRONIC: MAY CAUS E LIVER DAMAGE, KIDNEY DAMAGE, BRAIN DAMAGE.
Explanation of Carcinogenicity:NONE OF THE CHEMICALS IN THIS PRODUCT IS LISTED BY IARC, NTP OR OSHA AS A CARCINOGEN.
Effects of Overexposure:HEADACHE, DIZZINESS, NAUSEA, VOMITING, UNCONSCIOUSNESS AND EVEN ASPHYXIATION, CYANOSIS, RESPIRAT
ORY DISTRESS, DROWSINESS.
Medical Cond Aggravated by Exposure:PERSONS WITH A HISTORY OF SKIN AND RESPIRATORY DISORDERS MAY BE AT INCREASED RISK FROM EXPOSURE.
======================================
First Aid:INHALATION: REMOVE SUBJECT TO FRESH AIR. GIVE ARTIFICIAL RESPIRATION IF NOT BREATHING. EYE: FLUSH WITH PLENTY OF WATER FOR 15 MINUTES. GET IMMEDIATE MEDICAL ATTENTION. SKIN: WASH WITH SOAP AND WATER. INGESTION: DO NOT INDUCE VOMITING. GET I MMEDIATE
MEDICAL ATTENTION.
======================================
Extinguishing Media:CARBON DIOXIDE, FOAM, DRY CHEMICAL. WATER MAY BE INEFFECTIVE BUT SHOULD BE USED TO KEEP FIRE-EXPOSED CONTAINERS COOL.
Fire Fighting Procedures:FIRE FIGHTERS SHOULD USE NIOSH APPROVED SCBA & FULL PROTECTIVE EQUIPMENT WHEN FIGHTING CHEMICAL FIRE. USE WATER SPRAY TO COOL NEARBY CONTAINERS EXPOSED TO FIRE. Unusual Fire/Explosion Hazard:EXTREMELY FLAMMABLE. CONTEN TS UNDER
PRESSURE. EXPOSURE TO HIGH TEMPERATURE MAY CAUSE BURSTING.
======================================
Spill Release Procedures: ELIMINATE ALL IGNITION SOURCES. SOAK UP WITH ABSORBENT MATERIAL AND REMOVE TO A CHEMICAL DISPOSAL AREA. PREVENT ENTRY INTO NATURAL BODIES OF WATER. Neutralizing Agent: NONE SPECIFIED BY MANUFACTURER.
======================================

Handling and Storage Precautions:STORE IN COOL, DRY, WEL

PER CURRENT 29 CFR 1910.134, INSTRUCTIONS/

WARNINGS AND

NIOSH-RESPIRATOR SELECTION.

Ventilation:LOCAL EXHAUST VENTILATION. ENCLOSED SYSTEM DESIGN.

Protective Gloves: IMPERVIOUS

Eye Protection: CHEMICAL SAFETY GOGGLES

Other Protective Equipment:SAFETY SHOWER AND EYE BATH. OTHER EQUIPMENT AS REQUIRED TO MINIMIZE EXPOSURE FROM PROLONGED OR REPEATED CONTACT.

Work Hygienic Practices: WASH THROUGHLY AFTER HANDLING AND BEFORE EATING. LAUNDER CONTAMINATED CLOTHING BEFORE REUSE.

Supplemental Safety and Health

HANDLE IN ACCORDANCE WIT

H GOOD INDUSTRIAL HYGIENE AND SAFETY PRACTICES.

THESE PRACTICES INCLUDE AVOIDING UNNECESSARY EXPOSURE AND REMOVAL OF THE MATERIAL FROM EYES, SKIN AND CLOTHING.

HCC:V3 Vapor Density:> THAN AIR Spec Gravity:< THAN WATER Evaporation Rate & amp; Reference:> THAN BUTYL ACETATE Solubility in Water:SLIGHT

Stability Indicator/Materials to Avoid:YES NONE SPEC IFIED BY MANUFACTURER. Stability Condition to Avoid:HIGH TEMPERATURES, SPARKS, AND OPEN FLAMES Hazardous Decomposition Products:OXIDES OF CARBON.

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH ALL APPLICABLE FEDERAL, STATE AND LOCAL LAWS AND REGULATIONS. EMPTY CONTAINER MAY CONTAIN EXPLOSIVE VAPORS. DO NOT CUT, PUNCTURE OR WELD ON OR NEARBY. INCINERATION WILL C AUSE CONTAINER TO BURST VIOLENTLY.

Disclaimer

(provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.