

FULLER H B CO -- ADHESIVE SC 1806 -- 8040-00-270-8150

=====
Product Identification
=====

Product ID:ADHESIVE SC 1806

MSDS Date:01/01/1987

FSC:8040

NIIN:00-270-8150

MSDS Number: BHQSH

=== Responsible Party ===

Company Name:FULLER H B CO

Address:2400 KASOTA AVE

City:SAINT PAUL

State:MN

ZIP:55108-1511

Country:US

Info Phone Num:612-645-3401 / FAX 612-645-6936

Emergency Phone Num:612-645-3401

CAGE:925

28

=== Contractor Identification ===

Company Name:FULLER H B CO

Address:2400 KASOTA AVE

Box:City:ST PAUL

State:MN

ZIP:55108-1511

Country:US

Phone:612-645-3401

CAGE:92528

=====
Composition/Information on Ingredients
=====

Ingred Name:N-HEPTANE

CAS:142-82-5

RTECS #:MI7700000

Fraction by Wt: 21%

OSHA PEL:500 PPM/500 STEL

ACGIH TLV:400 PPM/500STEL;9293

Ingred Name:TOLUENE (SARA III)

CAS:108-88-3

RTECS #:XS5250000

Fraction by Wt: 26%

OSHA PEL:200 PPM/150 STEL

ACGIH TLV:50 PPM; 9

293
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:ISOPROPYL ALCOHOL (SARA III)
CAS:67-63-0
RTECS #:NT8050000
Fraction by Wt: 32%
OSHA PEL:400 PPM/500 STEL
ACGIH TLV:400 PPM/500STEL;9192

Ingred Name:METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA III)
CAS:78-93-3
RTECS #:EL6475000
Fraction by Wt: 21%
OSHA PEL:200 PPM/300 STEL
ACGIH TLV:200 PPM/300STEL 9192
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:NAPHTA (PETROLEUM SPIRITS OR BENZIN)
CAS:8030-30-6
RTECS #:DE3030000
Fraction
by Wt: 5-10%
OSHA PEL:100 PPM

=====
Hazards Identification
=====

Routes of Entry: Inhalation:NO Skin:NO Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Effects of Overexposure:POSSIBLE DIZZINESS OR HEADACHE

=====
First Aid Measures
=====

First Aid:ADEQUATE VENTILATION

=====
Fire Fighting Measures
=====

Flash Point Method:TCC
Flash Point:22F/-5.56 C
Lower Limits:NA
Up

per Limits:NA

Extinguishing Media:CLEAR AND CHARACTERISTIC LACQUER

Fire Fighting Procedures:DO NOT USE WATER -- EXCEPT FOG NOZZLE

Unusual Fire/Explosion Hazard:NONE

===== Accidental Release Measures =====

Spill Release Procedures:REMOVE ALL SOURCES OF SPARK OR FLAME. ABSORB WITH OIL ABSORBING COMPOUND AND FLUSH WITH WATER

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN RED LABEL AREAS AWAY FROM

SPARKS, FLAME OR EXCESSIVE HEAT

Other Precautions:NA

===== Exposure Controls/Personal Protection =====

Respiratory Protection:AIR MASK OR CANNISTER MASK

Ventilation:LOCAL EXHAUST

Protective Gloves:PLASTIC OR RUBBER

Eye Protection:GOGGLES

Other Protective Equipment:HAND CREAM -- EXPLOSION PROOF EQUIPMENT

Work Hygienic Practices:GOOD PERSONAL HYGIENE PRACTICES

Supplemental Safety and Health

NK

===== Physical/Chemical Properties =====

HCC:F2

Boiling

Pt:B.P. Text:176 F

Spec Gravity:0.88

Evaporation Rate & Reference:2.3

Solubility in Water:PARTIALLY

Appearance and Odor:CLEAR & CHARACTERISTIC LACQUER

Percent Volatiles by Volume:86

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

NK

Hazardous Decomposition Products:NA

===== Disposal Considerations =====

Waste Disposal Methods:FOLLOW PRACTICE FOR FLAMMABLE ORGANIC SOLVENTS

Disclaimer (provide

d with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.