

GENERAL ELECTRIC COMPANY -- 7526 AIR DRYING ADHESIVE -- 8040-00-530-4820

===== Product Identification =====

Product ID:7526 AIR DRYING ADHESIVE

MSDS Date:01/15/1988

FSC:8040

NIIN:00-530-4820

MSDS Number: BHTJD

=== Responsible Party ===

Company Name:GENERAL ELECTRIC COMPANY

Address:3135 EASTON TURNPIKE

City:FAIRFIELD

State:CT

ZIP:06431

Info Phone Num:(518) 438-6500

Emergency Phone Num:(518) 438-65

00

CAGE:24446

=== Contractor Identification ===

Company Name:CHEMICAL COMMODITIES AGENCY, INC.

Address:27447 PACIFIC STREET

Box:City:HIGHLAND

State:CA

ZIP:92346-2640

Country:US

Phone:909-864-2310

CAGE:60777

Company Name:GENERAL ELECTRIC CO

Address:3135 EASTON TURNPIKE

Box:City:FAIRFIELD

State:CT

ZIP:06431

Country:US

Phone:800-626-2000/800-626-2004 (CHRIS)

CAGE:24446

===== Composition/Information on Ingredients =====

Ingred Name:XYLENE, DIMETHYLBENZENE, XYLOL

CAS:1330-20-7

RTE

CS #:ZE2100000
Fraction by Wt: 50%
Other REC Limits:100 PPM
OSHA PEL:100 PPM
ACGIH TLV:100 PPM, SKIN
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:CELLOSOLVE (2-ETHOXYETHANOL), DOWANOL EE, ETHYLENE GLYCOL
ETHYL ETHER, OXITOL

CAS:110-80-5
RTECS #:KK8050000
Fraction by Wt: 10%
Other REC Limits:19 MG/CUM
OSHA PEL:200 PPM
ACGIH TLV:18 MG/CUM
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:LIGHT ALIPHATIC NAPHTHA, VM & P NAPHTHA *4/91*

CAS:64742-89-8
Fraction by Wt: 10%

Ingred Name:
Name:CAPTAN
CAS:133-06-2
RTECS #:GW5075000
Fraction by Wt: 1%
OSHA PEL:5 MG/CUM
ACGIH TLV:5 MG/CUM
EPA Rpt Qty:10 LBS
DOT Rpt Qty:10 LBS

=====
===== Hazards Identification =====
=====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:SKIN: DERMATITIS. INHALATION: CENTRAL
NERVOUS SYSTEM DAMAGE, LIVER & KIDNEY DAMAGE, PULMONARY EDEMA,
REPRODUCTIVE DISORDERS, MALE REPRODUCTIVE

DAMAGE. PRODUCT CONTAINS

A COMPONENT THAT IS A MUTAGEN, T ERATOGEN, & TUMOROGENIC. EYES:
DAMAGE.

Effects of Overexposure:SKIN: DERMATITIS. INHALATION: CENTRAL NERVOUS
SYSTEM DAMAGE, LIVER & KIDNEY DAMAGE, PULMONARY EDEMA,
RESPRODUCTIVE DISORDERS, MALE REPRODUCTIVE DAMAGE. PRODUCT CONTAINS
A COMPONENT THAT IS A MUTAGEN, TERATOGEN, & TUMOROGENIC.

=====
First Aid Measures
=====

First Aid:INGESTION: DON'T INDUCE VOMITING, DRINK PLENTY OF
WATER.

NEVER GIVE ANYTHING BY MOUTH IF UNCONSCIOUS PERSON. ASPIRATION MAY
CAUSE SEVERE LUNG DAMAGE. EMPTY STOMACH AVOIDING ASPIRATION. SKIN:
WASH W/SO AP & WATER. INHALATION: REMOVE TO FRESH AIR. IF BREATHING
STOPS, GIVE ARTIFICIAL RESPIRATION, PREFERABLE MOUTH-TO-MOUTH. IF
BREATHING IS DIFFICULT, GIVE OXYGEN. OBTAIN MEDICAL ATTENTION IN
ALL CASES.

=====
Fire Fighting Measures
=====

Flash Point:61F

Lower Limits:0.9%

Upper Limits:7%

Ex tin

guishing Media:CO2, DRY CHEMICAL, FOAM, OR WATER MIST

Fire Fighting Procedures:WEAR POSITIVE PRESSURE, SELF-CONTAINED
BREATHING APPARATUS. EVACUATE AREA & FIGHT FROM SAFE DISTANCE.
MODE.

Unusual Fire/Explosion Hazard:VAPORS MAY FORM EXPLOSIVE MIXTURE W/AIR.
CONTAINERS CAN BUILD-UP PRESSURE IF EXPOSED TO HEAT/FIRE. EXTREMELY
FLAMMABLE.

=====
Accidental Release Measures
=====

Spill Release Procedures:WIPE, SCRAPE OR SCOOP UP IN AN INERT MATERIAL
&
PUT IN CONTAINER FOR DISPOSAL. WEAR PROTECTIVE EQUIPMENT. REMOVE
ALL SOURCES OF IGNITION. WARN OTHER WORKERS OF SPILL. INCREASE AREA
VENTILATION.

=====
Handling and Storage
=====

Handling and Storage Precautions:KEEP CONTAINERS CLOSED WHEN NOT IN
USE. OPEN CONTAINER CAUTIOUSLY. USE ONLY IN WELL VENTILATED AREA.
USE GROUND TRAP.

Other Precautions:AVOID BREATHING VAPORS. AVOID CONTACT W/SKIN & EYES.
DANGER EXTREMELY FLAMMABLE. KEEP AWAY FROM

FOOD & SMOKING
MATERIALS.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE APPROVED NIOSH RESPIRATORY PROTECTION OR
SELF-CONTAINED BREATHING APPARATUS WHEN >TLV.

Ventilation:MECHANICAL: RECOMMENDED.

Protective Gloves:NEOPRENE

Eye Protection:MONOGOGGLES OR FACE SHIELD

Work Hygienic Practices:REMOVE/LANUDER CONTAMINATED CLOTHING BEFORE
REUSE. WASH HANDS BEFORE EATING & SMOKING.

Supplemental Safety and Health

===== Physical
/Chemical Properties =====

HCC:F2

Boiling Pt:B.P. Text:280F

Vapor Pres:6

Vapor Density:3.7

Appearance and Odor:BLUE ADHESIVE W/AROMATIC ODOR

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

ACIDIC, BASIC OR OXIDIZING AGENTS

Stability Condition to Avoid:HEAT OR FIRE

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE W/LOCAL, STATE, &
FEDERAL REGULAT
IONS. FLAMMABLE LIQUID.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to

their
particular situation.