

CORONADO PAINT CO -- PAINT, RUBBER BASE, MASONRY -- 8010-00-584-3364

=====
Product Identification
=====

Product ID:PAINT, RUBBER BASE, MASONRY

MSDS Date:01/01/1987

FSC:8010

NIIN:00-584-3364

MSDS Number: BHVTB

=== Responsible Party ===

Company Name:CORONADO PAINT CO

Address:308 OLD COUNTY RD

Box:308

City:EDGEWATER

State:FL

ZIP:32032-1812

Country:US

Info Phone Num:904-428-6461

Emergency Phone Num:90

4-428-6461

CAGE:33200

=== Contractor Identification ===

Company Name:CORONADO PAINT COMPANY, INC.

Address:308 OLD COUNTY ROAD

Box:City:EDGEWATER

State:FL

ZIP:32132-1812

Country:US

Phone:904-428-6461

CAGE:33200

=====
Composition/Information on Ingredients
=====

Ingred Name:PIGMENTS

Fraction by Wt: 26.2%

Other REC Limits:NOT HAZARDOUS

Ingred Name:VEHICLE

Fraction by Wt: 01.7%

Other REC Limits:NOT HAZARDOUS

Ingred Name:AROMATIC AND ALIPHATIC HYDROCARBONS (SOLVENTS)

Fraction by

Wt: 42.1%
OSHA PEL:500 PPM
ACGIH TLV:500 PPM

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:NK:Explanation of Carcinogenicity:NONE
OF THE CHEMICALS IN THIS PRODUCT IS LISTED BY IARC, NTP OR OSHA AS
A CARCINOGEN.
Effects of Overexposure:EYE: SEVERE EYE IRRITATION SKIN: CAUSES DRYING
OF THE SKIN. INHALATION: EXCESSIVE I
NHALATION CAUSES HEADACHE,
DIZZINESS, NAUSEA.

===== First Aid Measures =====

First Aid:EYE: EYE CONTACT FLUSH WITH WATER. SKIN: SKIN CONTACT WASH
WITH MILD SOAP AND WATER AND APPLY SKIN CREAM. INHALATION: REMOVE
TO FRESH AIR AND CALL PHYSICIAN. INGESTION: NK

===== Fire Fighting Measures =====

Flash Point Method:SCC
Flash Point:102F 39C
Lower Limits:0.9
Upper Limits:7.0
Extinguishing Media:USE FOAM, CARBON DIO
XIDE, DRY CHEMICAL
Fire Fighting Procedures:TREAT AS CLASS B FIRE.
Unusual Fire/Explosion Hazard:VAPORS MAY FORM EXPLOSIVE MIXTURES WITH
AIR.

===== Accidental Release Measures =====

Spill Release Procedures:WEAR A RESPIRATOR. FLUSH WITH WATER INTO
RETAINING AREA OR CONTAINER. AVOID EXPOSURE TO SPARKS, FIRE OR HOT
METAL SURFACES.
Neutralizing Agent:NONE APPLICABLE FOR THIS MATERIAL

===== Handling and Storage =====

Hand

ling and Storage Precautions:KEEP AWAY FROM HEAT, SPARKS, OPEN FLAME. USE WITH ADEQUATE VENTILATION. AVOID PROLONGED OR REPEATED SKIN CONTACT.

Other Precautions:COMBUSTIBLE LIQUID

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:SELF CONTAINED NIOSH APPROVED RESPIRATOR IF TLV IS EXCEEDED.

Ventilation:LOCAL EXHAUST MAY BE REQUIRED IF WORK AREA IS NOT VENTED.

Protective Gloves:YES

Eye Protection:YES

Other Protective Equipment:SAFETY SHOWER AND EYE BATH.

Supplemental Safety and Health

DO NOT ALLOW STORAGE FOR PROLONGED PERIODS IN NON-INSULATED TRAILERS.

=====
===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:240F,116C

Vapor Pres:6@68F

Vapor Density:3.7

Spec Gravity:1.31

Evaporation Rate & Reference:(N BU AC=1) 0.9

Solubility in Water:VERY SLIGHT

Appearance and Odor:OPAQUE LIQUID. PETROLEUM DISTILLATE ODOR.

Percent Volatiles by Volume:56

=====
===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZERS

Stability Condition to Avoid:HIGH TEMPERATURES, SPARKS, AND OPEN FLAMES

Hazardous Decomposition Products:THERMAL DECOMPOSITION MAY YIELD CARBON MONOXIDE.

=====
===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF IN LANDFILL, INCINERATION UNDER SAFE AND SUPERVISED CONDITIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is form

ulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.