

GARDINER SOLDER COMPANY DIV GARDINER METAL CO -- TIN LEAD ANTIMONY ALLOY,XM-200  
CORE.C.#181 -- 3439-01-087-1536

=====  
Product Identification  
=====

Product ID:TIN LEAD ANTIMONY ALLOY,XM-200 CORE.C.#181

MSDS Date:05/01/1990

FSC:3439

NIIN:01-087-1536

MSDS Number: BHXZM

=== Responsible Party ===

Company Name:GARDINER SOLDER COMPANY DIV GARDINER METAL CO

Address:4820 S CAMPBELL AVE

City:CHICAGO

State:I

L

ZIP:60632-1494

Country:US

Info Phone Num:312-847-0100

Emergency Phone Num:312-847-0100

CAGE:84311

=== Contractor Identification ===

Company Name:GARDINER SOLDER COMPANY DIV GARDINER METAL CO

Address:4820 S CAMPBELL AVE

Box:City:CHICAGO

State:IL

ZIP:60632-1494

Country:US

Phone:312-847-0100 CHEMTREC AFTER HOURS

CAGE:84311

=====  
Composition/Information on Ingredients  
=====

Ingred Name:LEAD (SARA III)

CAS:7439-92-1

RTECS #:OF7525000

Fraction by Wt: 5-94.8%

Other REC Limits:N

ONE SPECIFIED

OSHA PEL:0.05 MG/M3;1910.1025

ACGIH TLV:0.15 MG/M3;DUST 9192

EPA Rpt Qty:1 LB

DOT Rpt Qty:1 LB

Ingred Name:TIN

CAS:7440-31-5

RTECS #:XP7320000

Fraction by Wt: 5-94.8%

Other REC Limits:NONE SPECIFIED

OSHA PEL:2 MG/M3

ACGIH TLV:2 MG/M3; 9192

Ingred Name:ANTIMONY (SARA III)

CAS:7440-36-0

RTECS #:CC4025000

Fraction by Wt: 0.2-2.0%

Other REC Limits:NONE SPECIFIED

OSHA PEL:0.5 MG/M3

=====  
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:UNKNOWN Ingestion:YES  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:SHORT TERM EXPOSURE TO WELDING FUMES,  
GASES OR DUST MAY RESULT IN DISCOMFORT SUCH AS DIZZINESS, NAUSEA,  
FEVER, DRYNESS AND/OR IRRITATION OF NOSE, THROAT AND EYES.METALLIC  
TASTE IN MOUTH .IRRITATION OF RESPIRATORY TRACT.

Explanation  
of Carcinogenicity:LEAD IS REGULATED BY OSHA UNDER  
1910.1025

Effects of Overexposure:EXPOSURE TO WELDING FUMES MAY RESULT IN  
DISCOMFORT SUCH AS DIZZINESS, NAUSEA, FEVER, DRYNESS AND/OR  
IRRITATION OF NOSE, THROAT AND EYES. SKIN SENSITIVITY MAY ALSO BE  
NOTED. WATERY EYES, HEADACHE, BREA THING DIFFICULTY, FREQUENT  
COUGHING AND/OR CHEST PAINS MAY OCCURE FROM ACUTE EXPOSURE. TOXIC  
GASES CAN BE FATAL.

Medical Cond Aggravated by Exposure:SOME WORKERS MAY BE AFFECTED BY A  
PR

E-EXISTING CONDITION OR OTHER OCCUPATIONAL ILLNESS BECAUSE OF THE  
WIDE VARIATION IN INDIVIDUAL SUSCEPTIBILITIES.

=====  
===== First Aid Measures =====

First Aid:IN CASE OF ELECTRICAL SHOCK, TURN OFF POWER PRIOR TO REMOVAL  
FROM EXPOSURE AREA AND ADMINISTRATION OF FIRST AID. REMOVE FROM  
EXPOSURE AREA AND CALL FOR MEDICAL AID. ADMINISTER OXYGEN IF  
BREATHING IS D IFFICULT. IF NOT BREATHING, BEGIN ARTIFICIAL  
RESPIRATION. IF NO DETECTABLE PULSE, BEG  
IN EXTERNAL HEART MASSAGE.  
EMPLOY FIRST AID TECHNIQUES RECOMMENDED BY THE AMERICAN RED CROSS.

=====  
===== Fire Fighting Measures =====

Flash Point:NONE  
Extinguishing Media:NOT FLAMMABLE;DO NOT USE WATER;USE WATER FOG,  
CARBON DIOXIDE, FOAM, OR DRY CHEMICAL.  
Fire Fighting Procedures:FIRE FIGHTERS SHOULD USE NIOSH APPROVED SCBA &  
FULL PROTECTIVE EQUIPMENT WHEN FIGHTING CHEMICAL FIRE. USE WATER  
SPRAY TO COOL NEARBY CONTAINERS EXPOSED TO FIRE.

Unusual Fir

e/Explosion Hazard:NONE EXPECTED;FIRE OR EXCESSIVE HEAT MAY CAUSE PRODUCTION OF HAZARDOUS DECOMPOSITION PRODUCTS.

===== Accidental Release Measures =====

Spill Release Procedures:CLEAN UP ANY GRINDING DUST OR WASTE RESIDUES AND PLACE IN SUITABLE DOT APPROVED CONTAINERS AND DISPOSE OF IN FULL COMPLIANCE WITH FEDERAL, STATE AND LOCAL REGULATIONS. AVOID INHALATION AND SKIN EXPOSURE.

===== Handling and Storage =====

Handling and Storage Precautions:WEAR GLOVES AND FLAME RETARDANT CLOTHING WHEN CUTTING, GRINDING OR WELDING. DO NOT EXPOSE SKIN TO RADIATION WHEN HOT CUTTING OR WELDING.

Other Precautions:PROVIDE PROTECTIVE SCREENS TO SHIELD OTHERS. WHEN ELECTRODES AND FLUXES ARE CONSUMED, THE FUME AND GAS DECOMPOSITION PRODUCTS GENERATED ARE DIFFERENT IN FORM FROM THE INGREDIENTS LISTED. NEW COMPOUNDS NOT IN THE ELECTRODES MAY FORM.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE WELD FUME RESPIRATOR OR AIR SUPPLIED RESPIRATOR WHEN CUTTING, GRINDING OR WELDING IN A CONFINED SPACE OR WHERE LOCAL EXHAUST OR GENERAL VENTILATION DOES NOT KEEP EXPOSURE BELOW RECOMMENDED LIMITS. USE ONLY NIOSH APPROVED RESPIRATORS.

Ventilation:USE ENOUGH VENTILATION WHEN CUTTING, GRINDING OR WELDING TO KEEP THE DUST, FUMES & GASES FROM THE WORKERS BREATHING ZONE

Protective Gloves:WELDERS LEATHER GLOVES

Eye Protection:OSHA APPROVED GOGGLES /FACE SHIELD W/LENS

Other Protective Equipment:FLAME RETARDANT CLOTHING WHEN CUTTING, GRINDING OR WELDING. DO NOT EXPOSE SKIN TO RADIATION WHEN HOT CUTTING OR WELDING.

Work Hygienic Practices:WASH THOROUGHLY BEFORE EATING OR SMOKING. LAUNDRY CONTAMINATED CLOTHING BEFORE REUSE.

Supplemental Safety and Health

WASH AFTER USE .FOLLOW GOOD INDUSTRIAL HYGIENE PRACTICES.

===== Physical/Chemical Properties =====

HCC:N1

Boiling Pt:B.P. Text:2516F,1380C

Melt/Free

ze Pt:M.P/F.P Text:361F,183C

Vapor Pres:1

Spec Gravity:7.55-11.0

Solubility in Water:INSOLUBLE

Appearance and Odor:SILVER GREY SOLID,ODORLESS

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS

Stability Condition to Avoid:HIGH TEMPERATURES

Hazardous Decomposition Products:WELDING AND CUTTING OPERATION MAY  
INCLUDE OXIDES OF THE METALS,METAL FUMES ABOVE 1832F

===== Disposal Considerations ==

=====

Waste Disposal Methods:DISPOSE I/A/W FEDERAL, STATE & LOCAL REGULATIONS

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and

assume responsibility for the suitability of this information to their particular situation.