

DEXTER HYSOL CORPORATION -- XEA 9396 PART A -- 8040-00-209-1286

=====  
Product Identification  
=====

Product ID:XEA 9396 PART A

MSDS Date:02/23/1988

FSC:8040

NIIN:00-209-1286

Kit Part:Y

MSDS Number: BJGVG

=== Responsible Party ===

Company Name:DEXTER HYSOL CORPORATION

Address:2850 WILLOW PASS ROAD

Box:312

City:PITTSBURG

State:CA

ZIP:94565

Info Phone Num:(415) 687-4201

Emergency Phone Num:(415) 687-4201

CAGE:33564

=== Contractor Identification ===

Company Name:DEXTER CORPORATION ADHESIVE & COATING SYSTEMS

Address:2850 WILLOW PASS ROAD

Box:312

City:BAY POINT

State:CA

ZIP:94565-3299

Country:US

Phone:202-483-7616

CAGE:33564

=====  
Composition/Information on Ingredients  
=====

Ingred Name:EPOXY RESIN

CAS:25085-99-8

=====  
Hazards Identification  
=====

Routes of Entry: Inhalation:NO Skin:YES Ingestion:NO

Reports of Carcinogenicity:NTP:NO I

ARC:NO OSHA:NO

Health Hazards Acute and Chronic:SKIN: IRRITATION, ALLERGIC REACTIONS,  
& RASH. EYES: IRRITATION.

Explanation of Carcinogenicity:NONE

Effects of Overexposure:SKIN: IRRITATION, ALLERGIC REACTIONS, & RASH.  
EYES: IRRITATION.

Medical Cond Aggravated by Exposure:ALLERGIC REACTIONS/RASH

=====  
===== First Aid Measures =====

First Aid:EYES: FLUSH W/PLENTY OF WATER. SKIN: WASH THOROUGHLY WITH  
SOAP & WATER, RUBBING ALCOHOL/HAND CLEANER. DON'T USE  
SOLVENTS.  
REMOVE/WASH CONTAMINATED CLOTHING BEFORE REUSE. SEE PHYSICIAN.

=====  
===== Fire Fighting Measures =====

Flash Point Method:TOC

Flash Point:>300F

Extinguishing Media:DRY CHEMICAL, HALON FIRE EXTINGUISHER, WATER SPRAY,  
FOAM, FOG

Fire Fighting Procedures:USE SELF-CONTAINED BREATHING APPARATUS WHEN  
FIGHTING FIRES IN CONFINED AREAS.

Unusual Fire/Explosion Hazard:DENSE SMOKE & TOXIC GASES MAY BE  
LIBERATED.

=====  
===== Accidental Release  
Measures =====

Spill Release Procedures:WEAR PROTECTIVE CLOTHING. SCRAPE UP & TRANSFER  
TO METAL CONTAINER. WIPE UP REMAINING RESIDUE WITH SOLVENTS,  
OBSERVING SOLVENT FLAMMABILITY CAUTIONS.

=====  
===== Handling and Storage =====

Handling and Storage Precautions:KEEP COOL IN ACCORDANCE WITH LABEL  
INSTRUCTIONS. STORE AT 40F FOR 12 MONTHS. FOLLOW RECOMMENDED CURING  
SCHEDULE. AVOID CONTACT WITH SKIN/EYES.

Other Precautions:WASH THOROUGHLY  
AFTER HANDLING. AVOID MIXING RESIN &  
CURING AGENT IN BATCHES >1 LB TOTAL. DON'T HEAT MIXED ADHESIVE  
>125F UNLESS CURING SURFACES TO BE BONDED.

=====  
===== Exposure Controls/Personal Protection =====

Respiratory Protection:NOT NEEDED WITH GOOD INDUSTRIAL VENTILATION.

Ventilation:LOCAL EXHAUST: RECOMMENDED

Protective Gloves:IMPERVIOUS PLASTIC, RUBBER

Eye Protection:SAFETY GLASSES, GOGGLES

Work Hygienic Practices:REMOVE/LAUNDER CONTAMINATED CLOTHING BEFORE  
REUSE.

Suppleme

ntal Safety and Health

KEY1:N1. THIS ENTRY DESCRIBES PART A OF A TWO PART KIT. SEE THIS SAME  
NSN, PART B, FOR PART B DATA.

===== Physical/Chemical Properties =====

HCC:C2

Boiling Pt:B.P. Text:DECOMPOSES

Vapor Pres:1

Evaporation Rate & Reference:NIL

Solubility in Water:NIL

Appearance and Odor:BLUE PASTE WITH SLIGHT ODOR

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS, STR

ONG LEWIS/MINERAL ACIDS

Stability Condition to Avoid:HEAT

Hazardous Decomposition Products:CO, NITROGEN OXIDES, ALDEHYDES, ACIDS,  
TOXIC GASES, & ORGANICS

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF AS HAZARDOUS WASTE ACCORDING TO DOT  
HAZARD CLASS. IF NOT REGULATED BY DOT, DISPOSE OF AS ORM-E.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Depart  
ment

of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.