View NSN Online: https://aerobasegroup.gr/nsn/8010-00-297-2119

IVC INDUSTRIAL COATINGS -- 55183 TT-E-516A LUSTERLESS ENAMEL (BLUE) -- 8010-00-297-2119

========= Product Identification ==============

Product ID:55183 TT-E-516A LUSTERLESS ENAMEL (BLUE)

MSDS Date: 10/26/1985

FSC:8010

NIIN:00-297-2119

MSDS Number: BJMCT === Responsible Party ===

Company Name: IVC INDUSTRIAL COATINGS

Address:2245-50 VALLEY AVENUE

City: INDIANAPOLIS

State:IN ZIP:46218 Country:US

Info Phone Num:317

-636-4407

Emergency Phone Num:317-636-4407

CAGE:1Y253

=== Contractor Identification ===

Company Name: IVC INDUSTRIAL COATINGS

Address:2245-50 VALLEY AVENUE

Box:City:INDIANAPOLIS

State:IN ZIP:46218 Country:US

Phone:317-636-4407

CAGE:1Y253

======= Composition/Information on Ingredients ========

Ingred Name: AROMATICS (VP 19.40 MMHG)

Fraction by Wt: 44.12% Other REC Limits:LEL 1.0 ACGIH TLV:100 PPM

Ingred Name: ALIPHATICS (VP 2.00 MMHG)

Fraction by Wt: .09% Other REC Limits:LEL 1.0

ACG

| ========== Hazards Identification =========== |
|---|
| Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Health Hazards Acute and Chronic:ANESTHESIA: HEADACHE, NAUSEA, DIZZINESS, ETC. LIQUID MODERATELY IRRITATING TO SKIN AND EYES. Effects of Overexposure:ANESTHESIA: HEADACHE, NAUSEA, DIZZINESS, ETC. LIQUID MODERATELY IRRITATING TO SKIN AND EYES. |
| ====================================== |
| First Aid:REMOVE VICTIM AND RESTORE BREATHING IF REQUIRED. REMOVE FROM SKIN WITH SOAP AND WATER. FLUSH EYES WITH COPIOUS QUANTITIES OF WATER, SEE A DOCTOR. |
| ============= Fire Fighting Measures ============== |
| Flash Point:22 F/-6 C Extinguishing Media:A,B,C TYPE EXTINGUISHERS Fire Fighting Procedures:SPRAY AT BASE OF FIRE Unusual Fire/Explosion Hazard:KEEP CONTAINERS TIGHTLY CLOSED. KEEP CONTAINERS ISOLATED FROM HEAT, SPARKS, ELECTRICAL EQUIPMENT AND OPEN FLAME. |
| ========= Accidental Rel ease Measures ============= |
| Spill Release Procedures:WIPE UP IMMEDIATELY AND SAFELY, DISCARD SATURATED ABSORBANTS. IN THE EVEN OF LARGE SPILLS, DIKE AREA AND PUMP MATERIAL TO A WASTE TANK. MAINTAIN SUFFICIENT VENTILATION. |
| ====================================== |
| Handling and Storage Precautions:DO NOT STORE ABOVE 120F. STORE LARGE QUANTITIES IN BLDGS DESIGNED FOR STORAGE OF NFPA CLASS II FLAMMABLE LIQUIDS. DO NOT STORE ANY NEAR FEED OR FOOD. Ot |
| her Precautions:DO NOT TAKE INTERNALLY. CONTAINERS SHOULD BE GROUNDED WHEN POURING. AVOID FREE FALL OF LIQUID IN EXCESS OF A FEW INCHES. DO NOT FLAME CUT, BRAZE OR WELD WITHOUT U.S. BUREAU OF MINES APPROVED RESPIRATO R OR APPROPRIATE VENTILATION. |
| ====== Exposure Controls/Personal Protection ======== |

IH TLV:500 PPM

Respiratory Protection:OUTDOOR/OPEN AREAS USE BUREAU OF MINES APPROVED MECH FILTER RSPRTR TO REMOVE SOLID AIR BORNE PARTICLES DURING SPRAYING. RESTRICTED VENT:CHEM

| -MECH FILTER TO REMOVE COMBINATION OF |
|--|
| PARTICULATE/GAS/VAPOR. CONFINED AREA:AIRLINE TY RSPRTRS/HOODS |
| Ventilation:GEN DILUTION/LOCAL EXHAUST VENT IN VOL/PATTERN TO KEEP |
| TLV/LEL OF MOST HAZARD INGRED BELOW LIMITS. REMOVE DECOMP PRODUCT |
| Protective Gloves:REQUIRED FOR PROLONGED/REPEATED CONTACT |
| Eye Protection:SAFETY EYEWEAR IF SPLASHING OF LIQUID |
| Other Protective Equipment:PREVENT PROLONGED SKIN CONTACT WITH |
| CONTAMINATED CLOTHING. |
| Supplemental Safety and Health |

| ======================================= | Physi |
|---|-------------|
| cal/Chemical Properties | =========== |

Boiling Pt:B.P. Text:193 TO 300F Vapor Density:> THAN AIR Evaporation Rate & Dercent Volatiles by Volume:60.89

======== Stability and Reactivity Data ==========

Stability Indicator/Materials to Avoid:YES
Hazardous Decomposition Products:LIQUID PRODUCT MAY EMIT ACRID FUMES
AND MAY EXPLODE UNDER EXTREME HEAT.

======= Disposal Considerations ===========

Waste Disposal Metho ds:DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS. DO NOT INCINERATE CLOSED CONTAINERS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.