View NSN Online: https://aerobasegroup.gr/nsn/6850-00-782-2740

AMERICAN GAS AND CHEMICAL COMPANY,LTD -- FLAW-FINDER AG-RH CLEANER(POST 3/90) -- 6850-00-782-2740

Product ID:FLAW-FINDER AG-RH CLEANER(POST 3/90) MSDS Date:08/29/1990 FSC:6850 NIIN:00-782-2740 Kit Part:Y **MSDS Number: BJMZY** === Responsible Party === Company Name: AMERICAN GAS AND CHEMICAL COMPANY, LTD Address:220 PEGASUS AVENUE, City:NORTHVALE State:NJ ZIP:07647-190 4 Country:US Info Phone Num:201-767-7300 Emergency Phone Num:201-767-7300 Preparer's Name: GEORGE KOSEL, CHIEF CHEM CAGE:03530 === Contractor Identification === Company Name: AMERICAN GAS AND CHEMICAL COMPANY, LTD Address:220 PEGASUS AVENUE, City:NORTHVALE State:NJ ZIP:07647-1904 Country:US Phone:201-767-7300 CAGE:03530 

Ingred Name:METHYL CHLOROFORM (1,1,1-TRICHLOROEHANE) (SARA III) CAS:71-55-6 RTECS #:KJ2975000 Fraction by Wt: 96.0% Other REC Limits:NONE SPECIFIED OSHA PEL:350 PPM/450 STEL ACGIH TLV:350 PPM/450STEL;9192 EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS **Ozone Depleting Chemical:1** Ingred Name: CHLORODIFLUOROMETHANE CAS:75-45-6 RTECS #:PA6390000 Fraction by Wt: 4.0% OSHA PEL:1000 PPM ACGIH TLV:1000PPM; 9192 **Ozone Depleting Chemical:2** Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic: ACUTE: IRRITATION OF EYES, SKIN, RESPIRATORY TRACT; HEADACHE, DIZZINESS, ANESTHETIC EFFECTS, CNS DEPRESSION; CHRONIC: DEFATTING, DERMATITIS; HEALTH STUDIES HAVE SHOWN THAT MANY HALOGENATED HYDROCARBON S POSE POTENTIAL HUMAN HEALTH RISKS WHICH MAY VARY FROM PERSON TO PERSON. Explanation of Carcinogenicity:MFRG STATED THAT 1,1,1-TRICHLOROETHANE HAS BEEN SUBJECTED TO A CARCINOGENESIS BIOASSAY BY NCI AND FOUND NOT A CARCINOGEN Effects of Overe xposure:INHALATION:HIGH VAPOR CONC CAUSES IRRITATION, HEADACHE, DIZZINESS AND CNS DEPRESSION; SKIN: PROLONGED/REPEATED CONTACT TENDS TO REMOVE SKIN OIL POSSIBLY LEADING TO IRRITATION AND DERMATITIS; EYES: LIQ CONTA CT MAY CAUSE IRRITATION; INGESTION: PRODUCT HAS LOW ORDER OF ACUTE ORAL TOXICITY.MINUTE QTY INSPIRATED IN LUNGS IS FATAL. Medical Cond Aggravated by Exposure:NONE REPORTED BY THE MANUFACTURER. HOWEVER, PRE-EXISTING CONDITIONS MAY BE WORSEN. ==================== Fi 

First Aid:INHALATION: REMOVE TO FRESH AIR: SEEK MEDICAL HELP. IF BREATHING IS IRREGULAR OR HAS STOPPED, START RESUSCITATION AND ADMINISTER OXYGEN IF AVAILABLE; SKIN AND EYES: FLUSH WITH PLENTY OF WATER FOR ABOU T 15 MINUTES. SEEK MEDICAL HELP IF IRRITATION PERSISTS. INGESTION: DO NOT INDUCE VOMITING. IMMEDIATELY CALL A PHYSICIAN.

Flash Point:NONE Lower Limits:7.5

Upper Limits:15.0

Extinguishing Media:USE WATER FOG, CARBON DIOXIDE, FOAM, OR DRY CHEMICAL.

Fire Fighting Procedures:WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AND A FULL FACED SELF CONTAINED BREATHING APPARATUS. COOL FIRE EXPOSED CONTAINERS WITH WATER SPRAY. CONTAIN RUNOFF.

Unusual Fire/Explosion Hazard:NONE CURRENTLY KNOWN.COMBUSTION OR HEAT OF FIRE MAY PRODUCE HAZARDOUS DECOMPOSITION PRODUCTS AND VAPORS.

Spill

Release Procedures:USE PROPER PERSONAL PROTECTION: REMOVE ALL IGNITION SOURCES: RECOVER FREE LIQUID; USE SUITABLE INERT ABSORBENT MATERIAL SUCH AS SAND, SAWDUST, ETC.. TO ABSORB SPILLED LIQUID. VENTILATE CONFINED SPACES .KEEP MATERIAL OUT OF SEWERS AND WATER COURSES.

Handling and Storage Precautions:STORE IN A COOL DRY PLACE BELOW 120F. DO NOT PUNCTURE OR INCINERATE AEROSOL CANS. DO NOT STORE OR HANDLE

NEAR HEAT, SPARKS OR OXIDANTS.

Other Precautions:DO NOT PRESSURIZE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND,OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME, SPARKS OR OTHER SOURCES OF IGNITION:THEY MAY EXPLODE AND CAUSE INJURY OR DEATH.DO NOT ATTEMPT TO CLE AN SINCE RESIDUE IS DIFFICULT TO REMOVE.

Respiratory Protection:USE SUPPLIED-AIR RESPIRATOR PROTECTION IN CONFINED AREA, IF NEEDED. Ventilation:PROVIDE >60FPM HOOD

FACE VELOCITY. LOCAL EXHAUST TO

MAINTAIN PEL/TLV (USE EXPLOSION PROOF EQUIPMENT.)

Protective Gloves: USE CHEMICAL RESISTANT OTHER THAN RUBBER

Eye Protection: FACE SHIELD/SPLASH PROOF GOGGLES.

Other Protective Equipment: USE CHEMICAL RESISTANT APRON OR OTHER IMPERVIOUS CLOTHING, IF NEEDED, TO AVOID CONTAMINATING REGULAR

CLOTHING.

Work Hygienic Practices: WASH THOROUGHLY AFTER EACH USE.

Supplemental Safety and Health

AG-RH CLEANER IS CLASS 1 REMOVER OF MIL-I-25135. PER MFRG, PROPELLANT

HAS BEEN SWITCHED FROM CARBON DIOXIDE TO FREON 22 EFFECTIVE MARCH 90. PER MIL-I-25135, REV E AND QPL-25135-14/15, THIS REMOVER, AG-RH , IS QUALIFIED WITH FORM-D DEVELOPER ANDTY I, METH C, LEVEL 3 PENETRANT. SEE PNIND C FOR OLD CLEANER PROPELLANT. KEY1: J7

HCC:V2 Boiling Pt:B.P. Text:162F,72C Vapor Pres:100MMHG@20 Vapor Density:4.55 Spec Gravity:1.32 (BULK) Evaporation Rate & amp; Reference:1.33 (WATER=1) (BULK) Solubilit y in Water:NEGLIGIBLE Appearance and Odor:COLORLESS LIQUID; SWEET ODOR Percent Volatiles by Volume:>99%

Stability Indicator/Materials to Avoid:YES STRONG OXIDIZING AGENT, STRONG CAUSTICS, REACTIVE METALS LIKE ALUMINUM. Stability Condition to Avoid:EXTREMELY HIGH TEMPERATURES Hazardous Decomposition Products:HYDROGEN CHLORIDE, SMALL AMOUNT OF PHOSGENE AND CHLORINE.

======== Disposal Considerations =========

========

Waste Disposal Methods:DISPOSE OF RECOVERED MATERIAL AT AN APPROVED DISPOSAL SITE OR FACILITY. CAN BE RECLAIMED AND RECYCLED. ASSURE CONFORMITY WITH ALL APPLICABLE LOCAL, STATE AND FEDERAL DISPOSAL REGULATIONS. DO NOT INCIN ERATE EMPTY OR PARTIALLY FILLED AEROSOLCANS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whats oever,

expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.