

J. F. JELENKO AND CO. -- WAX PATTERN CLEANER -- 6520-00-889-7494

=====
Product Identification
=====

Product ID:WAX PATTERN CLEANER

MSDS Date:11/09/1984

FSC:6520

NIIN:00-889-7494

MSDS Number: BJQGL

=== Responsible Party ===

Company Name:J. F. JELENKO AND CO.

Address:99 BUSINESS PARK DRIVE

City:ARMONK

State:NY

ZIP:10504

Info Phone Num:914-273-8600

Emergency Phone Num:914-273-8600

Preparer's Name:M.

KRAMER

CAGE:31976

=== Contractor Identification ===

Company Name:J. F. JELENKO AND CO.

Address:99 BUSINESS PARK DRIVE

Box:City:ARMONK

State:NY

ZIP:10504

Phone:914-273-8600

CAGE:31976

=====
Composition/Information on Ingredients
=====

Ingred Name:6-TRIDECANOL, 3,9-DIETHYL-, HYDROGEN SULFATE, SODIUM SALT
(SODIUM HEPTADECYL SULFATE)

CAS:3282-85-7

RTECS #:YD4550000

Fraction by Wt: 1%

Other REC Limits:NONE SPECIFIED

=====
Hazards Identification
=====

=====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:EYES/SKIN: PROLONGED CONTACT CAN CAUSE
SLIGHT IRRITATION. AVOID BREATHING OF VAPOR.

Explanation of Carcinogenicity:NONE OF THE CHEMICALS IN THIS PRODUCT IS
LISTED BY IARC, NTP OR OSHA AS A CARCINOGEN.

Effects of Overexposure:IRRITATION OF EYES/SKIN/RESPIRATORY TRACT.

Medical Cond Aggravated by Exposure:PERSONS WITH A HISTORY OF SKIN AND

RESPIRATORY DISORDERS MAY BE AT INCREASED RISK FROM EXPOSURE.

===== First Aid Measures =====

First Aid:EYE: IMMEDIATELY FLUSH WITH PLENTY OF WATER FOR 15 MINUTES.
GET MEDICAL ATTENTION. SKIN: WASH WITH SOAP AND WATER. INHALATION:
REMOVE TO FRESH AIR. INGESTION: INDUCE VOMITING. GET MEDICAL
ATTENTION A S REQUIRED.

===== Fire Fighting Measures =====

Extinguishing Media:USE WATER FOG, CARBON DIOXIDE, FOAM,
OR DRY

CHEMICAL AS APPROPRIATE FOR SURROUNDINGS.

Fire Fighting Procedures:WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AND A
FULL FACED SELF CONTAINED BREATHING APPARATUS. COOL FIRE EXPOSED
CONTAINERS WITH WATER SPRAY. CONTAIN RUNOFF.

Unusual Fire/Explosion Hazard:COMBUSTION OR HEAT OF FIRE MAY PRODUCE
HAZARDOUS DECOMPOSITION PRODUCTS AND VAPORS.

===== Accidental Release Measures =====

Spill Release Procedures:MOP OR WIPE UP SPILL.

Neutralizing Agent:NON

E

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN A COOL, DRY, WELL VENTILATED
AREA AWAY FROM SOURCES OF IGNITION. KEEP CONTAINER CLOSED WHEN NOT
IN USE. PROTECT FROM PHYSICAL DAMAGE.

Other Precautions:NONE SPECIFIED BY MANUFACTURER.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF VENTILATION DOES NOT MAINTAIN INHALATION
EXPOSURES BELOW PEL (TLV), USE NIOSH/MSHA APPROVED RE

SPIRATOR AS

PER CURRENT 29 CFR 1910.134, INSTRUCTIONS/WARNINGS AND
NIOSH-RESPIRATOR SELECTION.

Ventilation:MECHANICAL (GENERAL) VENTILATION IS USUALLY ADEQUATE.

Protective Gloves:RUBBER GLOVES

Eye Protection:SAFETY GLASSES/CHEMICAL SPLASH GOGGLES

Other Protective Equipment:NONE SPECIFIED BY MANUFACTURER.

Work Hygienic Practices:NONE SPECIFIED BY MANUFACTURER.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:N1

Boiling Pt:B.P. Text:

212F,100C

Vapor Pres: