View NSN Online: https://aerobasegroup.gr/nsn/6525-01-301-3326

Product ID: FIXER SYSTEMS CLEANER MSDS Date:03/01/1989 FSC:6525 NIIN:01-301-3326 **MSDS Number: BJQKS** === Responsible Party === Company Name: PICKER INTERNATIONAL INC GOVERNMENT SALES DEPT Address:595 MINER ROAD **City:HIGHLAND HEIGHTS** State:OH ZIP:44143-2131 Country:US Info Pho ne Num:609-424-3620 Emergency Phone Num:609-424-3620/800-424-9300(CHEMTREC) CAGE:9R532 === Contractor Identification === Company Name: PICKER INTERNATIONAL INC GOVERNMENT SALES DEPT Address:595 MINER ROAD Box:City:HIGHLAND HEIGHTS State:OH ZIP:44143-2131 Country:US Phone:609-424-3620 CAGE:9R532

Ingred Name:WATER CAS:7732-18-5 RTECS #:ZC0110000 Fraction by Wt: 85-90% % Other REC Limits:NONE SPECIFIED

Ingred Name:SODIUM HYDROXI

DE (SARA III) CAS:1310-73-2 RTECS #:WB4900000 Fraction by Wt: 5-10% % Other REC Limits:NONE SPECIFIED OSHA PEL:2 MG/M3 ACGIH TLV:C 2 MG/M3; 9293 EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:CAUSES BURNS AND IRRITATION. MAY CAUSE ALLER

GIC SKIN REACTION.

Explanation of Carcinogenicity: PRODUCT CONTAINS NO MATERIALS CURRENTLY CLASSIFIED AS CARCINOGENIC BY NTP, IARC OR OSHA.

Effects of Overexposure:SEVERE IRRITATION, BURNS AND IRRITATION, ALLERGIC SKIN REACTIONS.

Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

First Aid:EYES: IMMEDIATELY FLUSH WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES AND GET MEDICAL ATTENTION. SKIN: FLUSH WI TH PLENTY OF

WATER. IF AN ALLERGIC SKIN REACTION DEVELOPS, GET MEDICAL ATTENTION. INHALATI ON: REMOVE FROM EXPOSURE.

Flash Point Method:CC Flash Point:NONE Autoignition Temp:Autoignition Temp Text:NONE Lower Limits:NONE Upper Limits:NONE Extinguishing Media:WATER SPRAY, DRY CHEMICAL, ALCOHOL FOAM, CARBON DIOXIDE Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS AND PROTECTIVE CLOTHING TO PREVENT

CONTACT WITH SKIN AND EYES. Unusual Fire/Explosion Hazard:NONE SPECIFIED BY MANUFACTURER.

======================================
Spill Release Procedures:NEUTRALIZE WITH SODIUM BISULFATE. FLUSH TO SEWER WITH LARGE AMOUNTS OF WATER. Neutralizing Agent:SODIUM BISULFATE.
======================================
Handling and Storage Precautions:AVOID CONTACT WITH EYES AND SKIN. STORE BETWEEN 50-80 F. KEEP ABOVE 40 F. Other Precauti
ons:EMPTY CONTAINERS (THOSE CONTAINING LESS THAN 3 % BY WEIGHT OF THE TOTAL CAPACITY OF THE CONTAINER) ARE NOT REGULATED UNDER HAZARDOUS WASTE REGULATIONS AND MAY BE DISPOSED OF IN THE NORMAL MANNER.
======================================
Respiratory Protection:NONE SPECIFIED BY MANUFACTURER. Ventilation:GOOD GENERAL (MECHANICAL) VENTILATION SHOULD BE SUFFICIENT. Protective Gloves:NITRILE RUBBER Eye Protection:CHEMICAL SPLASH GOGGLES Other Protective Eq uipment:NONE SPECIFIED BY MANUFACTURER. Work Hygienic Practices:AVOID CONTACT WITH EYES AND SKIN. Supplemental Safety and Health NONE SPECIFIED BY MANUFACTURER.
======================================
HCC:B3 Spec Gravity:1.10 pH:12.0 Solubility in Water:COMPLETE

Appearance and Odor:COLORLESS LIQUID, SLIGHT ODOR. Percent Volatiles by Volume:90 %

Stability Indicator/Materials to Avoid:YES ACIDS Sta

bility Condition to Avoid:NONE SPECIFIED BY MANUFACTURER. Hazardous Decomposition Products:NONE SPECIFIED BY MANUFACTURER.

Waste Disposal Methods:NO SPECIFIC METHOD NECESSARY IF NEUTRALIZED. DISCHARGE, TREATMENT OR DISPOSAL MAY BE SUBJECT TO CERTAIN GOVERNMENT REGULATIONS. COMPLY WITH ALL APPLICABLE LOCAL, STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This

information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.