

TRA-CON INC -- TRA-BOND FDA-2 HARDENER -- 1440-00-152-3172

===== Product Identification =====

Product ID:TRA-BOND FDA-2 HARDENER

MSDS Date:04/03/1987

FSC:1440

NIIN:00-152-3172

Kit Part:Y

MSDS Number: BJQMR

=== Responsible Party ===

Company Name:TRA-CON INC

Address:55 NORTH STREET

Box:3933

City:MEDFORD

State:MA

ZIP:02155-4225

Country:US

Info Phone Num:617-391-5550

Emergency Phone Num:617-391-5550

C

AGE:22835

=== Contractor Identification ===

Company Name:EUR-PAC CORP.

Address:112 PORTER ST

Box:City:WATERBURY

State:CT

ZIP:06708

Country:US

Phone:203-756-0102 / FAX 0103

CAGE:8B805

Company Name:TRA-CON INC

Address:55 NORTH ST

Box:3933

City:MEDFORD

State:MA

ZIP:02155-4225

Country:US

Phone:617-391-5550

CAGE:22835

===== Composition/Information on Ingredients =====

Ingred Name:TRIETHYLENE TETRAMINE

CAS:112-24-3

RTECS #:YE6650000

Fraction by Wt: 260C

Extinguishing Media:USE WATE

R FOG, CARBON DIOXIDE, OR DRY CHEMICAL.

Fire Fighting Procedures:WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AND A FULL FACED SELF CONTAINED BREATHING APPARATUS.

Unusual Fire/Explosion Hazard:COMBUSTION OR HEAT OF FIRE MAY PRODUCE HAZARDOUS DECOMPOSITION PRODUCTS AND VAPORS.

===== Accidental Release Measures =====

Spill Release Procedures:PREVENT SKIN AND EYE CONTACT. SOAK UP IN ABSORBENT MATERIAL, OR SCRAPE UP AND TRANSFER TO DISPOSAL CONTAINER. WIPE UP

REMAINING RESIDUE WITH SOLVENTS, OBSERVING SOLVENT FLAMMABILITY CAUTIONS, OR USE D ETERGENT.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

Handling and Storage Precautions:FOR INDUSTRIAL USE ONLY: WARNING! MAY CAUSE BURNS OR IRRITATION. AVOID EYE AND/OR SKIN CONTACT AND PROLONGED INHALATION OF VAPORS.

Other Precautions:STORE IN A COOL PLACE IN CLOSED CONTAINERS.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE NIOSH/MSHA APPROVED AIR-SUPPLIED OR ORGANIC CANISTER MASK RESPIRATOR IN CONFINED AREAS.

Ventilation:LOCAL & MECHANICAL(GENERAL) VENTILATION RECOMMENDED.

Protective Gloves:RUBBER OR PLASTIC DISPOSABLE GLOVES

Eye Protection:SAFETY GLASSES OR GOGGLES

Other Protective Equipment:AS REQUIRED TO PREVENT ALL BODY CONTACT; EYE BATH AND/OR SAFETY SHOWER.

Work Hygienic Practices:WASH THOROUGHLY BEFORE EATING OR SMOKING. DO NOT EAT, DRINK, OR SMOKE IN WORK AREA.

Supplemental Safety and Health

THIS IS PART 2 OF A TWO PART EPOXY ADHESIVE RESIN. SEE P/N IND A, THIS NSN, FOR ADDITIONAL INFORMATION.

===== Physical/Chemical Properties =====

HCC:N1

Boiling Pt:B.P. Text:DECOMPOSES

Vapor Pres:LOW

Vapor Density:>1

Spec Gravity:0.97

Evaporation Rate & Reference:LOW

Solubility in Water:SLIGHT

Appearance and Odor:VISCOUS LIGHT AMBER LIQUID, SLIGHT AMINE ODOR

Percent Volatiles by Volume:LOW

===== St

ability and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES

STRONG ACIDS OR STRONG OXIDIZING AGENTS, CHLORINATED COMPOUNDS.

Stability Condition to Avoid: COPPER AND COPPER ALLOYS; AVOID HIGH TEMPERATURES.

Hazardous Decomposition Products: THERMAL PRODUCTS; NITROGEN OXIDES, ALDEHYDES, CARBON MONOXIDE AND/OR CARBON DIOXIDE.

===== Disposal Considerations =====

Waste Disposal Methods: DISPOSE OF AS HAZARDOUS WASTE ACCORDING TO DOT

HAZARD CLASS. IF NOT REGULATED BY DOT, DISPOSE OF AS ORM-E.

DISPOSAL METHOD CAN BE LAND BURIAL OR CHEMICAL INCINERATION AS REGULATED BY ALL GOVERNMENTAL AGENCIES.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this

document should seek competent professional advice to verify and

assume responsibility for the suitability of this information to their particular situation.