

U.S. OIL CO., INC. -- 250522 FUEL OIL 2 -- 9140-00-247-4365

=====
Product Identification
=====

Product ID:250522 FUEL OIL 2
MSDS Date:03/01/1987
FSC:9140
NIIN:00-247-4365
MSDS Number: BJVZH
=== Responsible Party ===
Company Name:U.S. OIL CO., INC.
Address:425 S. WASHINGTON ST.
Box:25
City:COMBINED LOCKS
State:WI
ZIP:54113
Country:US
Info Phone Num:414-739-6100
Emergency Phone Num:414-739-6100
CAG
E:9V710
=== Contractor Identification ===
Company Name:U S OIL CO INC
Address:558 CARTER CT
Box:City:KIMBERLY
State:WI
ZIP:54136
Country:US
Phone:920-735-8287
CAGE:9V710

=====
Composition/Information on Ingredients
=====

Ingred Name:ALIPHATIC PETROLEUM DISTILLATES
CAS:68476-30-2
Fraction by Wt: >95%
Other REC Limits:100 MG/CUM (NIOSH)
OSHA PEL:500 PPM
ACGIH TLV:500 PPM

=====
Hazards Identification
=====

Routes of Entry: Inhalation:YES Skin

:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:SKIN: IRRITATION,
DEFATTING/DERMATITIS. EYE: IRRITATION. INHALATION:
NASAL/RESPIRATORY IRRITATION,CNS DEPRESSION. INGESTION: GI
IRRITATION/ASPIRATION INTO LUNGS CAUSING CHEMICAL PNEUMONITIS.

Explanation of Carcinogenicity:NONE

Effects of Overexposure:INGESTION: ASPIRATION OF MATERIAL INTO THE
LUNGS CAN CAUSE CHEMICAL PNEUMONITIS & DEATH. SKIN: RASH, ITCHING,
DEFATTING. EY

ES: REDNESS, TEARING, BLURRED VISION. INHALATION:
FATIGUE, NAUSEA, HEADACHE, UNCONSCIOUSNESS, & ASPHYXIATION.

Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

=====
First Aid Measures
=====

First Aid:EYES: FLUSH WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES.
SKIN: WASH WITH SOAP AND WATER. INHALATION: REMOVE TO FRESH AIR.
GIVE CPR OR OXYGEN IF NEEDED. INGESTION: DO NOT INDUCE VOMITING.
KEEP WARM/QU IET. AVOID ASPIRATION OF
MATERIAL INTO THE LUNGS DUE
TO VOMITING. OBTAIN MEDICAL ATTENTION IN ALL CASES.

=====
Fire Fighting Measures
=====

Flash Point:120F,49C

Lower Limits:1.1

Extinguishing Media:REGULAR FOAM, CARBON DIOXIDE, OR DRY CHEMICAL.

Fire Fighting Procedures:WEAR SCBA WITH FULL FACEPIECE OPERATED IN
PRESSURE-DEMAND OR OTHER POSITIVE PRESSURE MODE. WATER OR FOAM MAY
CAUSE FROTHING.

Unusual Fire/Explosion Hazard:VAPORS ARE HEAVIER THAN AIR AND TRAVEL OR
MOVE
BY VENTILATION & BE IGNITED AND FLASH BACK.

=====
Accidental Release Measures
=====

Spill Release Procedures:ABSORB ON PAPER/VERMICULITE/FLOOR ABSORBENT.
ELIMINATE IGNITION SOURCES. STOP SPILL AT SOURCE. CONTAIN SPILL,
PUMP TO SALVAGE TANK. TAKE UP ON SAND, CLAY, EARTH, FLOOR
ABSORBENT/SHOVEL IN CONTAINER. E VACUATE AREA.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

=====
Handling and Storage
=====

Handling and

Storage Precautions:STORE IN A COOL, DRY, WELL-VENTILATED AREA. KEEP AWAY FROM IGNITION SOURCES AND STRONG OXIDIZING AGENTS.
Other Precautions:DON'T TRANSFER TO UNLABELED CONTAINER. DON'T USE CUTTING, WELDING TORCH ON & NEAR DRUM BECAUSE PRODUCT RESIDUE CAN IGNITE EXPLOSIVELY.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:NIOSH/MSHA JOINTLY APPROVED AIR SUPPLIED RESPIRATOR IS ADVISED IN ABSENCE OF PROPER ENVIRONMENTAL CONTROL.
IM

PLEMENT ENGINEERING/ADMINISTRATIVE CONTROLS. OSHA PERMITS OTHER NIOSH/MSHA RESPIRATORS UNDE R SPECIFIC CONDITIONS (29CFR1910.134).

Ventilation:PROVIDE SUFFICIENT LOCAL EXHAUST/MECHANICAL VENTILATION TO KEEP EXPOSURE UNDER TLV.

Protective Gloves:RESISTANT, NEOPRENE, NITRILE RUBBER

Eye Protection:CHEMICAL SPLASH GOGGLES, SAFETY GLASSES

Other Protective Equipment:IMPERVIOUS CLOTHING & BOOTS.

Work Hygienic Practices:REMOVE/LAUNDER CONTAMINATED CLOTHING BEFORE REUSE. GOOD HYGIENIC PRACTIC

ES.

Supplemental Safety and Health

PRODUCT CONTAINS DIESEL FUEL 2. MATERIALS SIMILAR TO DIESEL FUEL 2 HAVE BEEN SHOWN TO PRODUCE SKIN CANCER IN LABORATORY ANIMALS FOLLOWING REPEATED SKIN EXPOSURE WITHOUT WASHING OR REMOVAL.

=====
===== Physical/Chemical Properties =====

HCC:F4

Boiling Pt:B.P. Text:347F,175C

Vapor Pres:0.4 MM HG

Spec Gravity:0.807

Evaporation Rate & Reference:0.02 (N-BUTYL ACETATE=1)

Appearance and Odor:NONE SPECIFIED BY MANUFACTURER.

Percent V

olatiles by Volume:100

=====
===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS

Stability Condition to Avoid:HEAT, PILOT LIGHTS, FLAMES, IGNITION SOURCES, FLARES, & ELECTRICAL SPARKS.

Hazardous Decomposition Products:TOXIC MATERIALS, OXIDES OF CARBON, & VARIOUS HYDROCARBONS.

=====
===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE

AND
FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.