View NSN Online: https://aerobasegroup.gr/nsn/5330-00-559-6120

GERARD PACKING AND BELTING CORP -- PACKING MATERIAL: PART NO. UNKNOWN 5330-00-559-6120

MSDS Date:03/11/1989 FSC:5330 NIIN:00-559-6120 MSDS Number: BJXMP === Responsible Party === Company Name: GERARD PACKING AND BELTING CORP Address:24 MIDLAND AVE City:HICKSVILLE State:NY ZIP:11801 Country:US Info Phone Num:516-935-2400 Emergency Phone Num:516-953-2400 Preparer 's Name:DOD HMIS/DGSC-SSH CAGE:2G277 === Contractor Identification === Company Name: GERARD PACKING AND BELTING CORP Address:24 MIDLAND AVENUE Box:City:HICKSVILLE State:NY ZIP:11801 Country:US Phone:516-935-2400 CAGE:2G277

Ingred Name:ASBESTOS, CHRYSOTILE CAS:12001-29-5 RTECS #:CI6478500 OSHA PEL:0.2 FIBERS/CC ACGIH TLV:2 FIBERS/CC; A1;9192

Ingred Name:OTHER INGREDIENTS NOT SPECIFIED. RTECS #:99999992Z

\_\_\_\_\_

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO
Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:YES
Health Hazards Acute and Chronic: ACUTE: NO ACUTE EFFECTS ARE
KNOWN;CHRONIC: DUST FROM ABRASIVE ACTIONS(EG. CUTTING, MACHINING,
FILING, ETC.) MAY CONTAIN ASBESTOS FIBERS. CHRONIC OVEREXPOSURE TO
AIRBORNE FIBERS MAY LEAD TO ASBESTOSIS & MESOTHELIOMA. SMOKING
COMBINED W/FIBER INHALATION GREATLY INCREASES LUNG CANCER RI
SK!
Explanation of Carcinogenicity:OVEREXPOSURE TO AIRBORNE CONCENTRATIONS
OF ASBESTOS MAY LEAD TO ASBESTOSIS AND MESOTHELIOMA.
Effects of Overexposure: INHAL: INHALATION OF AIRBORNE DUST CONTAINING
ASBESTOS FIBERS ON REPEATED EXPOSURE MAY CAUSE OR CAN LEAD TO
ASBESTOSIS / MESOTHELIOMA; SKIN: PROLONGED EXPOSURE MAY LEAD TO
IRRITATION, WARTS; EYE: P OTENTIAL IRRITATION FROM AIRBOR DUST;
INGEST: N/K.
Medical Cond Aggravated by Exposure: PRE-EXISTING RESPIRATORY
CONDITION
S.

First Aid:INHAL: REMOVE TO FRESH AIR. OBTAIN MEDICAL ADVICE; SKIN: WASH EXPOSED AREA WITH SOAP & WATER; EYE: FLOOD W/ WATER. IF IRRITATION OCCURS, GET MEDICAL ATTN; INGEST: CONSULT A PHYSICIAN; OTHER C HANGE CLOTHING AS REQUIRED TO AVOID CARRYING DUST PARTICLES INTO OTHER AREAS

Flash Point:NONE

Extinguishing Media:MATERIAL IS N

OT FLAMMABLE ; USE MEDIA APPROPRIATE

FOR SURROUNDING FIRE.

Fire Fighting Procedures: COMBUSTION PRODUCTS OF THIS MATERIAL MAY BE TOXIC. USE A SELF-CONTAINED BREATHING APPARATUS WHEN FIGHTING FIRES INVOLVING CHEMICAL PRODUCTS.

Unusual Fire/Explosion Hazard: FIRE MAY RELEASE ASBESTOS FIBERS INTO THE AIR.

Spill Release Procedures: USE PROPER PERSONAL PROTECTION. VACUUM OR WET CLEAN IF DUST IS INVOLVED. ANY VACUU

M SYSTEM SHOULD BE EQUIPPED AN OUTLET "HEPA" FILTER TO PREVENT REINTRODUCING ASBESTOS FIBERS TO THE ATMOSPHERE.

Handling and Storage Precautions:HANDLE IN A MATTER TO MINIMIZE FORMATION OR RETENTION OF AIRBORNE DUST. USE PROPER PERSONAL PROTECTION FOR TA AT HAND. CHECK W/YOUR SAFETY OFFICE!!! Other Precautions:AS MANUFACTURED, LOCKED-IN ASBESTOS DOES NOT PRESENT

A HAZARD. ONLY WHEN THE ITEM IS SUBJECTED TO

**ABRASIVE ACTIONS &** 

DUST IS GENERATED, THEN ASBESTOS FIBERS MAY BE RELEASED & BECOME AIRBORNE, THERBY CREATING A HAZARD.

Respiratory Protection: IF EXPOSURES EXCEED ESTABLISHED LIMITS, A NIOSH/MSHA APPROVED RESPIRATOR FOR ASBESTOS SHOULD BE USED. CONSULT YOUR SAFETY OFFICE/IH PERSONNEL FOR GUIDANCE FOR THE TASK AT HAND.

Ventilation:LOCAL EXHAUST IS RECOMMENDED IN SITUATIONS WHERE DUST IS GENERAT BY

ABRASIVE ACTIONS, ABRASION OR OTHER MEANS.

Protective Gloves: AS REQUIRED FOR TASK AT HAND.

Eye Protection: SAFETY GLASSES W/SIDE SHIELDS OR GOGGLES

Other Protective Equipment: AS REQUIRED FOR TASK AT HAND, AND THE GUIDANCE SET FORTH BY YOUR SAFETY OFFICE OR IH PERSONNEL

Work Hygienic Practices: DONOT INHALE DUST CREATED BY ABRADING ACTIONS. USE FULL PROTECTION AGAINST AIRBORNE FIBERS. AVOID AIRBORNE DUST CREATION

Supplemental Safety and Health

GENERIC "MSDS" CREATED FOR "NSN" IDENTI

FIED AS CONTAINING ASBESTOS.

WHEN A MANUFACTURER'S SPECIFIC "MSDS" IS PROVIDED FOR MATERIAL PROCURED UNDER THIS NSN, THIS GENERIC "MSDS" WILL BE REMOVED.

HCC:T7

Evaporation Rate & amp; Reference:NONE Solubility in Water:NOT SOLUBLE Appearance and Odor:MANUFACTURED COMMODITY DESCRIBED BY LOGISTICS:"ITEM-NAME" Percent Volatiles by Volume:NONE

Waste Disposal Methods:DUST SHOULD BE HANDLED AS A HAZARDOUS AIR POLLUTANT I/A/W 40CFR61 SUBPART "M" PERTAINING TO ASBESTOS. USE LANDFILLS APPROVED FOR ASBESTOS DISPOSAL. NOTE IF ITEM UNDER CONSIDERATION FOR DISPOSAL IS "FRIABLE OR NON-FRIABLE".

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.