

GERARD PACKING AND BELTING CORP -- PACKING MATERIAL: PART NO. UNKNOWN --
5330-00-559-6120

===== Product Identification =====

MSDS Date:03/11/1989

FSC:5330

NIIN:00-559-6120

MSDS Number: BJXMP

=== Responsible Party ===

Company Name:GERARD PACKING AND BELTING CORP

Address:24 MIDLAND AVE

City:HICKSVILLE

State:NY

ZIP:11801

Country:US

Info Phone Num:516-935-2400

Emergency Phone Num:516-953-2400

Preparer

's Name:DOD HMIS/DGSC-SSH

CAGE:2G277

=== Contractor Identification ===

Company Name:GERARD PACKING AND BELTING CORP

Address:24 MIDLAND AVENUE

Box:City:HICKSVILLE

State:NY

ZIP:11801

Country:US

Phone:516-935-2400

CAGE:2G277

===== Composition/Information on Ingredients =====

Ingred Name:ASBESTOS, CHRYSOTILE

CAS:12001-29-5

RTECS #:CI6478500

OSHA PEL:0.2 FIBERS/CC

ACGIH TLV:2 FIBERS/CC; A1;9192

Ingred Name:OTHER INGREDIENTS NOT SPECIFIED.

RTECS #:9999999ZZ

=====

Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO

Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:YES

Health Hazards Acute and Chronic:ACUTE: NO ACUTE EFFECTS ARE

KNOWN;CHRONIC: DUST FROM ABRASIVE ACTIONS(EG. CUTTING, MACHINING, FILING, ETC.) MAY CONTAIN ASBESTOS FIBERS. CHRONIC OVEREXPOSURE TO AIRBORNE FIBERS MAY LEAD TO ASBESTOSIS & MESOTHELIOMA. SMOKING COMBINED W/FIBER INHALATION GREATLY INCREASES LUNG CANCER RISK!

Explanation of Carcinogenicity:OVEREXPOSURE TO AIRBORNE CONCENTRATIONS OF ASBESTOS MAY LEAD TO ASBESTOSIS AND MESOTHELIOMA.

Effects of Overexposure:INHAL: INHALATION OF AIRBORNE DUST CONTAINING ASBESTOS FIBERS ON REPEATED EXPOSURE MAY CAUSE OR CAN LEAD TO ASBESTOSIS / MESOTHELIOMA; SKIN: PROLONGED EXPOSURE MAY LEAD TO IRRITATION, WARTS; EYE: POTENTIAL IRRITATION FROM AIRBOR DUST; INGEST: N/K.

Medical Cond Aggravated by Exposure:PRE-EXISTING RESPIRATORY CONDITION

S.

===== First Aid Measures =====

First Aid:INHAL: REMOVE TO FRESH AIR. OBTAIN MEDICAL ADVICE; SKIN: WASH EXPOSED AREA WITH SOAP & WATER; EYE: FLOOD W/ WATER. IF IRRITATION OCCURS, GET MEDICAL ATTN; INGEST: CONSULT A PHYSICIAN; OTHER CHANGE CLOTHING AS REQUIRED TO AVOID CARRYING DUST PARTICLES INTO OTHER AREAS

===== Fire Fighting Measures =====

Flash Point:NONE

Extinguishing Media:MATERIAL IS NOT FLAMMABLE ; USE MEDIA APPROPRIATE FOR SURROUNDING FIRE.

Fire Fighting Procedures:COMBUSTION PRODUCTS OF THIS MATERIAL MAY BE TOXIC. USE A SELF-CONTAINED BREATHING APPARATUS WHEN FIGHTING FIRES INVOLVING CHEMICAL PRODUCTS.

Unusual Fire/Explosion Hazard:FIRE MAY RELEASE ASBESTOS FIBERS INTO THE AIR.

===== Accidental Release Measures =====

Spill Release Procedures:USE PROPER PERSONAL PROTECTION.VACUUM OR WET CLEAN IF DUST IS INVOLVED. ANY VACUUM

M SYSTEM SHOULD BE EQUIPPED AN
OUTLET "HEPA" FILTER TO PREVENT REINTRODUCING ASBESTOS FIBERS TO
THE ATMOSPHERE.

=====
Handling and Storage
=====

Handling and Storage Precautions:HANDLE IN A MANNER TO MINIMIZE
FORMATION OR RETENTION OF AIRBORNE DUST. USE PROPER PERSONAL
PROTECTION FOR TASK AT HAND. CHECK W/YOUR SAFETY OFFICE!!!
Other Precautions:AS MANUFACTURED, LOCKED-IN ASBESTOS DOES NOT PRESENT
A HAZARD. ONLY WHEN THE ITEM IS SUBJECTED TO
ABRASIVE ACTIONS &
DUST IS GENERATED, THEN ASBESTOS FIBERS MAY BE RELEASED & BECOME
AIRBORNE, THEREBY CREATING A HAZARD.

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection:IF EXPOSURES EXCEED ESTABLISHED LIMITS, A
NIOSH/MSHA APPROVED RESPIRATOR FOR ASBESTOS SHOULD BE USED.
CONSULT YOUR SAFETY OFFICE/IH PERSONNEL FOR GUIDANCE FOR THE TASK
AT HAND.
Ventilation:LOCAL EXHAUST IS RECOMMENDED IN SITUATIONS WHERE DUST IS
GENERATED BY
ABRASIVE ACTIONS, ABRASION OR OTHER MEANS.
Protective Gloves:AS REQUIRED FOR TASK AT HAND.
Eye Protection:SAFETY GLASSES W/SIDE SHIELDS OR GOGGLES
Other Protective Equipment:AS REQUIRED FOR TASK AT HAND, AND THE
GUIDANCE SET FORTH BY YOUR SAFETY OFFICE OR IH PERSONNEL
Work Hygienic Practices:DONOT INHALE DUST CREATED BY ABRADING ACTIONS.
USE FULL PROTECTION AGAINST AIRBORNE FIBERS. AVOID AIRBORNE DUST
CREATION
Supplemental Safety and Health
GENERIC "MSDS" CREATED FOR "NSN" IDENTIFIED AS CONTAINING ASBESTOS.
WHEN A MANUFACTURER'S SPECIFIC "MSDS" IS PROVIDED FOR MATERIAL
PROCURED UNDER THIS NSN, THIS GENERIC "MSDS" WILL BE REMOVED.

=====
Physical/Chemical Properties
=====

HCC:T7
Evaporation Rate & Reference:NONE
Solubility in Water:NOT SOLUBLE
Appearance and Odor:MANUFACTURED COMMODITY DESCRIBED BY
LOGISTICS:"ITEM-NAME"
Percent Volatiles by Volume:NONE

=====
Stability and Reactivity Data
=====

Stability Indicator/Materials to Avoid: YES

NONE KNOWN

Stability Condition to Avoid: AVOID PHYSICAL DAMAGE

===== Disposal Considerations =====

Waste Disposal Methods: DUST SHOULD BE HANDLED AS A HAZARDOUS AIR POLLUTANT I/A/W 40CFR61 SUBPART "M" PERTAINING TO ASBESTOS. USE LANDFILLS APPROVED FOR ASBESTOS DISPOSAL. NOTE IF ITEM UNDER CONSIDERATION FOR DISPOSAL IS "FRIABLE OR NON-FRIABLE".

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.