

View NSN Online: <https://aerobasegroup.com/nsn/9150-01-080-9652>

N/P -- G 351 SILICONE GREASE COMPOUND -- 9150-01-080-9652

Product ID:G 351 SILICONE GREASE COMPOUND

MSDS Date:01/01/1987

FSC:9150

NIIN:01-080-9652

MSDS Number: BJXQZ

=== Responsible Party ===

CAGE:9A544

=== Contractor Identification ===

Company Name:GENERAL ELECTRIC SUPPLY CO.

Address:1505 SHERWOOD AVENUE

Box:27607

City:RICHMOND

State:VA

ZIP:23261

Country:US

Phone:804-358-4941

CAGE:9A544

=====
Composition/Information on
Ingredients =====

Ingred Name:LITHIUM SOAP THICKENER (LITHIUM STEARATE)

CAS:4485-12-5

RTECS #:W14370000

Fraction by Wt: 10-30%

Other REC Limits:NONE SPECIFIED

OSHA PEL:15 MG/M3 TDUST

ACGIH TLV:10 MG/M3 (STEARATES)

Ingred Name:SILICONE GREASE

Fraction by Wt: 70-90%

Other REC Limits:NONE SPECIFIED

=====
Hazards Identification =====

LD50 LC50 Mixture:ORAL LD50 (RAT) IS UNKNOWN.

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO

Reports of Carcino

genicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:EYE: MILD IRRITATION. INGESTION: IRRITATION. DO NOT INDUCE VOMITING. GIVE LARGE QUANTITIES OF WATER AND GET MEDICAL ATTENTION. NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON. IF CONTACT WITH SKIN, WASH WITH SOAP AND WATER.

Explanation of Carcinogenicity:NONE OF THE COMPOUNDS IN THIS PRODUCT IS LISTED BY IARC, NTP, OR OSHA AS A CARCINOGEN.

Effects of Overexposure:IRRITATION OF EYES AND SKIN.

Medical C

ond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

=====
===== First Aid Measures =====

First Aid:INHALATION: MOVE PERSON TO FRESH AIR. RESTORE BREATHING. TREAT SYMPTOMATICALLY. GET MEDICAL HELP. EYES: FLUSH IMMEDIATELY WITH LARGE AMOUNTS OF WATER FOR AT LEAST 15 MINUTES. GET MEDICAL TREATMENT. SK IN: REMOVE COMPLETELY WITH A DRY CLOTH PRIOR TO WASHING AFFECTED SKIN AREAS WITH SOAP AND WATER. REMOVE CONTAMINATED CLOTHING. INGESTION: R INSE MOUTH WITH WATER SEVERAL TIMES AND GET MEDICAL ATTENTION

=====
===== Fire Fighting Measures =====

Flash Point:>500F,>260C; COC

=====
===== Accidental Release Measures =====

Spill Release Procedures:WIPE, SCRAPE OR SOAK UP IN AN INERT MATERIAL AND PUT IN A CONTAINER FOR DISPOSAL. WASH WALKING SURFACES WITH DETERGENT AND WATER TO REDUCE SLIPPAGE.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

=====
===== Handling and Storage =====

Handling and Storage Precautions:NONE SPECIFIED BY MANUFACTURER. Other Precautions:AVOID CONTACT WITH EYES. CONTROL DUST LEVELS.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE NIOSH/MSHA APPROVED RESPIRATORS FOR ORGANIC VAPORS. USE NIOSH/MSHA APPROVED AIRLINE TYPE RESPIRATORS OR HOODS IN CONFINED AREAS.

Ventilation:SUFFICIENT VENTILATION TO CONTROL DUST LEVELS.

Protective Gloves:CLOTH GLOVES
Eye Pro

tection:CHEMICAL SAFETY GLASSES.

Other Protective Equipment:USE DISPOSABLE OR IMPERVIOUS CLOTHING IF
WORK CLOTHING CONTAMINATION IS LIKELY. USE PROTECTIVE SKIN CREAM IF
REQUIRED.

Work Hygienic Practices:WASH HANDS BEFORE EATING OR SMOKING OR USING
THE WASH ROOM. LAUNDER CONTAMINATED CLOTHING BEFORE REUSE.

Supplemental Safety and Health
NONE SPECIFIED BY MANUFACTURER.

===== Stability and Reactivity Data =====

Hazardous Decomposition Products:CARBON DIOXIDE
& CARBON MONOXIDE, AND
SILICON DIOXIDE.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSAL SHOULD BE DONE IN ACCORDANCE WITH
FEDERAL, STATE AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and

disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.