

J. F. JELENKO AND CO. -- 270070, MODEL SPRAY -- 6520-00-542-5185

=====
Product Identification
=====

Product ID:270070, MODEL SPRAY

MSDS Date:01/01/1987

FSC:6520

NIIN:00-542-5185

MSDS Number: BJYHS

=== Responsible Party ===

Company Name:J. F. JELENKO AND CO.

Address:99 BUSINESS PARK DRIVE

City:ARMONK

State:NY

ZIP:10504

Country:US

Info Phone Num:914-273-8600

Emergency Phone Num:914-273-8600

CAGE:319

76

=== Contractor Identification ===

Company Name:J. F. JELENKO AND CO.

Address:99 BUSINESS PARK DRIVE

Box:City:ARMONK

State:NY

ZIP:10504

Phone:914-273-8600

CAGE:31976

=====
Composition/Information on Ingredients
=====

Ingred Name:TOLUENE (SARA III)

CAS:108-88-3

RTECS #:XS5250000

Fraction by Wt: 20%

OSHA PEL:200 PPM/150 STEL

ACGIH TLV:50 PPM; 9293

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:ACRYLIC RESINS

CAS:9003-01-4

RTECS #:AT4680000

Fraction by Wt: 12%

Other R

EC Limits:NONE SPECIFIED

Ingred Name:PROPANE

CAS:74-98-6

RTECS #:TX2275000

Fraction by Wt: 15%

OSHA PEL:1000 PPM

ACGIH TLV:ASPHYXIAN; 9192

=====
Hazards Identification
=====

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:MAY CAUSE SKIN, EYE, NOSE, UPPER TRACT
IRRITATION.

Effects of Overexposure:SEE "HEALTH HAZARDS"
Medical Cond Aggravated by Exposure:NONE STATED

=====
First Aid Measures
=====

First Aid:INHALE: REMOVE TO FRESH AIR, USE OXYGEN IF NEEDED; SKIN/EYE:
FLUSH WITH PLENTY OF WATER.

=====
Fire Fighting Measures
=====

Flash Point:AEROSOL CAN
Extinguishing Media:CARBON DIOXIDE, DRY CHEMICAL, ALCOHOL FOAM.
Fire Fighting Procedures:WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AND A
FULL FACED SELF CONTAINED BREATHING APPARATUS.
Unusual Fire/Explosion Hazard:NONE SPECIFIED BY MANUFACTURER.

=====
Accidental Release Measures
=====

Spill Release Procedures:STOP SOURCES OF IGNITION. VENTILATE THE AREA.
Neutralizing Agent:NONE STATED.

=====
Handling and Storage
=====

Handling and Storage Precautions:DO NOT STORE NEAR HIGH TEMPERATURE,
SPARKS, ETC.

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection:USE NIOSH/MSHA APPROVED RESPIRATOR IF TLV IS
EXCEEDED.

Ventilation:USE LOCAL EXHAUST.
Protective Gloves:RECOMMENDED.
Eye Protection:SAFETY GLASSES OR GOGGLES.
Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:V3
Boiling Pt:=29.4C, 85.F
Vapor Pres:65 PSIG
Vapor Density:3.2
Solubility in Water:NEGLIGIBLE
Appearance and Odor:CLEAR VISCOUS LIQUID, AROMATIC ODOR.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
NONE SPECIFIED BY MANUFAC
TURER.
Stability Condition to Avoid:HIGH HEAT, OPEN FLAMES AND OTHER SOURCES
OF IGNITION
Hazardous Decomposition Products:CARBON DIOXIDE, CARBON MONOXIDE.

===== Disposal Considerations =====

Waste Disposal Methods:TO COMPLY WITH LOCAL, STATE AND FEDERAL
REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no
manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.