View NSN Online: https://aerobasegroup.gr/nsn/6685-00-247-2972

CONNECTICUT VALLEY INDUSTRIES INC -- MERCURY IN GLASS THERMOMETER

6660-00-247-2972

Product ID:MERCURY IN GLASS THERMOMETER

MSDS Date:06/10/1989

FSC:6660

NIIN:00-247-2972

MSDS Number: BJYTR

=== Responsible Party ===

Company Name: CONNECTICUT VALLEY INDUSTRIES INC

Address:16 PLAINS RD

City:ESSEX State:CT

ZIP:06426-1501

Country:US

Info Phone Num:203-767-9051

Emerg

ency Phone Num:203-767-9051

CAGE:55560

=== Contractor Identification ===

Company Name: CONNECTICUT VALLEY INDUSTRIES INC

Address:8 CENTER ROAD Box:City:OLD STAYBROOK

State:CT ZIP:06475 Country:US

Phone:860-388-0822/FAX: 860-388-1651

CAGE:55560

======= Composition/Information on Ingredients ========

Ingred Name: MERCURY (SARA III)

CAS:7439-97-6

RTECS #:OV4550000 Fraction by Wt: 100%

OSHA PEL:S, C, 0.1 MG/M3 ACGIH TLV:S, 0.05 MG/M3; 9192

EPA Rpt Qty:1 LB DOT Rpt Qty:1 LB

=========

====== Hazards Identification =============
Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:ACUTE: INGEST-BURNING IN MOUTH & THROAT;THIRST; SHOCK; CARDIAC ARRHYTHMIAS; NAUSEA, VOMITING, ABDOMINAL PAIN, BLODDY DIARRHEA; HEMATURIA,ALBUMINURIA; INHAL: METAL FUME FEVER; GASTROINTESTINAL SYMPTOMS; BRONCHITIS; CHRONIC: CNS- VASOMOTOR DISTURBANCES; INSOMMIA; TREMORS;INHAL-COUGH , FEVER; HEMATOPOIETIC-MILD ANEMIA. Effects of Overexposure:INHAL: METAL FUME FEVER; SALIVATION & METALLIC TASTE; CHEST TIGHTNESS; COUGH; SKIN: PRIMARY IRRITANT &
OCCASIONALLY SENSITIZER; INGEST: THIRST, SHOCK, NAUSEA, VOMITING
Medical Cond Aggravated by Exposure:PRECLUDE FROM EXPOSURE INDIVIDUALS
======================================
First Aid:CONTACT QUALIFIED PHYSICIAN.
======================================
Fire Fig hting Procedures:USE SELF CONTAINED OR AIR LINE RESPIRATORS ONLY.
Unusual Fire/Explosion Hazard:MERCURY IS NOT COMBUSTIBLE, BUT WILL EVAPORATE WHEN HEATED, CREATING TOXIC FUMES. WILL COMBINE WITH OTHER COMPOUNDS TO CREATE UNSTABLE COMPOUNDS.
======== Accidental Release Measures ==========
Spill Release Procedures:WEAR RUBBER GLOVES,SCBA,PROTECTIVE CLOTHING; METAL: COLLECT ALL DROPLETS & POOLS AT ONCE BY MEANS OF SUCTION PUMP ASPIRATOR BOTTLE W/LONG CAPIL LARY TUBE. COVER FINE DROPLETS IN
NON ACCESSIBLE CRACKS W /CALCIUM POLYSULFIDE & EXCESS SULFUR.
============ Handling and Storage ===============
Handling and Storage Precautions:MERCURY IS THE THERMOMETER INDICATING FLUID. HANDLE & STORE SO AS TO MINIMIZE BREAKAGE OF THERMOMETER & MERCURY SPILLAGE.
====== Exposure Controls/Personal Protection ========
Respiratory Protection:NOT NEEDED UNLESS MERCURY IS SPILLED. AT 0.5 MG/CUM:ANY CHEM. CARTRIDG

E RESPIRATOR W/CARTRIDGE(S) PROVIDING PROTECTION AGAINST COMPOUND/ANY SUPPLIED-AIR RESPIR/SCBA; AT 1.25 MG/CUM: SUPPL-AIR RESPIR. IN CONTINUOUS FLOW MODE/"PAPRS" Ventilation: NORMAL ROOM VENTILATION: IF MERCURY PRESENT: ADEQUATE VENTILATION W/REGULAR MONITORING OF WORK AREA. Protective Gloves: IMPERVIOUS TYPE FOR HANDLING MERCURY. Eye Protection: AS REQUIRED FOR SITUATION AT HAND. Other Protective Equipment: NORMAL WORKING CLOTHING COVERING ARMS & LEGS. Work Hygienic Practices: HANDLE THERMOMETERS SO AS TO AVOID BREAKAGE & THUS SPILLAGE OF MERCURY. Supplemental Safety and Health ========= Physical/Chemical Properties =========== HCC:T6 Boiling Pt:B.P. Text:676F,358C Melt/Freeze Pt:M.P/F.P Text:-38F/-38.9C Vapor Pres:0.0019 Spec Gravity:13.6 Evaporation Rate & Evaporation R Solubility in Water:NONE Appearance and Odor:SILVER METALLIC LIQUID. Percent Volatiles by Volume:100 ========= Stability and Reactivity Data ========== Stability Indicator/Materials to Avoid:YES AMMONIA, GOLD AND SILVER. Stability Condition to Avoid:NONE Hazardous Decomposition Products: NONE STATED. ======= Disposal Considerations ============ STOPPER BOTTLE. HOLD IT FOR PURIFICATION OR SALE. DO NOT ALLOW MERCURY TO CONTAMINATE AIR OR WATER.

Waste Disposal Methods: COMBINE ALL CONTAMINATED MERCURY IN AN TIGHTLY

Disclaimer (provided with this information by the compiling agencies): This information is formu

lated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.