

SANITEK PRODUCTS, INC. -- SANITEK 613-1 (PRODUCT CODE 04020) -- 9150-01-037-1306

=====
Product Identification
=====

Product ID:SANITEK 613-1 (PRODUCT CODE 04020)

MSDS Date:01/15/1987

FSC:9150

NIIN:01-037-1306

MSDS Number: BJZXR

=== Responsible Party ===

Company Name:SANITEK PRODUCTS, INC.

Address:3959 GOODWIN AVENUE

City:LOS ANGELES

State:CA

ZIP:90039

Country:US

Info Phone Num:213-245-6781

Emergen

cy Phone Num:213-245-6781

CAGE:54666

=== Contractor Identification ===

Company Name:SANITEK PRODUCTS, INC.

Address:3959 GOODWIN AVENUE

Box:City:LOS ANGELES

State:CA

ZIP:90039

Country:US

Phone:213-245-6781

CAGE:54666

=====
Composition/Information on Ingredients
=====

Ingred Name:MANUFACTURER LISTED "NONE" UNDER THE HAZARDOUS INGREDIENTS
HEADING OF THE MSDS.

Fraction by Wt: 100%

Other REC Limits:NONE SPECIFIED

=====
Hazards Identification
=====

=====

Routes of Entry: Inhalation:NO Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:PRODUCT IS MILDLY IRRITATING TO BODY
TISSUES. PER MFR'S MSDS TOXICITY APPEARS TO BE VERY LOW.

Explanation of Carcinogenicity:NONE OF THE CHEMICALS IN THIS PRODUCT
ARE LISTED AS CARCINOGENIC BY NTP, IARC OR OSHA.

Effects of Overexposure:CONTACT MAY CAUSE EYE & SKIN IRRITATION. MAY
CAUSE MILD G/I IRRITATION. INHALATION IS HIGHLY UNLIKELY.

M

Medical Cond Aggravated by Exposure:NONE

=====
First Aid Measures
=====

First Aid:EYE:FLUSH W/WATER 15 MIN, HOLD LIDS OPEN. SKIN:WASH WITH SOAP & WATER. REMOVE CONTAMINATED CLOTHING AND LAUNDRER BEFORE REUSE. INHALED:REMOVE TO FRESH AIR. RESTORE BREATHING IF NECESSARY. INGESTED:DO NOT INDUCE VOMITING. GIVE 2 LARGE GLASSES OF MILK OR WATER AND GET IMMEDIATE MEDICAL CARE.(DOCTOR MAY ORDER VOMITING.)NOTHING BY MOUTH IF UNCONSCIOUS. IF IRRITATION PERSISTS OR IS SEVERE,SEE A DOCTOR.

=====
Fire Fighting Measures
=====

Flash Point:NON-FLAMMABLE
Autoignition Temp:Autoignition Temp Text:NONE
Extinguishing Media:USE WATER FOG, CARBON DIOXIDE, FOAM, OR DRY CHEMICAL.
Fire Fighting Procedures:WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AND A FULL FACED SELF CONTAINED BREATHING APPARATUS. EVACUATE AREA. COOL FIRE EXPOSED CONTAINERS WITH WATER SPRAY.
Unusual Fire/Explosion Hazard:COMBUSTION OR HEAT OF FIRE MAY PRODUCE HAZARDOUS DECOMPOSITION PRODUCTS AND VAPORS.

=====
Accidental Release Measures
=====

Spill Release Procedures:ABSORB WITH INERT MATERIAL. SWEEP UP & PLACE IN WASTE CONTAINER. WASH RESIDUE WITH SOAP & WATER.
Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

=====
Handling and Storage
=====

Handling and Storage Precautions:STORE IN A COOL DRY AREA. PROTECT FROM FREEZING.
Other Precautions:DO NOT REUSE PRODUCT CONTAINERS. TRIPPLE RINSE, REPLACE BUNG SECURELY THEN SENT TO MFR OR RECONDITIONER.

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection:RESPIRATOR WILL NOT NORMALLY BE NECESSARY. USE NIOSH/MSHA APPROVED AIR SUPPLIED RESPIRATOR OR RESPIRATOR FOR DUST/MIST IF EXPOSURE IS ABOVE THE TLV/PEL. SEE 29 CFR 1910.134 FOR REGULATIONS PERTAINING TO RESPIRATOR USE.
Ventilation:NORMAL ROOM VENTILATION IS SUFFICIENT.
Protective Gloves:N

OT NORMALLY NEEDED.

Eye Protection:SAFETY GLASSES .

Other Protective Equipment:NONE RECOMMENDED BY MANUFACTURER (SUPPLIER).

Work Hygienic Practices:USE GOOD INDUSTRIAL HYGIENE PRACTICE. MINIMIZE CONTACT. WASH THOROUGHLY BEFORE EATING, DRINKING,ETC.

Supplemental Safety and Health

NONE

===== Physical/Chemical Properties =====

HCC:V6

Boiling Pt:B.P. Text:212F,100C

Vapor Pres:17.5 MM

Vapor Density: