View NSN Online: https://aerobasegroup.gr/nsn/8010-00-664-6302

CON-LUX COATINGS, INC. -- PRIMER SURFACER WHITE -- 8010-00-664-6302

Product ID: PRIMER SURFACER WHITE MSDS Date:04/22/1988 FSC:8010 NIIN:00-664-6302 **MSDS Number: BKHQK** === Responsible Party === Company Name: CON-LUX COATINGS, INC. Address:226 TALMADGE RD. Box:847 City:EDISON State:NJ ZIP:08818-0847 Info Phone Num:(201) 287-4000 Emergency Phone Num: (201) 287-4000 CA GE:60189 === Contractor Identification === Company Name: CON-LUX COATINGS INC Address:226 TALMADGE RD Box:847 City:EDISON State:NJ ZIP:08818-0847 Country:US Phone:732-287-4000 CAGE:60189 Ingred Name: MINERAL SPIRITS CAS:64742-86-7 Fraction by Wt: >1% **OSHA PEL:500 PPM** ACGIH TLV:100 PPM Ingred Name: MAGNESIUM SILICATE HYDRATE CAS:1343-90-4 RTECS #:OM4360000 Fraction by Wt: >1% **OSHA PEL:20 MPPCF** ACGIH TLV:2 MG/CUM Ingred Name:TIT

ANIUM DIOXIDE CAS:13463-67-7 RTECS #:XR2275000 Fraction by Wt: >1% OSHA PEL:15 MG/M3 TDUST ACGIH TLV:10 MG/M3 TDUST; 9293

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:SKIN/EYE/INGESTION: IRRITATION. INHALATION: IRRITATION TO THE RESPIRATORY TRACT, HEADACHE, NAUSEA, DIZZINESS. Explanation of Carcinogenicity:NONE Effects of Overexposure:SKIN/EYE/INGESTION: IRRITATION. INHALATION:

IRRITATION TO THE RESPIRATORY TRACT, HEADACHE, NAUSEA, & DIZZINESS.

First Aid:EYES: FLUSH W/PLENTY OF WATER FOR AT LEAST 15 MINS. SKIN: WASH W/SOAP & WATER. INHALATION: REMOVE TO FRESH AIR. GIVE CPR OR OXYGEN IF NEEDED. TREAT SYMPTOMATICALLY. INGESTION: DRINK 1 OR 2 GLASSES OF WATER TO DILUTE. DON'T INDUCE VOMITING.IF SPONTANEOUS VOMITING OCCURS KEE

P HEAD AT OR BELOW KNEE LEVEL TO PREVENT ASPIRATION INTO THE LUNGS. OBTAIN MEDICAL ATTENTION IN ALL CASES.

Flash Point Method:TCC Flash Point:105F Lower Limits:1% Extinguishing Media:FOAM, CO2, DRY CHEMICAL, & WATER MIST. Fire Fighting Procedures:SMOTHER FLAMES W/ONE OF EXTINGUISHING MEDIA. WATER MAY BE USED TO COOL DOWN UNOPENED CONTAINERS IN VICINITY. Unusual Fire/Explosion Hazard:FLAMMABLE LIQUID.

==	Accidental	Release	Measures	
----	------------	---------	----------	--

Spill Release Procedures: ELIMINATE ALL IGNITION SOURCES. WEAR APPROPRIATE PERSONAL PROTECTION EQUIPMENT & APPROVED RESPIRATOR. CONTAIN SPILL W/ABSORBENT MATERIAL & PUT INTO VAPOR TIGHT CONTAINERS.

Handling and Storage Precautions:STORE IN APPROPRIATE AREAS. GROUND CONTAINERS WHEN POURING LIQUIDS & POWDERS TO AVOID STATIC CHARGE BUILD UP.

Other Precautions

:PROVIDE ADEQUATE VENTILATION OR RESPIRATORY

PROTECTION TO REMOVE DECOMPOSITION PRODUCTS DURING WELDING OR FLAME CUTTING COATED SURFACES.

Respiratory Protection: IN OUTDOOR OR OPEN AREA, USE APPROVED RESPIRATOR TO REMOVE SOLID AIRBORNE PARTICLES OF OVER SPRAY DURING SPRAY APPLICATION. IN RESTRICTED VENTILATION AREAS USE APPROVED RESPIRATOR DESIGN TO REMOVE A C OMBINATION OF PARTICLES & VAPOR. Ventilation: PRO

VIDE SUFFICIENT VENTILATION, IN VOLUME & PATTERN TO KEEP AIR

Evaporation Rate & amp; Reference: SLOWER THAN ETHER Percent Volatiles by Volume: 60.45%

Stability Indicator/Materials to Avoid:YES OXIDIZING AGENTS Stability Condition to Avoid:EXTREME HEAT, SPARKS, OPEN FLAMES, & SOURCES OF IGNITION. Hazardous Decomposition Products:HAZARDOUS FUMES

Waste Dis

posal Methods:DISPOSE OF IN ACCORDANCE W/LOCAL, STATE, & FEDERAL REGULATIONS. PREVENT MATERIAL FROM CONTACTING ANY WATER SOURCES OR SEWERS LEADING TO SURFACE WATERS. FLAMMABLE LIQUID.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for

its use. Any person utilizing this

document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.