

ASPEN PAINTS -- STAIN, MAPLE -- 8010-00-598-7669

===== Product Identification =====

Product ID:STAIN, MAPLE

MSDS Date:09/01/1991

FSC:8010

NIIN:00-598-7669

MSDS Number: BKZZR

=== Responsible Party ===

Company Name:ASPEN PAINTS

Address:1128 S.W. SPOKANE STREET

City:SEATTLE

State:WA

ZIP:98134

Country:US

Info Phone Num:206-682-4603 (M-F, 8:30-5:00)

Emergency Phone Num:800-424-9300 (CHEMTREC)

Preparer'

s Name:D. KIER

CAGE:0AL09

=== Contractor Identification ===

Company Name:ASPEN PAINTS

Address:1128 SW SPOKANE STREET

City:SEATTLE

State:WA

ZIP:98134

Country:US

Phone:800-424-9300 CHEMTREC

CAGE:0AL09

Company Name:ASPEN PAINTS/ASAMIPEN AMERICA INC

Address:1128 SPOKANE STREET

Box:City:SEATTLE

State:WA

ZIP:98134-1187

Country:US

Phone:303-573-1014(MED ONLY)

CAGE:0AL09

===== Composition/Information on Ingredients =====

Ingred Name:STODDARD SOLVENT

CAS:8052-41-3

RTECS #:WJ8925000

Fr

action by Wt: 100%
Other REC Limits:NONE SPECIFIED
OSHA PEL:500 PPM
ACGIH TLV:100 PPM; 9293

Ingrid Name:VOC = 594 G/L
RTECS #:9999999VO
Other REC Limits:NONE RECOMMENDED
OSHA PEL:NOT RELEVANT
ACGIH TLV:NOT RELEVANT

=====
Hazards Identification
=====

LD50 LC50 Mixture:SEE INGREDIENTS
Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:INHALATION: NASAL & RESPIRATORY

IRRITATION, DIZZINESS, WEAKNESS, FATIGUE, NAUSEA, HEADACHE,
POSSIBLE UNCONSCIOUSNESS, ASPHYXIATION. MAY BE HARMFUL OR FATAL.
SKIN: PROLONGED & REPEATED CONTACT W/SKIN CAN CAUSE DEFATTING &
DRYING OF SKIN RESULTING IN IRRITATION & DERMATITIS. EYE: SEVERE
IRRITATION, REDNESS, TEARING *

Effects of Overexposure:* & BLURRED VISION. INGESTION: CAN CAUSE
GASTROINTESTINAL IRRITATION, NAUSEA, VOMITING & DIARRHEA.
ASPIRATION OF MATERIAL INTO LUNGS CAN CAUSE CHEMICAL PNEUMONITIS

WHICH CAN BE FATAL. REPORTS HAVE ASSOCIATED REPEATED & PROLONGED
OCCUPATIONAL OVEREXPOSURE TO SOLVENT W/PERMANENT BRAIN & NERVOUS
SYSTEM DAMAGE.

=====
First Aid Measures
=====

First Aid:INHALATION: REMOVE VICTIM FROM FURTHER EXPOSURE & RESTORE
BREATHING IF REQUIRED. EYE: FLUSH W/WATER FOR AT LEAST 15 MINUTES
WHILE HOLDING EYELIDS OPEN. SKIN: WASH CONTAMINATED SKIN W/MILD
SOAP & WATER . INGESTION: DO NOT INDUCE VOMITING. OBTAIN MEDICAL
ATTENTION IMMEDIATELY.

=====
Fire Fighting Measures
=====

Flash Point Method:TCC
Flash Point:112F,44C
Lower Limits:0.8
Upper Limits:5.0
Extinguishing Media:DRY CHEMICAL, CO2, FOAM AND WATER FOG.
Fire Fighting Procedures:DO NOT ENTER CONFINED FIRE SPACE W/O ADEQUATE
PROTECT CLOTH & APPROVED POSITIVE PRESS SCBA. EXCLUDE AIR. USE
WATER ONLY AS FOG. COOL FIRE EXPOSED CONTNR W/WATER.
Unusual Fire/Explosion Hazard:AVOID EXCESSIVE HEAT, OPEN FLAMES & ALL

IGNITION SOURCES.

===== Accidental Release Measures =====

Spill Release Procedures: REMOVE IGNITION SOURCES. VENT AREA. ABSORB SPILL W/ ABSORB MAT'L & PLACE IN CLOSED CNTNR. LARGE SPILL-DIKE AREA TO PREVENT MAT'L FROM ENTERING WATER SYSTEMS. WEAR PROTECT EQUIPMENT DURING CLEANUP. NOTIFY PROPER AUTHORITIES IF SPILL EXCEEDS 220 LBS.

===== Handling and Storage =====

Handling and Storage Precautions: COMBUSTIBLE LIQUID. STORE IN A COOL, DRY, WELL-VENTILATED AREA, AWAY FROM HEAT & IGNITION SOURCES. AVOID PROLONGED OR REPEATED CONTACT W/ SKIN.

Other Precautions: AVOID BREATHING SPRAY/MIST. LAUNDRY CONTAM CLOTHING PRIOR TO REUSE. GROUND CONTAINERS WHEN POURING. LIMIT FREE FALL TO MINIMIZE STATIC CHARGE BUILD-UP. EMPTY CONTAINERS MAY BE HZDS FROM PRODUCT RESIDUE & VAPORS & ALL CAUTIONS APPLY TO THEM.

===== Exposure Controls/Personal Protection =====

Respiratory Protection

A CANISTER-TYPE RESPIRATOR MUST BE WORN TO PREVENT THE INHALATION OF VAPORS OR SPRAY MISTS WHEN THE TLV/PEL IS EXCEEDED.

Ventilation: GENERAL VENT IS REQUIRED DURING NORMAL USE. LOCAL VENT MAY BE REQUIRED IN CERTAIN CASES TO KEEP EXPOS LEVEL BELOW LIMIT.

Protective Gloves: CHEM-RESIST NITRILE, NEOPRENE OR RUBBER.

Eye Protection: WEAR FACE SHIELD OR CHEMICAL GOGGLES.

Other Protective Equipment: WEAR PROTECTIVE CLOTHING TO PREVENT SKIN CONTACT. EYE WASH STATION/SAFETY SHOWER SHOULD BE AVAILABLE.

Work Hygienic Practices: USE GOOD PERSONAL HYGIENE.

Supplemental Safety and Health

DO NOT TAKE INTERNALLY. CLOSE CONTAINER AFTER EACH USE. KEEP AWAY FROM CHILDREN.

===== Physical/Chemical Properties =====

Boiling Pt: B.P. Text: 301 TO 402F

Vapor Pres: >7.0 @ 38C

Vapor Density: 4.8

Spec Gravity: 0.87

Viscosity: 10"-25"

Evaporation Rate & Reference: SLOWER THAN BUTYL ACETATE

Solubility in Water: NEGLIGIBLE

Appearance and Odor: THIN LIQUID, MILD ODOR.

Percen

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES

AVOID CONTACT WITH STRONG OXIDIZING AGENTS, LEWIS OR MINERAL ACIDS.

Hazardous Decomposition Products: CARBON MONOXIDE AND CARBON DIOXIDE ARE PRODUCED ON COMBUSTION.

Conditions to Avoid Polymerization: AVOID EXCESSIVE HEAT, OPEN FLAME AND ALL IGNITION SOURCES.

===== Disposal Considerations =====

Waste Disposal Methods:

TREAT AS HAZARDOUS WASTE IF NOT POSSIBLE TO

RECLAIM. DISPOSE OF AT A LICENSED WASTE DISPOSAL COMPANY OR

INCINERATE W/APPROVAL OF ENVIRONMENTAL AUTHORITY. ALL DISPOSAL

PROCEDURES MUST COMPLY W/LOCAL, STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and

disclaims all liability for its use. Any person utilizing this

document should seek competent professional advice to verify and

assume responsibility for the suitability of this information to their

particular situation.