View NSN Online: https://aerobasegroup.gr/nsn/3439-00-262-2673

Product ID:BARE ROD OR WIRE MSDS Date:05/01/1991 FSC:3439 NIIN:00-262-2673 MSDS Number: BLHGR === Responsible Party === Company Name: HARRIS J W CO INC Address:10930 DEERFIELD RD. City:CINCINNATI State:OH ZIP:45242-4110 Country:US Info Phone Num:513-891-2000 Emergency Phone Num:800-424-9300 CAGE: JO820 === C ontractor Identification === Company Name: J. W. HARRIS CO., INC Address:10930 DEERFIELD RD Box:City:CINCINNATI State:OH ZIP:45242-4110 Country:US Phone:513-891-2000 CAGE: JO820 Company Name: J. W. HARRIS CO., INC. Address:10930 DEERFIELD ROAD Box:City:CINCINNATI State:OH ZIP:45242-4110 Country:US Phone:513-891-2000 CAGE:27911

Ingred Name:SILICON CAS:7440-21-3 RTECS #:VW0400000 Fraction by Wt: 0 - 13% Other REC Limits:NONE SPECI FIED OSHA PEL:15 MG/M3 TDUST ACGIH TLV:10 MG/M3 TDUST; 9293

Ingred Name:IRON CAS:7439-89-6 RTECS #:NO4565500 Other REC Limits:NONE SPECIFIED OSHA PEL:5 MG/M3 ACGIH TLV:10 MG/M3 AS FE2O3

Ingred Name:COPPER (SARA III) CAS:7440-50-8 RTECS #:GL5325000 Other REC Limits:NONE SPECIFIED OSHA PEL:0.1MG/M3 FUME/1 DUST ACGIH TLV:0.2MG/M3 FUME; 9192 EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS

Ingred Name:MANGANESE (SARA III) CAS:7439-96-5 RTECS #:OO9275000 Other REC Limits:NONE SPECIFIED OSHA PEL:(C) 5 M G/M3 DUST ACGIH TLV:5 MG/M3 DUST 9293

Ingred Name:MAGNESIUM CAS:7439-95-4 RTECS #:OM2100000 Fraction by Wt: 0 - 5.5% Other REC Limits:5 MG/M3 CEILING MFR

Ingred Name:CHROMIUM (SARA III) CAS:7440-47-3 RTECS #:GB4200000 Other REC Limits:NONE SPECIFIED OSHA PEL:1 MG/M3 ACGIH TLV:0.5 MG/M3; 9192 EPA Rpt Qty:1 LB DOT Rpt Qty:1 LB

Ingred Name:ZINC OXIDE CAS:1314-13-2 RTECS #:ZH4810000 Fraction by Wt: 0 - .25% Other REC Limits:NONE SPECIFIED OSHA PEL:15MG/M3 TDUST/5 FUME ACGIH TLV:10MG/M3 TDUST; 92 Ingred Name:TITANIUM, METAL CAS:7440-32-6 RTECS #:XR1700000 Other REC Limits:NONE SPECIFIED

Ingred Name:COBALT (SARA III) CAS:7440-48-4 RTECS #:GF8750000 Other REC Limits:NONE SPECIFIED OSHA PEL:0.1 MG/M3;AS CO ACGIH TLV:0.05 MG/M3;DUST 9293

Ingred Name:ALUMINUM (SARA III) CAS:7429-90-5 RTECS #:BD0330000 Other REC Limits:NONE SPECIFIED OSHA PEL:15MG/M3 DUST/5 FUME ACGIH TLV:10MG/M3 DUST; 9192

LD50 LC50 Mixture:TLV (AL UMINUM) 10 MG/M3 Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:YES Health Hazards Acute and Chronic: CENTRAL NERVOUS SYSTEM DISTURBANCES, RESPIRATORY TRACT IRRITATION, PULMONARY IRRITATION, PNEUMOCONIOSIS, SIDEROSIS, MEYAL FUME FEVER, ARC RAYS FROM ELECTRIC OPERATIONS CAN INJURE EYES AND BURN SKIN. E LECTRIC SHOCK FROM ARC WELDING EQUIPMENT CAN KILL. HEAT RAYS CAN INJURE EYES. Explanation of Carcinogenicity:CHROMIUM IS CONSIDERED TO BE A POSSIBLE CARCINOGEN. Effects of Overexposure: DISCOMFORT, DIZZINESS, NAUSEA, DRYNESS OF THROAT, FEVER, BODY ACHE, CHILLS. Medical Cond Aggravated by Exposure: INDIVIDUALS WITH IMPAIRED PULMONARY FUNCTIONS OR ILLNESS MAY HAVE SYMPTOMS EXACERBATED BY FUME IRRITANTS.

First Aid:REMOVE FROM DUST OR FUME EXPOSURE. IF BREATHING HAS STOPPED, PERFORM ARTIFICIAL RESPIRATION. SUMMON MEDICAL AID IMME

93

DIATELY.

Flash Point:NONFLAMMABLE
Lower Limits:NONFLAMMABLE
Upper Limits:NONFLAMMABLE
Extinguishing Media:NONFLAMMABLE. USE MEDIA SUITABLE FOR SURROUNDING FIRE.
Fire Fighting Procedures:NONFLAMMABLE. USE PROCEDURES SUITABLE FOR SURROUNDING FIRE.
Unusual Fire/Explosion Hazard:WELDING ARC, OPEN FLAME AND SPARKS CAN IGNITE COMBUSTIBLES.

Neutralizin

g Agent:NONE SPECIFIED BY MANUFACTURER.

Handling and Storage Precautions:NONE SPECIFIED BY MANUFACTURER. Other Precautions:WELDING AND BRAZING FUMES AND GASES CANNOT BE CLASSIFIED SIMPLY. THE COMPOSITION AND QUANTITY ARE DEPENDENT ON THE METAL BEING BRAZED, THE PROCESS, PROCEDURES, FILLER METALS, COATINGS ON THE METAL, NUM BER OF WELDERS, WORKSPACE, VENTILATION.

========= Exposure Controls/Personal Protection

=============

Respiratory Protection:USE RESPIRABLE FUME RESPIRATOR OR AIR SUPPLIED RESPIRATOR WHEN WELDING, BRAZING OR SOLDERING IN CONFINED SPACE OF WHERE LOCAL EXHAUST OR VENTILATION DOES NOT KEEP EXPOSURE BELOW THE TLV.

Ventilation: USE ENOUGH VENTILATION AND LOCAL EXHAUST AT THE FLAME OR ARC TO KEEP THE FUMES AND GASES OUT OF BREATHING ZONE.

Protective Gloves:WELDER'S GLOVES

Eye Protection:WELDING HELMET

Other Protective Equipment:PROTECTION SCREENS, FLASH GOGGLE, ARM P

ROTECTORS, APRONS, HATS, SHOULDER PROTECTION, AS WELL AS DARK SUBSTANTIAL CLOTHNG

Work Hygienic Practices: WASH WITH SOAP AND WATER AFTER HANDLIN PRODUCT AND BEFORE EATING, DRINKING OR SMOKING.

Supplemental Safety and Health

THE CONCENTRATION OF A GIVEN FUME OR GAS COMPONENT MAY DECREASE OR INCREASE BY MANY TIMES THE ORIGINAL CONCENTRATION IN THE FILLER METAL. ALSO, NEW COMPOUNDS MAY FORM. ACTUAL EXPOSURE SHOULD BE DETERM INED BY MONITORING FUME IN THE OPERATORS BREATHING ZONE

HCC:N1

Boiling Pt:B.P. Text:NOT GIVEN Melt/Freeze Pt:M.P/F.P Text:NOT GIVEN Vapor Pres:SOLID Vapor Density:SOLID Spec Gravity:NOT GIVEN Evaporation Rate & amp; Reference:NIL Solubility in Water:NEGLIGIBLE Appearance and Odor:SOLID WIRE Percent Volatiles by Volume:0 %

Stability Indicator/Materials to Avoid:YES NONE SPECIFIED BY MANUFACTURER. Stability Condi tion to Avoid:NONE SPECIFIED BY MANUFACTURER. Hazardous Decomposition Products:THE COMPOSITION & QUANTITY OF FUMES AND GASES ARE DEPENDENT UPON THE METAL BEING WELDED, THE PROCESS AND FILLER METALS.

Waste Disposal Methods: DISPOSE OF IN ACCORDANCE WITH ALL APPLICABLE STATE, LOCAL AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department

of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.